

**PUMP CAVITATION—
VARIOUS NPSHR CRITERIA, NPSHA MARGINS, IMPELLER LIFE EXPECTANCY**

by

Bruno Schiavello

Flowserve Pump Division

Director, Fluid Dynamics

Phillipsburg, New Jersey

and

Frank C. Visser

Flowserve Pump Division

Manager R&D

Etten-Leur, The Netherlands



Bruno Schiavello has been Director for Fluid Dynamics at Flowserve Pump Division, Applied Technology Department, in Phillipsburg, New Jersey, since 2000, and previously served in the same position with Ingersoll Dresser Pump Company. He started in the R&D Department of Worthington Nord (Italy), joined Central R&D of Worthington, McGraw Edison Company, and then Dresser Pump Division.

Mr. Schiavello was co-winner of the H. Worthington European Technical Award in 1979. He has written several papers and lectured at seminars in the area of pump recirculation, cavitation, and two-phase flow. He is a member of ASME, has received the ASME 2006 Fluid Machinery Design Award, and has served on the International Pump Users Symposium Advisory Committee since 1983.

Mr. Schiavello received a B.S. degree (Mechanical Engineering, 1974) from the University of Rome, and an M.S. degree (Fluid Dynamics, 1975) from Von Karman Institute for Fluid Dynamics.



Frank C. Visser is Manager R&D with Flowserve Pump Division, in Etten-Leur, The Netherlands. After joining Flowserve in 1995, he was assigned to the company's Brite-Euram research project on "Advanced and preventive diagnosis of fluid-handling rotating machinery using artificial excitation and dynamic parameter identification techniques (APHRODITE)," and has been involved with after-market activities dealing with hydraulic rerates and cavitation control strategy.

Dr. Visser has a B.S. degree and M.S. degree (Mechanical Engineering), and a Ph.D. degree (Technical Sciences) from the University of Twente, Enschede, The Netherlands. He is a member of the Dutch Royal Institution of Engineers, and is the author of several technical papers.

This paper was not available in time to be published.

