



(12) **United States Patent**
Holtzapple et al.

(10) **Patent No.:** **US 7,950,250 B2**
(45) **Date of Patent:** **May 31, 2011**

(54) **JET EJECTOR SYSTEM AND METHOD**

3,597,328 A * 8/1971 Michel 202/173
3,892,361 A 7/1975 Mocarski 239/432
4,152,898 A 5/1979 Awerbuch 60/641.5
4,379,734 A 4/1983 Franzen 159/17.1

(75) Inventors: **Mark T. Holtzapple**, College Station, TX (US); **Gary P. Noyes**, Houston, TX (US); **George A. Rabroker**, College Station, TX (US)

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignees: **Terrabon Adve, LLC**, Houston, TX (US); **The Texas A&M University System**, College Station, TX (US)

DE 1111 221 1/1955

(Continued)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 305 days.

Notification of Transmittal of the International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US04/030660, filed Sep. 20, 2005 (5 pages).

(21) Appl. No.: **11/972,013**

(Continued)

(22) Filed: **Jan. 10, 2008**

Prior Publication Data

Primary Examiner — Melvin Jones

US 2008/0253901 A1 Oct. 16, 2008

(74) *Attorney, Agent, or Firm* — Conley Rose, P.C.

Related U.S. Application Data

ABSTRACT

(62) Division of application No. 10/944,071, filed on Sep. 17, 2004, now Pat. No. 7,328,591.

According to one embodiment of the invention, a jet ejector method includes providing a primary jet ejector having a primary inlet stream, coupling one or more secondary jet ejectors to the primary jet ejector such that all of the jet ejectors are in a cascaded arrangement, bleeding off a portion of the primary inlet stream and directing the portion of the primary inlet stream to the secondary jet ejector that is closest to the primary jet ejector in the cascaded arrangement, and directing a motive fluid into the secondary jet ejector that is farthest from the primary jet ejector in the cascaded arrangement. The method further includes, at each secondary jet ejector, receiving at least some of the portion of the primary inlet stream and at least some of the motive fluid to create respective mixtures within the secondary jet ejectors, and at each secondary jet ejector, directing at least a portion of the respective mixture to adjacent jet ejectors in the cascaded arrangement.

(60) Provisional application No. 60/504,138, filed on Sep. 19, 2003.

(51) **Int. Cl.**
F25B 1/06 (2006.01)

(52) **U.S. Cl.** **62/500**

(58) **Field of Classification Search** 62/498,
62/500; 417/151


See application file for complete search history.

References Cited

U.S. PATENT DOCUMENTS

1,415,406 A 5/1922 Scanes
1,421,844 A 7/1922 Schmidt
2,941,787 A 6/1960 Ramén et al.

44 Claims, 39 Drawing Sheets



US 7,950,250 B2

Page 2

U.S. PATENT DOCUMENTS

4,696,625	A	9/1987	Greenberg	417/174
4,748,826	A *	6/1988	Laumen	65/268
4,803,958	A	2/1989	Erickson	122/21
5,837,096	A	11/1998	Fagerlind et al.	159/13.3
6,684,658	B2	2/2004	Holtzapfle et al.	62/268
6,904,769	B2 *	6/2005	Ogata et al.	62/500

FOREIGN PATENT DOCUMENTS

DE	3244761	A1	6/1983
DE	39 18 189		6/1989
DE	3924581		1/1991
DE	4019991		1/1992
EP	0193206	A1	2/1986
EP	0280676	A2	2/1988
EP	0411123	A1	2/1991
EP	0741241	A1	11/1996
FR	1050094		1/1954

FR	2230403	12/1974
FR	2505667	5/1981
FR	2545372	11/1984
GB	2054819	2/1981

OTHER PUBLICATIONS

PCT Invitation to Pay Additional Fees for International Application No. PCT/US04/030615, filed Sep. 20, 2004 (6 pages).

Notification of Transmittal of the International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US04/030619, filed Sep. 20, 2005 (16 pages).

Communication Pursuant to Article 94(3) EPC, Application No. 04 784 508.6-1266; Ref JL31713P.EPP, 3 pages, Aug. 24, 2009.

Examination Report dated Jan. 8, 2010 issued by the European Patent Office in corresponding EP Application No. 04 784 470.9, 4 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 4




FIG. 5




FIG. 6





FIG. 7






FIG. 8




FIG. 9
(AR=5)




FIG. 10
(AR=4)




FIG. 11
(AR=3)




FIG. 13
(AR=4)




FIG. 12
(AR=5)




FIG. 14
(AR=3)




FIG. 15
(AR=5)




FIG. 16
(AR=4)




FIG. 17
(AR=3)




FIG. 18
(AR=5)




FIG. 19
(AR=4)




FIG. 20
(AR=3)




FIG. 21






FIG. 22



90




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31
















FIG. 32












FIG. 43






FIG. 45






FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57A




FIG. 57B




FIG. 57C




FIG. 58A




FIG. 58B




FIG. 58D




FIG. 58C




FIG. 59A




FIG. 59B




FIG. 59C




FIG. 59D




FIG. 59E




FIG. 60A




FIG. 60B




FIG. 61A




FIG. 61B




FIG. 61C




FIG. 61D

JET EJECTOR SYSTEM AND METHOD

RELATED APPLICATIONS

This application is a divisional of U.S. application Ser. No. 10/944,071, filed Sep. 17, 2004, now U.S. Pat. No. 7,328,591. U.S. application Ser. No. 10/944,071 claims priority from U.S. Provisional Application No. 60/504,138, filed Sep. 19, 2003.

TECHNICAL FIELD OF THE INVENTION

The present invention relates generally to the field of jet ejectors and, more particularly, to an improved, ultra-high efficiency jet ejector system and method.

BACKGROUND OF THE INVENTION

Typical steam jet ejectors feed high-pressure steam, at relatively high velocity, into the jet ejector. Steam is usually used as the motive fluid because it is readily available; however, an ejector may be designed to work with other gases or vapors as well. For some applications, water and other liquids are sometimes good motive fluids as they condense large quantities of vapor instead of having to compress them. Liquid motive fluids may also compress gases or vapors.

The motive high-pressure steam enters a nozzle and issues into the suction head as a high-velocity, low-pressure jet. The nozzle is an efficient device for converting the enthalpy of high-pressure steam or other fluid into kinetic energy. A suction head connects to the system being evacuated. The high-velocity jet issues from the nozzle and rushes through the suction head.

Gases or vapors from the system being evacuated enter the suction head where they are entrained by the high-velocity motive fluid, which accelerates them to a high velocity and sweeps them into the diffuser. The process in the diffuser is the reverse of that in the nozzle. It transforms a high-velocity, low-pressure jet stream into a high-pressure, low-velocity stream. Thus, in the final stage, the high-velocity stream passes through the diffuser and is exhausted at the pressure of the discharge line.

SUMMARY OF THE INVENTION

According to one embodiment of the invention, a jet ejector method includes providing a primary jet ejector having a primary inlet stream, coupling one or more secondary jet ejectors to the primary jet ejector such that all of the jet ejectors are in a cascaded arrangement, bleeding off a portion of the primary inlet stream and directing the portion of the primary inlet stream to the secondary jet ejector that is closest to the primary jet ejector in the cascaded arrangement, and directing a motive fluid into the secondary jet ejector that is farthest from the primary jet ejector in the cascaded arrangement. The method further includes, at each secondary jet ejector, receiving at least some of the portion of the primary inlet stream and at least some of the motive fluid to create respective mixtures within the secondary jet ejectors, and at each secondary jet ejector, directing at least a portion of the respective mixture to adjacent jet ejectors in the cascaded arrangement.

According to another embodiment of the invention, a jet ejector includes a nozzle having a first stream flowing there-through and including an upstream portion, a downstream portion, and a throat disposed between the upstream portion and the downstream portion, a plurality of sets of apertures

located in a wall of the nozzle in the throat, wherein the plurality of sets are longitudinally spaced along the wall and each set of apertures having its apertures circumferentially located around the wall, and a device operable to inject a motive fluid through the apertures and into the first stream.

Embodiments of the invention provide a number of technical advantages. Embodiments of the invention may include all, some, or none of these advantages. An advantage of a jet ejector system according to one embodiment of the invention is that it blends gas streams of similar pressures; therefore, the velocity of each gas stream is similar. This leads to high efficiencies, even using traditional jet ejectors. The efficiency may be improved further by improving the design of the jet ejector.

A jet ejector according to one embodiment of the invention blends gas streams of similar velocities, but does not obstruct the flow of the propelled gas. This jet ejector may be used in many applications, such as compressors, heat pumps, water-based air conditioning, vacuum pumps, and propulsive jets (both for watercraft and aircraft).

An advantage of another jet ejector system according to one embodiment of the invention is it uses a high-efficiency liquid jet ejector in a cost-effective dewatering system. When combined with steam jet ejectors and multi-effect evaporators, any energy inefficiencies of the liquid jet system (liquid jet itself, pump, turbine) produce heat that usefully distills liquid. This liquid jet ejector may be used in water-based air conditioning.

In other embodiments, a heat exchanger is designed to facilitate a lower pressure drop than existing heat exchangers at low cost. Such a heat exchanger may include a plurality of plates (or sheets) inside a tube. The plates may be made of any suitable material; however, for some embodiments in which corrosion is a concern, the plates may be made of a suitable polymer.

Other technical advantages are readily apparent to one skilled in the art from the following figures, descriptions, and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the invention, and for further features and advantages, reference is now made to the following description, taken in conjunction with the accompanying drawings, in which:

FIG. 1 illustrates a low-pressure vapor-compression evaporator system;

FIG. 2 illustrates a medium-pressure vapor-compression evaporator system;

FIG. 3 is a graphical correlation for standard jet ejectors;

FIG. 4 illustrates P_{motive}/P_{inlet} (the inverse of the y-axis in FIG. 3) as a function of compression ratio (P_{outlet}/P_{inlet}) for each area ratio, AR;

FIG. 5 illustrates the slopes of FIG. 4 on a log-log graph;

FIG. 6 illustrates m_{motive}/m_{inlet} (the inverse of the x-axis in FIG. 3) as a function of compression ratio (P_{outlet}/P_{inlet}) for each area ratio, AR;

FIG. 7 illustrates the slopes of FIG. 6 on a log-log graph;

FIG. 8 illustrates a jet ejector system according to one embodiment of the invention;

FIGS. 9 through 20 illustrate the pressures and mass flows (using arbitrary units) according to various embodiments of the invention;

FIGS. 21 through 31 illustrate various jet ejector systems according to various embodiments of the invention;

FIG. 32 illustrates a jet ejector according to one embodiment of the invention;

FIG. 33 illustrates a jet ejector according to another embodiment of the invention;

FIGS. 34 and 35 illustrate a jet ejector according to another embodiment of the invention;

FIG. 36 illustrates a pattern of nozzle ducts according to one embodiment of the invention;

FIG. 37 illustrates a liquid jet ejector according to one embodiment of the invention;

FIG. 38 illustrates a liquid jet ejector according to another embodiment of the invention;

FIG. 39 illustrates a liquid jet ejector according to another embodiment of the invention;

FIG. 40 illustrates a liquid jet ejector according to another embodiment of the invention;

FIG. 41 illustrates a liquid jet ejector according to another embodiment of the invention;

FIGS. 42 through 51 illustrate various embodiments of an evaporator system that incorporates a liquid jet ejector according to various embodiments of the invention;

FIGS. 52 through 55 illustrate various embodiments of a vapor-compression evaporator system according to various embodiments of the invention;

FIG. 56 illustrates a cross-section of an example heat exchanger assembly including a shell and a sheet assembly disposed within the shell in accordance with an embodiment of the invention;

FIG. 57A illustrates a three-dimensional view of the sheet assembly of the heat exchanger assembly of FIG. 56 in accordance with one embodiment of the invention;

FIG. 57B is a blown-up view of a corner area of the sheet assembly of FIG. 57A in accordance with an embodiment of the invention;

FIG. 57C illustrates a side view of the corner of sheet assembly illustrated in FIG. 57B;

FIGS. 58A-58D illustrate an example method of forming a particular sheet of the sheet assembly shown in FIG. 57A in accordance with one embodiment of the invention;

FIGS. 59A-E illustrates various example manners for coupling the flange portions of adjacent sheets of the sheet assembly shown in FIG. 57A in accordance with one embodiment of the invention;

FIG. 60A illustrates a method of aligning the molecules in a polymer for making polymer sheets in accordance with one embodiment of the invention;

FIG. 60B illustrates a method of forming a sheet for a sheet assembly by joining a number of polymer sheets in accordance with one embodiment of the invention; and

FIGS. 61A-61D illustrates another example sheet assembly in accordance with another embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates a low-pressure vapor-compression evaporator system 2 performing desalination of salt water. A salt-containing feed 3 flows into an evaporator tank 4, which in this embodiment is operated under vacuum. Although, in the illustrated embodiment, feed 3 is a salt-containing feed, a sugar-containing feed or suitable feed is also contemplated by the present invention. The salt-containing feed 3 boils, producing low-pressure vapors. These vapors are removed from evaporator tank 4 using a jet ejector 5. The pressurized vapors exiting jet ejector 5 flow into a heat exchanger 6, where they condense. Because of the interaction of heat exchanger 6 and evaporator tank 4, the heat of condensation provides the heat of evaporation needed by the salt-containing feed 3. Distilled liquid water 7 is recovered from heat exchanger 6 in any suitable manner, and concentrated salt solution 8 is removed

from evaporator tank 4 using any suitable devices. The motive steam 9 added to jet ejector 5 may be condensed against cooling water; however, this condensation step may be eliminated if the product water is removed at a higher temperature than the feed water. A small vapor stream may be removed from evaporator tank 4 and sent to a condenser 10 to remove water vapor. The remaining gas is primarily noncondensibles, which may be removed using a vacuum pump (not explicitly illustrated).

FIG. 2 illustrates a medium-pressure vapor-compression evaporator system 20 according to an embodiment of the invention. System 20 operates similarly to system 2 in FIG. 1, except that an evaporator tank 22 operates at a moderate pressure, for example one atm. A motive steam 23 is added to a jet ejector 24 and exits evaporator tank 22 at moderate pressure and is useful for evaporating water. In the embodiment illustrated in FIG. 2, this medium-pressure steam may be used in a multi-effect evaporator 26, although a multi-stage flash evaporator may be used as well.

In the illustrated embodiment, multi-effect evaporator 26 includes any suitable number of tanks 27a, 27b, 27c in series each containing a feed 28 having a nonvolatile component, such as salt or sugar. Jet ejector 24 coupled to evaporator tank 22 and receives a vapor from evaporator tank 22. A heat exchanger 29 in evaporator tank 22 receives the vapor from jet ejector 24 where at least some of the vapor condenses therein. The heat of condensation provides the heat of evaporation to evaporator tank 22. At least some of the vapor inside evaporator tank 22 is delivered to a heat exchanger 30a in tank 27a, whereby the condensing, evaporating, and delivering steps continue through each tank until the last tank in the series (in this embodiment, tank 27c) is reached.

System 20 may also include a condenser 32 coupled to tank 27c for removing energy from system 20, and a vacuum pump (not illustrated) for removing noncondensibles from system 20. Any suitable devices may be utilized for removing concentrated feed 33 from tanks 22 and 27a-27c, and a plurality of sensible heat exchangers 34 may be coupled to tanks 22 and 27a-27c for heating the feed 28 before entering the tanks 22, 27a-27c. Sensible heat exchangers 34 may also be utilized for other suitable functions.

The pressure difference between the condensing steam and the boiling feed 28 depends upon the temperature difference between heat exchanger 29 and evaporator tank 22. In addition, salts (or other soluble materials) depress the vapor pressure, which increases the pressure difference even further. Table 1 illustrates the required compression ratio for pure water (i.e., no salt) as a function of the temperature difference.

TABLE 1

Required compression ratio for water as a function of temperature difference across the heat exchanger		
Temperature Difference (° C.)	Compression Ratio $T_{evaporator} = 100^{\circ} C.$	Compression Ratio $T_{evaporator} = 25^{\circ} C.$
1	1.0362	1.0612
2	1.0735	1.1256
3	1.1119	1.1934
4	1.1514	1.2647
5	1.1921	1.3397
6	1.2340	1.4185
7	1.2770	1.5013
8	1.3210	1.5883

The required temperature difference depends upon the cost of heat exchangers and the cost of capital. In one embodiment, a temperature difference of 5° C. is considered economical. For

a medium-pressure vapor-compression evaporator, such as system 20, the required compression ratio is approximately 1.2.

FIG. 3 illustrates a correlation for conventional jet ejectors. Table 2 illustrates the properties of a conventional jet ejector, based upon FIG. 3. Table 2 illustrates that using an area ratio of 100, 15.38-atm (226-psi) steam is able to evaporate 6.3 kg of water per kg of steam. Using system 20 (FIG. 2) as an example, the steam exits the evaporator tank 22 at 1 atm and can evaporate more water in multi-effect evaporators 26 or a multi-stage flash evaporator. In industry, multi-stage flash evaporators typically evaporate 8 kg of water per kg of steam, so the entire medium-pressure vapor-compression system 20 can evaporate about 14 kg of distilled water per kg of steam. If the efficiency of jet ejector 24 can be improved, then the yield of distilled water may improve further.

TABLE 2

Required pressure and motive steam consumption for $\Delta T = 5^\circ \text{C}$. and $T_{\text{evaporator}} = 100^\circ \text{C}$.				
Compression Ratio	Area Ratio	$\frac{P_{\text{inlet}}}{P_{\text{motive}}}$	P_{motive} (atm)	$\frac{m_{\text{inlet}}}{m_{\text{motive}}}$
1.2	100	0.065	15.38	6.3
1.2	50	0.115	8.70	5.7
1.2	25	0.200	5.00	4.5

For optimization purposes, it is desirable to find equations that present the same information. FIG. 4 illustrates $\frac{P_{\text{motive}}}{P_{\text{inlet}}}$ (the inverse of the y-axis in FIG. 3) as a function of compression ratio ($\frac{P_{\text{outlet}}}{P_{\text{inlet}}}$) for each area ratio, AR. As illustrated, each line is straight in FIG. 4. FIG. 5 illustrates the slopes versus area ratio on a log-log graph. From FIGS. 4 and 5, the following equation relates the parameters:

$$\frac{P_{\text{motive}}}{P_{\text{inlet}}} = 1 + 0.9848(AR)^{0.9072} \left(\frac{P_{\text{outlet}}}{P_{\text{inlet}}} - 1 \right) \quad (1)$$

FIG. 6 illustrates $\frac{m_{\text{motive}}}{m_{\text{inlet}}}$ (the inverse of the x-axis in FIG. 3) as a function of compression ratio ($\frac{P_{\text{outlet}}}{P_{\text{inlet}}}$) for each area ratio, AR. Again, the lines are straight. FIG. 7 illustrates the slopes versus area ratio on a log-log graph. From FIGS. 6 and 7, the following equation relates the parameters:

$$\frac{m_{\text{motive}}}{m_{\text{inlet}}} = 5.1179(AR)^{-0.4112} \left(\frac{P_{\text{outlet}}}{P_{\text{inlet}}} - 1 \right) \quad (2)$$

One reason jet ejectors may be inefficient is because they blend two gas streams with widely different velocities, which may occur when the motive pressure is significantly different from the inlet pressure. Thus, according to the teachings of one embodiment of the invention, the efficiency of jet ejectors may be improved substantially by developing jet ejectors and/or jet ejector systems that accomplish the required compression task by minimizing $\frac{P_{\text{motive}}}{P_{\text{inlet}}}$

FIGS. 8 through 31 illustrate various embodiments of an improved design of a ultrahigh-efficiency jet ejector system that allows motive gas and propelled gas to be blended in a manner that minimizes the velocity differences between the two streams, thus optimizing efficiency. Some embodiments may also allow for the energy to be added in the form of work, rather than heat, which increases efficiency even further.

FIG. 8 illustrates a jet ejector system 50, according to one embodiment of the invention, that minimizes $\frac{P_{\text{motive}}}{P_{\text{inlet}}}$. In the illustrated embodiment, system 50 includes a primary jet ejector 52 and one or more secondary jet ejectors 56a, 56b, 56c coupled to primary jet ejector 52 such that all of the jet ejectors are in a cascaded arrangement. As illustrated by various embodiments below in conjunction with FIGS. 9-31, this cascaded arrangement may be any suitable network of secondary jet ejectors 56 that receive a portion of a primary inlet stream 54 from primary jet ejector 52 and a motive steam 58 and process these streams before feeding a portion of the mixture of these streams back to primary jet ejector 52 for creation of primary outlet stream 55. Primary jet ejector 52 is analogous to jet ejector 5 of FIG. 1 or jet ejector 24 of FIG. 2.

In FIG. 8, a portion of primary inlet stream 54 is bled off and directed to secondary jet ejector 56a and, as described above, motive steam 58 is directed into secondary jet ejector 56c. At each secondary jet ejector 56, at least some of the portion of primary inlet stream 54 and at least some of motive steam 58 is received to create respective mixtures within secondary jet ejectors 56. And at each secondary jet ejector 56 at least a portion of the respective mixture is directed to adjacent jet ejectors (56 or 52) in the cascaded arrangement.

For various embodiments of the invention utilizing the concept of FIG. 8, Tables 3 through 6 show the required $\frac{P_{\text{motive}}}{P_{\text{inlet}}}$ (Equation 1) and the resulting $\frac{m_{\text{motive}}}{m_{\text{inlet}}}$ (Equation 2) for each secondary jet ejector (also referred to as a stage) in the cascade. FIGS. 9 through 20 illustrate the pressures and mass flows for each embodiment shown. Because any suitable operating parameters are contemplated by the present invention, the pressure units and mass units are arbitrarily shown in FIGS. 9 through 20; however, it may be convenient to use atmospheres for pressure and kilograms for mass.

TABLE 3

Analysis of jet ejector for compression ratio of 1.03.				
Area Ratio	Stage	$\frac{P_{\text{outlet}}}{P_{\text{inlet}}}$	$\frac{P_{\text{motive}}}{P_{\text{inlet}}}$	$\frac{m_{\text{motive}}}{m_{\text{inlet}}}$
5	1	1.03	1.127	0.079
	2	1.13	1.539	0.335
	3	1.37	2.552	0.966
	4	1.86	4.647	2.271
	5	2.49	7.319	3.934
4	1	1.03	1.104	0.087
	2	1.10	1.360	0.301
	3	1.23	1.804	0.671
	4	1.46	2.607	1.343
	5	1.78	3.704	2.260
	6	2.08	4.741	3.126
	7	2.28	5.427	3.699
3	1	1.03	1.080	0.098
	2	1.08	1.213	0.261
	3	1.12	1.331	0.404
	4	1.33	1.883	1.078
	5	1.41	2.105	1.349
	6	1.49	2.300	1.588
	7	1.55	2.457	1.779
	8	1.59	2.571	1.919
	9	1.62	2.649	2.013

7

TABLE 4

Analysis of jet ejector for compression ratio of 1.05.				
Area Ratio	Stage	$\frac{P_{outlet}}{P_{inlet}}$	$\frac{P_{motive}}{P_{inlet}}$	$\frac{m_{motive}}{m_{inlet}}$
5	1	1.05	1.212	0.132
	2	1.21	1.899	0.560
	3	1.57	3.405	1.497
	4	2.17	5.975	3.097
	5	2.75	8.421	4.621
4	1	1.05	1.173	0.145
	2	1.17	1.599	0.501
	3	1.36	2.257	1.051
	4	1.66	3.269	1.896
	5	1.97	4.374	2.819
3	6	2.21	5.205	3.514
	1	1.05	1.133	0.163
	2	1.13	1.355	0.433
	3	1.20	1.523	0.638
	4	1.27	1.731	0.893
	5	1.36	1.958	1.169
	6	1.44	2.173	1.433
	7	1.51	2.358	1.658
	8	1.56	2.499	1.831
	9	1.6	2.601	1.955

TABLE 5

Analysis of jet ejector for compression ratio of 1.1.				
Area Ratio	Stage	$\frac{P_{outlet}}{P_{inlet}}$	$\frac{P_{motive}}{P_{inlet}}$	$\frac{m_{motive}}{m_{inlet}}$
5	1	1.10	1.424	0.264
	2	1.42	2.798	1.120
	3	1.97	5.092	2.548
	4	2.59	7.751	4.204
4	1	1.10	1.346	0.289
	2	1.35	2.198	1.001
	3	1.63	3.193	1.832
	4	1.96	4.308	2.764
	5	2.20	5.170	3.485
3	1	1.10	1.267	0.326
	2	1.27	1.712	0.869
	3	1.35	1.936	1.143

8

TABLE 5-continued

Analysis of jet ejector for compression ratio of 1.1.				
Area Ratio	Stage	$\frac{P_{outlet}}{P_{inlet}}$	$\frac{P_{motive}}{P_{inlet}}$	$\frac{m_{motive}}{m_{inlet}}$
5	4	1.43	2.156	1.412
	5	1.50	2.345	1.642
	6	1.56	2.491	1.821
10	7	1.60	2.595	1.948
	8	1.63	2.668	2.036

TABLE 6

Analysis of jet ejector for compression ratio of 1.2				
Area Ratio	Stage	$\frac{P_{outlet}}{P_{inlet}}$	$\frac{P_{motive}}{P_{inlet}}$	$\frac{m_{motive}}{m_{inlet}}$
5	1	1.20	1.848	0.528
	2	1.85	4.596	2.239
	3	2.49	7.306	3.926
4	4	2.94	9.215	5.115
	1	1.20	1.693	0.579
	2	1.69	3.400	2.006
	3	2.01	4.491	2.917
25	4	2.24	5.281	3.577
	5	2.36	5.718	3.942
	1	1.20	1.534	0.652
	2	1.53	2.422	1.736
	3	1.58	2.545	1.886
30	4	1.61	2.630	1.990
	5	1.63	2.686	2.059
	6	1.65	2.724	2.104
	7	1.66	2.748	2.134

Table 7 illustrates the mass yield for various embodiments. The results indicate that the method works best when the per-stage compression ratio is small, which requires more stages. Further, the method works best when the area ratio is small, which also requires more stages. More stages allow the inlet pressures and motive pressures to be closely matched, thereby allowing streams with similar velocities to be blended. In some embodiments, extraordinarily high mass yields (kg water/kg steam) are possible.

TABLE 7

Case studies for vapor-compression distillation. ($T_{evaporator} = 100^{\circ} \text{C.}$)						
AT ($^{\circ} \text{C.}$)	Overall Compression Ratio	Per-Stage Compression Ratio	Number of Stages	Area Ratio	Per-Stage Mass Yield (kg water/kg steam)	Overall Mass Yield (kg water/kg steam)
5	1.2	1.03	6	5	119	19.8
				4	190	31.6
			3	425	70.8	
		1.05	4	5	37.1	9.3
				4	49.3	12.3
			3	138	34.5	
	1.10	2	5	11.1	5.55	
			4	11.5	5.75	
		3	18.2	9.10		
	1.20	1	5	3.58	3.58	
			4	3.72	3.72	
		3	4.48	4.48		

An advantage of utilizing a cascaded arrangement of jet ejectors, such as jet ejector system **50**, is that it blends gas streams of similar pressures; therefore, the velocity of each gas stream is similar. This leads to high efficiencies, even using traditional jet ejectors. Efficiency may be improved further by improving the design of the jet ejector, as is described in further detail below.

FIG. **21** illustrates a jet ejector system **60** according to another embodiment of the invention. In system **60**, a portion of a primary outlet stream **61** from primary jet ejector **62** is bled off and directed to one or more secondary jet ejectors **63**. This is in contrast to system **50** of FIG. **8** in which a portion of primary inlet stream **54** was bled off. The rest of system **60** work in a similar manner to system **50**.

FIG. **22** illustrates a jet ejector system **70** according to another embodiment of the invention. In system **70**, a high-pressure steam, as indicated by reference numeral **71**, that powers the cascade of jet ejectors is produced by drawing a side stream **72** from one of the jet ejectors and compressing it with a suitable mechanical compressor **73**. In this case, the compressor is powered by a suitable steam turbine **74** via shaft **75**. The waste steam **76** from turbine **74** may provide motive power to one or more of the jet ejectors, such as primary jet ejector **77**.

FIG. **23** illustrates a jet ejector system **80** according to another embodiment of the invention. System **80** is similar to system **70** except that in system **80** a compressor **81** is powered by a Brayton cycle engine **82** or other suitable engine. A suitable electric motor may also be utilized to power compressor **81**.

FIG. **24** illustrates a jet ejector system **90** according to another embodiment of the invention. In system **90**, multiple compression stages are employed by a plurality of primary jet ejectors **91a**, **91b**, **91c** in series. Each primary jet ejector **91** is supported by its own independent cascade of secondary jet ejectors, which may operate according to one of the embodiments described above in FIGS. **8**, **21**, **22** and/or **23**.

FIG. **25** illustrates a jet ejector system **100** according to another embodiment of the invention. In system **100**, multiple compression stages are employed by a plurality of primary jet ejectors **101a**, **101b**, **101c** in series. However, system **100** differs from system **90** of FIG. **24** in that some of the high-pressure secondary jet ejectors **102** from one cascade are shared with other primary jet ejectors **101** in the series. This reduces the number of secondary jet ejectors, thereby saving capital costs.

FIG. **26** illustrates a jet ejector system **110** according to another embodiment of the invention. In system **110**, multiple compression stages are employed by a plurality of primary jet ejectors **111a**, **111b**, **111c** in series. In this embodiment, only the first primary jet ejector **111a** in the series includes a cascade **112** of jet ejectors; however, each of the other primary jet ejectors **111b**, **111c** receive a stream from one of the secondary jet ejectors from cascade **112** (in this example, secondary jet ejector **112a**). This again helps reduce the number of jet ejectors, thereby saving capital costs.

FIG. **27** illustrates a jet ejector system **120** according to another embodiment of the invention. In system **120**, multiple compression stages are employed by a plurality of primary jet ejectors **121a**, **121b**, **121c** in series. In this embodiment, only the last primary jet ejector **121c** in the series includes a cascade **122** of jet ejectors; however, each of the other primary jet ejectors **121a**, **121b** receive a stream from one of the secondary jet ejectors from cascade **122** (in this example, secondary jet ejector **122a**). In addition, secondary jet ejector **122a** is receiving a portion of outlet stream **124** from primary jet ejector **121c**.

FIG. **28** illustrates a jet ejector system **130** according to another embodiment of the invention. In system **130**, multiple compression stages are employed by a plurality of primary jet ejectors **131a**, **131b**, **131c** in series. And an equal number of stages of secondary jet ejectors are included in each cascade. The secondary jet ejectors that comprise a particular stage are in series. In this embodiment, the stream for the cascades is drawn from a primary inlet stream **132** of the first primary jet ejector **131a**.

FIG. **29** illustrates a jet ejector system **140** according to another embodiment of the invention. System **140** is similar to system **130**, except the stream for the cascades is drawn from a primary outlet stream **142** of a primary jet ejector **141c** in the series.

FIGS. **30** and **31** illustrate jet ejector systems **150**, **160**, respectively, according to other embodiments of the invention. Systems **150**, **160** are similar to systems **130**, **140**, respectively; however, the flow arrangement in systems **150**, **160** obtains a closer match of motive pressures to inlet pressures. Other suitable arrangements of both primary and secondary jet ejectors as well as arrangement of cascades are contemplated by the present invention.

Thus, an advantage of the jet ejector systems described above is that they blend gas streams of similar pressures; therefore, the velocity of each gas stream is similar. This leads to high efficiencies, even using traditional jet ejectors. The efficiency may be improved further by improving the design of the jet ejector, some embodiments of which are described below in conjunction with FIGS. **32** through **41**.

FIGS. **32** through **36** illustrate various embodiments of an improved design of a jet ejector that allows large volumes of motive fluid to be added to propelled gas without obstructing the flow of the propelled gas.

FIG. **32** illustrates a jet ejector **200** according to one embodiment of the invention. Jet ejector **200** may have any suitable size and shape and may be formed from any suitable material. In the illustrated embodiment, jet ejector **200** includes a nozzle **202** having an upstream portion **203**, a downstream portion **204**, and a throat **205** disposed between upstream portion **203** and downstream portion **204**. A plurality of sets of apertures **206** are located in a wall of nozzle **202** in throat **205**, in which the plurality of sets are longitudinally spaced along the wall. Each set of apertures **206** has its apertures circumferentially located around the wall in any suitable pattern and spacing. Apertures **206** may be any suitably shaped apertures. For example, in the illustrated embodiment, apertures are in the form of circumferential slots. Jet ejector **200** also includes a device (not explicitly shown) that is operable to inject a motive fluid **207** through apertures **206** and into a first stream **208** flowing through nozzle **202**. Motive fluid **207** may be any suitable motive fluid, such as gas, vapor, liquid, and may be supplied through an annular space **211** in the wall of nozzle **202**. In such an embodiment, the pressure of motive gas **207** entering each set of apertures **206** is constant. In addition, motive fluid **207** enters first stream **208** at an angle with respect to the flow direction of first stream **208**.

In operation, first stream **208**, which may be any suitable propelled gas, such as low pressure vapor, enters upstream portion **203** of nozzle **202**. Throat **205** then initially accelerates first stream **208** when it enters throat **205**. The motive fluid **207** accelerates first stream **208** even further after entering throat **205** via apertures **206**. To minimize the velocity difference between motive fluid **207** and first stream **208**, it is advantageous to have the upstream most set of apertures **206a** accelerate first stream **208** first, then the next set of apertures **206b** accelerate first stream **208** second, and then the next set

of apertures **206c** accelerate first stream **208** last. The size of arrows **212** is meant to illustrate the accelerating of first stream **208** through nozzle **202**.

FIG. **33** illustrates a jet ejector **220** according to another embodiment of the invention. Jet ejector **220** is similar to jet ejector **200**; however, in this embodiment, jet ejector **220** includes sets of apertures **226** in which each successive set of apertures **226** (as their location is farther downstream) is fed with a motive fluid **227** at increasingly higher pressures, which allows motive gas **227** exiting the later set of apertures **206** to have increasingly larger velocities. Thus, set of apertures **226c** has a greater pressure than set of apertures **226b**, which has a greater pressure than set of apertures **226c**. Because a first stream **228** also has increasingly larger velocities, jet ejector **220** minimizes the velocity difference between the two streams, thereby improving efficiency.

FIGS. **34** through **36** illustrates a jet ejector **230** according to another embodiment of the invention. In this embodiment, a motive gas **237** enters a throat **235** of nozzle **232** through multiple point sources **236**, rather than through circumferential slots as in jet ejectors **200**, **220**. Multiple point sources **236** may have any suitable configuration but are preferably small holes or slots. FIG. **35A** is a cross-sectional view through the wall of throat **235** illustrating one of the point sources **236**. FIG. **35B** illustrates a frontal view of the interior wall of throat **235**. As illustrated, point source **236** is coupled to a fan-shaped duct **239** that is defined by walls diverging in a downstream direction in order to introduce motive fluid **237** into throat **235** to entrain first stream **238** (i.e., propelled gas) flowing through nozzle **232**. In one embodiment, fan-shaped duct **239** is a NACA duct. FIG. **36** is a two-dimensional view of the interior wall of nozzle **232** showing a staggered arrangement of multiple fan-shaped ducts **239**. However, the present invention contemplates any suitable arrangement of fan-shaped ducts **239**.

Thus, an advantage of the jet ejectors described in FIGS. **32** through **36** is that they blend gas streams of similar velocities, but do not obstruct the flow of the propelled gas. These jet ejectors may be used in any suitable application, such as compressors, heat pumps, water-based air conditioning, vacuum pumps, and propulsive jets (both for watercraft and aircraft).

FIGS. **37** through **41** illustrate various embodiments of an improved design of a liquid jet ejector that allows motive liquid to be added to the propelled gas without obstructing the flow of the propelled gas. In some embodiments, the motive liquid may be added in stages, which increases efficiency.

FIG. **37** illustrates a liquid jet ejector **250** according to one embodiment of the invention. Liquid jet ejector **250** is similar to jet ejector **200** (FIG. **32**); however, the motive fluid in liquid jet ejector **250** is liquid. In operation, a first stream **258**, which may be any suitable propelled gas, such as low pressure vapor, enters an upstream portion **253** of nozzle **252**. A throat **255** then initially accelerates first stream **258** when it enters throat **255**. The motive fluid **257** accelerates first stream **258** even further after entering throat **255** via nozzles **256**. To minimize the velocity difference between motive fluid **257** and first stream **258**, it is advantageous to have the upstream most set of nozzles **256a** accelerate first stream **258** first, then the next set of apertures **256b** accelerate first stream **258** second, and then the next set of apertures **256c** accelerate first stream **258** last. The size of arrows **251** is meant to illustrate the accelerating of first stream **258** through nozzle **252**. The motive liquid **257** may be supplied via an annular space **259** formed in the wall of nozzle **252**. Alternatively, each nozzle **256** could be supplied by its own pipe. In this embodiment, the pressure of the motive fluid **257** entering each nozzle **256** is constant.

Similar to apertures **206** of jet ejector **200**, nozzles **256** may be circumferentially located around the wall in any suitable pattern and spacing.

FIG. **38** illustrates a liquid jet ejector **260** according to one embodiment of the invention. Liquid jet ejector **260** is similar to jet ejector **220** (FIG. **33**); however, the motive fluid in liquid jet ejector **260** is liquid and liquid jet ejector **260** includes nozzles **266** similar to nozzles **256** of liquid jet ejector **250** of FIG. **37**.

FIG. **39** illustrates a liquid jet ejector **270** according to one embodiment of the invention. Liquid jet ejector **270** is similar to liquid jet ejector **250**, except that the motive liquid **277** enters a throat **275** of nozzle **272** through small tubes **276** that are tipped with nozzles. This embodiment facilitates the velocity of motive liquid **277** exiting the nozzles to be parallel to the velocity of a first stream **278** (i.e., the propelled fluid). Any suitable number and arrangement of tubes **276** is contemplated by the present invention.

FIG. **40** illustrates a liquid jet ejector **280** according to one embodiment of the invention. Liquid jet ejector **280** is similar to liquid jet ejector **270** except that the motive liquid **287** enters a throat **285** via tubes **286** at increasingly higher pressures as their location is farther downstream, which allows motive fluid **287** exiting the later set of tubes **286c** to have increasingly larger velocities. Thus, motive fluid **287** exiting tubes **286c** has a greater pressure than motive fluid **287** exiting tubes **286b**, which has a greater pressure than motive fluid **287** exiting tubes **286a**.

FIG. **41** illustrates a liquid jet ejector **290** according to one embodiment of the invention. Liquid jet ejector **290** includes a plurality of receptacles **291** coupled to the wall of nozzle **292** in order to collect the motive liquid **297**, thereby allowing the liquid to be readily collected and recycled. Receptacles **291** may be any suitable size and shape and are preferably located directly downstream from the nozzles of tubes **296**. The kinetic energy of the exiting liquid converts to pressure at the inlet to the pump, which reduces the required work input to the pump, thereby increasing efficiency. Although FIG. **41** illustrates only one liquid stage along the axial length of nozzle **292**, multiple liquid stages may be employed.

Thus, advantages of the liquid jet ejectors of FIGS. **37** through **41** are as follows: (1) the motive liquid may be added in stages, which increases system efficiency, and (2) the path of the propelled gas may be largely unobstructed by the nozzles that supply the motive liquid. These liquid jet ejectors may be used in any suitable applications, including compressors, heat pumps, water-based air conditioning, vacuum pumps, and vapor compression evaporators. Rather than propelling a gas, they could also be used to propel a liquid. If the outlet area of the jet ejector is less than its inlet area, then it may be used as a propulsive jet for watercraft.

FIGS. **42** through **51** illustrate various embodiments of an evaporator system that incorporates a liquid jet ejector according to various embodiments of the invention.

FIG. **42** illustrates an evaporator system **300** according to one embodiment of the invention. In the illustrated embodiment, system **300** includes a vessel **302** containing a feed **304** having a nonvolatile component (e.g., salt, sugar). The feed **304** may first be degassed by pulling a vacuum on it (equipment not explicitly shown). A liquid jet ejector **306** is coupled to vessel **302** and is operable to receive a vapor from vessel **302**. An example of liquid jet ejector **306** is one marketed by Hijet from Houston, Tex. A pump **308**, which may be driven by a suitable electric motor **310**, is operable to deliver a motive liquid **309** to liquid jet ejector **306**. A knock-out tank **312** is coupled to liquid jet ejector **306** and is operable to

separate liquid and vapor received from liquid jet ejector 306 with the aid of a float 313 and a valve 317.

A heat exchanger 314 is coupled inside vessel 302 and is operable to receive the vapor from knock-out tank 312, at least some of the vapor condensing within heat exchanger 314, thereby forming a distilled liquid such as distilled water if the feed is, for example, salt water. The heat of condensation provides the heat of evaporation to vessel 302 to evaporate feed 304. Concentrated product 315 is removed from vessel 302 via any suitable method. Energy that is added to system 300 may be removed using a condenser 318. Alternatively, if condenser 318 were eliminated, the energy added to system 300 will increase the temperature of concentrated product 315. This is acceptable if the product is not temperature sensitive. To remove noncondensibles from system 300, a small stream is pulled from vessel 302 and passed through a condenser 320, and then sent to a vacuum pump (not explicitly illustrated).

In system 300, motive liquid 309 may be a nonvolatile, immiscible, nontoxic, low-viscosity liquid (e.g., silicone oil) or it may be water. If it is water, the water will be in near equilibrium with the vapors discharged from jet ejector 306. When this water is pumped, it may easily cavitate in pump 308. In one embodiment, to overcome this problem, knock-out tank 312 is elevated relative to pump 308 so there is no cavitation. Ideally, if the system were perfect, the liquid water could be recycled indefinitely. However, in reality, energy is input into the circulating water (e.g., pump losses, pipe friction). This energy input causes the circulating water to evaporate, so make-up water should be added. In one embodiment, the make-up water is feed water, which has the following benefits: (1) the nonvolatile components increase the fluid density, which improves the efficiency of the jet ejector and (2) the waste thermal energy generated within the circulating fluid causes water to evaporate, which forms more product.

FIG. 43 illustrates an evaporator system 330 according to another embodiment of the invention. System 330 is similar to system 300, except that a vessel 332 is operated at a higher temperature and pressure than vessel 302. In system 330, energy that is added to vessel 332 can cascade through a multi-effect evaporator 334, which allows additional evaporation to occur. Only three stages are shown in FIG. 43, but more or less are contemplated by the present invention. Alternatively, a multi-stage flash evaporator could be employed rather than a multi-effect evaporator. In system 330, noncondensibles may be removed in a manner similar to system 300. A plurality of sensible heat exchangers 336 may be coupled to vessel 332 and the multi-effect evaporators for heating the feed or for other suitable functions.

FIG. 44 illustrates an evaporator system 340 according to another embodiment of the invention. System 340 is similar to system 300, except that a pump 342 is driven by a Brayton cycle engine 344 or other suitable engines, such as a Diesel engine or Otto cycle engine. In one embodiment of system 340, hot engine exhaust 346 is thermally contacted with the feed in the vessel 348, which produces more product.

FIG. 45 illustrates an evaporator system 350 according to another embodiment of the invention. System 350 is a combination of system 340 (FIG. 44), but includes a multi-effect evaporator 352, which allows additional evaporation to occur. Only three stages are shown in FIG. 45, but more or fewer are contemplated by the present invention. Alternatively, a multi-stage flash evaporator could be employed rather than a multi-effect evaporator.

FIG. 46 illustrates an evaporator system 360 according to another embodiment of the invention. System 360 is similar to system 300 (FIG. 42), except that a pump 362 is driven by

a steam turbine 364. Steam turbine may be a portion of a Rankine cycle. In this embodiment, the low-pressure steam 365 is sent to a steam jet ejector 366, such as those described above. Although FIG. 46 illustrates a single steam jet ejector 365, system 360 may have multiple stages or it may have a cascade steam jet ejector system, such as those described above. Steam jet ejector 366 is in series with a liquid jet ejector 368. In some embodiments, energy that is added to vessel 361 can cascade through a multi-effect evaporator, which allows additional evaporation to occur, similar to system 330 above.

FIG. 47 illustrates an evaporator system 370 according to another embodiment of the invention. System 370 is similar to system 360 (FIG. 46), except that the steam jet ejector 372 is in parallel with the liquid jet ejector 374. As such, steam jet ejector 372 also receives vapor from vessel 376 and compresses it before adding it to the vapor exiting a knock-out tank 378, which then is sent to a heat exchanger 379 in vessel 376. In some embodiments, energy that is added to vessel 376 can cascade through a multi-effect evaporator, which allows additional evaporation to occur, similar to system 330 above.

FIG. 48 illustrates an evaporator system 380 according to another embodiment of the invention. System 380 is similar to systems 360 and 370, except that the waste low-pressure steam 382 from a turbine 384 is sent directly to the primary heat exchanger 386. In some embodiments, energy that is added to vessel 381 can cascade through a multi-effect evaporator, which allows additional evaporation to occur, similar to system 330 above.

FIG. 49 illustrates an analysis of system 330 using the pump drive mechanism described in system 370. This analysis illustrates that 1 kg of high-pressure steam fed to the turbine produces 78.2 kg of distilled water. The assumptions follow:

- Temperature difference in main heat exchanger=5° C.
- Compression ratio=1.2
- Number of multi-effect evaporators=8 (three shown in FIG. 49)
- Steam jet ejector per-stage compression ratio=1.03
- Steam jet ejector number of stages=6
- Steam jet ejector number of cascade levels=3
- Steam jet ejector area ratio=5
- Liquid jet ejector efficiency=0.75
- Pump efficiency=0.85 (appropriate for large industrial pumps)
- Steam turbine efficiency=0.8 (relative to isentropic turbine)

The mass ratios shown for the cascade steam jet ejector are based upon the analysis presented above.

The mass flow through the liquid jet ejector is calculated as follows:

$$\text{Steam Through Liquid Jet Ejector} = \frac{\eta_{\text{pump}} \eta_{\text{ejector}} W_{\text{shaft}}}{\hat{H}_{\text{cond}} - \hat{H}_{\text{evap}}}$$

where \hat{H}_{cond} is the specific enthalpy of the condensing steam (1.2 atm), \hat{H}_{evap} is the specific enthalpy of the evaporating steam (1.0 atm), η_{pump} is the pump efficiency, η_{ejector} is the liquid jet ejector efficiency, and W_{shaft} is the shaft work. The shaft work is calculated as follows:

$$W_{\text{shaft}} = \eta_{\text{turbine}} (\hat{H}_{\text{high}} - \hat{H}_{\text{low}}) m_{\text{steam}}$$

where m_{steam} is the mass of high-pressure steam, η_{turbine} is the turbine efficiency (compared to isentropic), \hat{H}_{high} is the specific enthalpy of the high-pressure steam from the boiler, and

\hat{H}_{low} is the specific enthalpy of the low-pressure steam exiting the turbine. (Note: The conditions at the exit of the turbine correspond to an isentropic expansion.)

FIG. 50 illustrates an analysis similar to the one shown in FIG. 49. All the assumption are identical, except that the steam jet ejectors use an area ratio of 3, and four cascade levels are employed. In this scenario, 1 kg of high-pressure steam produces 93.4 kg of distilled water.

FIG. 51 illustrates an analysis similar to the one shown in FIGS. 49 and 50, except that no steam jet ejector is employed. The waste steam from the turbine is directly sent to the condensing side of the primary heat exchanger. In this case, 1 kg of high-pressure steam produces 75.5 kg of distilled water, which is nearly identical to the case shown in FIG. 49, but not quite as good as the case presented in FIG. 50. This illustrates that there may be a benefit of using the jet ejectors only if they are very efficient (i.e., low area ratio with many stages).

The following table compares various options:

Option	Energy (kJ/kg distilled water)	Effects*
Single-effect evaporator (100° C.)	2,256.58	1
FIG. 51	39.11	57.7
FIG. 49	37.80	59.7
FIG. 50	31.96	70.6
FIG. 44 (engine efficiency = 30%)	40.99	55.1
FIG. 44 (engine efficiency = 40%)	30.75	73.4
FIG. 44 (engine efficiency = 50%)	24.60	91.7
FIG. 44 (engine efficiency = 60%)	20.50	110.1
FIG. 45 (engine efficiency = 30%, 8 stages)	37.29	60.5
FIG. 45 (engine efficiency = 40%, 8 stages)	28.44	79.4
FIG. 45 (engine efficiency = 50%, 8 stages)	23.01	98.1
FIG. 45 (engine efficiency = 60%, 8 stages)	19.32	116.8

*Effect = Energy of single-effect vapor/Energy of the option

This table illustrates that a simple liquid jet ejector combined with a high-efficiency engine (FIGS. 44 and 45) may be the most attractive option. However, high-efficiency engines often require premium fuels, which can be expensive. The steam-turbine systems (FIG. 46 through 48) may use low-cost fuels (e.g., coal), and may be the most economical system in some situations.

An advantage is it uses a high-efficiency liquid jet ejector in a cost-effective dewatering system. When combined with steam jet ejectors and multi-effect evaporators, any energy inefficiencies of the liquid jet system (liquid jet itself, pump, turbine) produce heat that usefully distills liquid. This liquid jet ejector may be used in water-based air conditioning.

FIGS. 52 through 55 illustrate various embodiments of an improved design of a vapor-compression evaporator system. Some important features of the improved designs are (1) compressor equipment may be smaller due to lower vapor throughput, and (2) the systems may be tuned to the operating regions where the compressors are most efficient.

FIG. 52 illustrates a vapor-compression evaporator system 400 according to one embodiment of the invention. In the illustrated embodiment, system 400 includes a plurality of vessels 402a-c in series to form a multi-effect evaporator system. Each vessel contains a feed 404 having a nonvolatile component (e.g., salt, sugar). The feed 404 may first be degassed by pulling a vacuum on it (equipment not explicitly shown). A liquid jet ejector 406 is coupled to the last vessel in the series (402c) and is operable to receive a vapor therefrom. An example of liquid jet ejector 406 is one marketed by Hijet from Houston, Tex. A pump 408 is operable to deliver a motive liquid 410 to the liquid jet ejector 406 for compressing

the vapors pulled from the coldest evaporator stage, vessel 402c. A knock-out tank 412 is coupled to liquid jet ejector 406 and is operable to separate liquid and vapor received from liquid jet ejector 406. A plurality of heat exchangers 414a-c are coupled inside respective vessels 402a-c. Heat exchanger 414a is operable to receive the vapor from knock-out tank 412, at least some of the vapor condensing therein, whereby the heat of condensation provides the heat of evaporation to vessel 402a. At least some of the vapor inside vessel 402a is delivered to heat exchanger 414b, whereby the condensing, evaporating, and delivering steps continue until the last vessel in the series is reached (in this embodiment, vessel 402c).

In FIG. 52, only three stages are shown (i.e., three vessels 402); however, more or fewer could be used. Concentrated product 416 may be removed from each of the vessels 402. Energy that is added to system 400 may be removed using a suitable condenser 418. Alternatively, if condenser 418 were eliminated, the energy added to system 400 will increase the temperature of concentrated product 416. This is acceptable if the product is not temperature sensitive. To remove noncondensibles from system 400, a small stream is pulled from each vessel 402 and passed through a suitable condenser 419 and is sent to a vacuum pump (not shown).

In system 400, motive liquid 410 may be a nonvolatile, immiscible, nontoxic, low-viscosity liquid (e.g., silicone oil) or it may be water. If it is water, the water will be in near equilibrium with the vapors discharged from jet ejector 406. When this water is pumped, it may easily cavitate in pump 408. In one embodiment, to overcome this problem, knock-out tank 412 is elevated relative to pump 408 so there is no cavitation. Ideally, if the system were perfect, the liquid water could be recycled indefinitely. However, in reality, energy is input into the circulating water (e.g., pump losses, pipe friction). This energy input causes the circulating water to evaporate, so make-up water should be added. In one embodiment, the make-up water is feed water, which has the following benefits: (1) the nonvolatile components increase the fluid density, which improves the efficiency of the jet ejector and (2) the waste thermal energy generated within the circulating fluid causes water to evaporate, which forms more product.

FIG. 53 illustrates a vapor-compression evaporator system 430 according to another embodiment of the invention. System 430 is similar to system 400 above, except that the vapor-compression evaporator vessels 432 are operated at a higher temperature and pressure than in system 400. In system 430, energy that is added to the vapor-compression evaporator vessels 432 may cascade through a multi-effect evaporator 434 (three stages shown), which allows additional evaporation to occur. Alternatively, a multi-stage flash evaporator may be employed rather than a multi-effect evaporator. In system 430, noncondensibles may be removed in a manner similar to system 400.

FIG. 54 illustrates a vapor-compression evaporator system 440 according to another embodiment of the invention. System 440 is similar to system 400 above, except that the vapors are compressed using a mechanical compressor 442 driven by a suitable electric motor 443. To reduce the superheat in compressor 445, and thereby increase its efficiency, atomized liquid water 444 is added to compressor 445. Preferably, the liquid water is feed water; as water evaporates from the feed water as it removes the heat of compression, it creates more distilled water and a concentrated product. Alternatively, if the compressor materials do not tolerate the nonvolatile components (e.g., salt) in the circulating cooling liquid 444, then the cooling liquid 445 could be distilled water.

FIG. 55 illustrates a vapor-compression evaporator system 450 according to another embodiment of the invention. Sys-

tem **450** is similar to systems **440** except that energy that is added to vapor-compression evaporators **452** may cascade through a multi-effect evaporator **454**, which allows additional evaporation to occur, similar to system **430** above.

Thus, advantages of the vapor-compression evaporator systems of FIGS. **52** through **55** are 1) because the vapor flow through the compressors is smaller, the compressors may be smaller than the compressors described in the evaporator systems above; and 2) the compression ratio may be adjusted so the compressor operates in its most efficient range. This is particularly important for a liquid jet ejector, which has lower efficiency at lower compression ratios.

Referring now to FIGS. **56** through **61**, in general, a heat exchanger is provided that includes a shell and a sheet assembly disposed within the shell. The sheet assembly may include a number of substantially parallel rectangular sheets configured such that they define first passageways extending generally in a first direction and second passageways extending generally in a second direction perpendicular to the first direction. The sheet assembly may be configured such that communicating a first fluid through the first passageways and communicating a second fluid through the second passageways causes heat transfer between the first and second fluids. For example, the first fluid may comprise high pressure steam and the second fluid may comprise a liquid solution (such as saltwater, seawater, concentrated fermentation broth, or concentrated brine, for example) such that communicating the high-pressure steam and the liquid solution through the first and second passageways, respectively, causes at least a portion of the high-pressure steam to condense and at least a portion of liquid solution to boil off.

FIG. **56** illustrates a cross-section of an example heat exchanger assembly **500** including a shell **510** and a sheet assembly **512** disposed within shell **510** in accordance with an embodiment of the invention. Shell **510** may comprise any suitable shape and may be formed from any suitable material for housing pressurized gasses and/or liquids. For example, in the embodiment shown in FIG. **56**, shell **510** comprises a substantially cylindrical portion **516** and a pair of hemispherical caps (not expressly shown) coupled to each end of cylindrical portion **516**. The cross-section shown in FIG. **56** is taken at a particular point along the length of cylindrical portion **516**, which length extends in a direction perpendicular to the page.

In general, heat exchanger assembly **500** is configured to allow at least two fluids to be communicated into shell **510**, through passageways defined by sheet assembly **512** (such passageways are illustrated and discussed below with reference to FIG. **57A**) such that heat is transferred between the at least two fluids, and out of shell **510**. Shell **510** may include any number of inlets and outlets for communicating fluids into and out of shell **510**. In the embodiment shown in FIG. **56**, shell **510** includes a first inlet **520**, a first outlet **522**, a second inlet **524**, a second outlet **526** and a third outlet **528**. First inlet **520** and first outlet **522** are configured to communicate a first fluid **530** into and out of shell **510**. Second inlet **524**, second outlet **526**, and third outlet **528** are configured to communicate a second fluid **532** into and out of shell **510**.

Due to the transfer of heat between first fluid **530** and second fluid **532**, at least a portion of first fluid **530** and/or second fluid **532** may change state within shell **510** and thus exit shell **510** in a different state than such fluids **530** and/or **532** entered shell **510**. For example, in a particular embodiment, relatively high-pressure steam **534** enters shell **510** through first inlet **520**, enters one or more first passageways within sheet assembly **512**, becomes cooled by a liquid **540** flowing through one or more second passageways adjacent to

the one or more first passageways within sheet assembly **512**, which causes at least a portion of the steam **534** to condense to form steam condensate **536**. The steam condensate **536** flows toward and through first outlet **522**. Concurrently, liquid **540** (saltwater, seawater, concentrated fermentation broth, or concentrated brine, for example) enters shell **510** through second inlet **524**, enters one or more second passageways within sheet assembly **512**, becomes heated by steam **534** flowing through the one or more first passageways adjacent to the one or more second passageways within sheet assembly **512**, which causes at least a portion of the liquid **540** to boil to form relatively low pressure steam **542**. The low pressure steam **542** escapes from shell **510** through second outlet **526**, while the unboiled remainder of liquid **540** flows toward and through third outlet **528**.

In some embodiments, heat exchanger assembly **500** includes one or more pumps **550** operable to pump liquid **540** that has exited shell **510** through third outlet **528** back into shell **510** through second inlet **524**, as indicated by arrows **552**. Pump **550** may comprise any suitable device or devices for pumping a fluid through one or more fluid passageways. As shown in FIG. **56**, liquid **540** may be supplied to the circuit through a feed input **554**. In embodiments in which liquid **540** comprises a solution (such as a seawater solution, for example), a relatively dilute form of such solution (as compared with the solution exiting shell **510** through third output **528**) may be supplied through feed input **554**. In addition, a portion of liquid **540** being pumped toward second inlet **524** of shell **510** may be redirected away from shell **510**, as indicated by arrow **556**. In embodiments in which liquid **540** comprises a solution (such as a seawater solution, for example), such redirected liquid **540** may comprise a relatively concentrated form of such solution (as compared with the diluted solution supplied through feed input **554**). Although inlets **520**, **524** and outlets **522**, **526** and **528** are described herein as single inlets and outlets, each inlet **520**, **524** and each outlet **522**, **526** and **528** may actually include any suitable number of inlets or outlets.

Heat exchanger assembly **500** may also include a plurality of mounting devices **560** coupled to shell **510** and operable to mount sheet assembly **512** within shell **510**. Each mounting device **560** may be associated with a particular corner of sheet assembly **512**. Each mounting device **560** may be coupled to shell **510** in any suitable manner, such as by welding or using fasteners, for example. In the embodiment shown in FIG. **56**, each mounting device **560** comprises a Y-shaped bracket into which a corner of sheet assembly **512** is mounted. Each mounting device **560** may extend along the length of shell **510**, or at least along the length of a portion of shell **510** in which fluids **530** and **532** are communicated, in order to create two volumes within shell **510** that are separated from each other. A first volume **564**, which includes regions generally to the left and right of sheet assembly **510**, as well as one or more first passageways defined by sheet assembly **510** (such first passageways are illustrated and discussed below with reference to FIG. **57A**), is used to communicate first fluid **530** through heat exchanger assembly **500**. A second volume **566**, which includes regions generally above and below sheet assembly **510**, as well as one or more second passageways defined by sheet assembly **510** (such second passageways are illustrated and discussed below with reference to FIG. **57A**), is used to communicate second fluid **532** through heat exchanger assembly **500**.

Since first volume **564** is separated from second volume **566** by the configuration of sheet assembly **512** and mounting devices **560**, first fluid **530** is kept separate from second fluid **532** within shell **510**. In addition, one or more gaskets **562**

may be disposed between each Y-shaped bracket **560** and its corresponding corner of sheet assembly **512** to provide a seal between first volume **564** and second volume **566** at each corner of sheet assembly **512**. Gaskets **562** may comprise any suitable type of seal or gasket, may have any suitable shape (such as having a square, rectangular or round cross-section, for example) and may be formed from any material suitable for forming a seal or gasket.

Heat exchanger assembly **500** may also include one or more devices for sliding, rolling, or otherwise positioning sheet assembly **512** within shell **510**. Such devices may be particularly useful in embodiments in which sheet assembly **512** is relatively heavy or massive, such as where sheet assembly **512** is formed from metal. In the embodiment shown in FIG. **56**, heat exchanger assembly **500** includes wheels **568** coupled to sheet assembly **512** that may be used to roll sheet assembly **512** into shell. Wheels **568** may be aligned with, and roll on, wheel tracks **570** coupled to shell **510** in any suitable manner.

FIG. **57A** illustrates a three-dimensional view of sheet assembly **512** of heat exchanger assembly **500** in accordance with one embodiment of the invention. Sheet assembly **512** includes a plurality of sheets **580** configured and coupled to each other to form a plurality of first passageways **582** extending in a first direction **584** alternating with a plurality of second passageways **586** extending in a second direction **588** perpendicular to the first direction **584**. Each passageway **582** and **586** is substantially defined by an adjacent pair of sheets **580**. In this embodiment, sheets **580** are aligned substantially parallel and, when positioned within shell **510**, the major surface of each sheet **580** extends in a plane substantially perpendicular to the direction of the length of cylindrical portion **516** of shell **510**.

As discussed above with reference to FIG. **56**, first passageways **582** form a portion of first volume **564** and are thus used to communicate first fluid **530**, while second passageways **586** form a portion of second volume **566** and are thus used to communicate second fluid **532**. As fluids **530** and **532** pass through alternating first passageways **582** and second passageways **586**, respectively, heat is transferred from the higher temperature fluid **530** or **532** to sheets **580**, and then from sheets **580** to the lower temperature fluid **530** or **532**. In this manner, heat is transferred between fluids **530** and **532** via sheets **580**.

In the embodiments shown in FIG. **57A**, each sheet **580** has a substantially square shape having four edges **590**. In other embodiments, sheets **580** may comprise any suitable shape and configuration. For example, sheets **580** may have a generally rectangular, hexagonal, circular, or other geometric shape. In order to define alternating passageways **582** and **586**, each sheet **580** is coupled to an adjacent sheet **580** on one side at two of the four edges **590** and to an adjacent sheet **580** on the other side at the other two of the four edges **590**. For example, sheet **580a**, which is positioned between adjacent sheet **580b** and adjacent sheet **580c**, is coupled to adjacent sheet **580b** at opposite edges **590a** and **590b** of sheet **580a**, and is coupled to adjacent sheet **580c** at opposite edges **590c** and **590d** of sheet **580a**.

Sheets **580** may be coupled to each other at edges **590** in any suitable manner, as discussed in greater detail below with reference to FIG. **59**. In the embodiment shown in FIG. **57A**, each sheet **580** is folded near each edge **590** to form flanges **592** at each edge **590** which are then coupled to corresponding flanges **592** of adjacent sheets **580**. FIG. **57B** is a blown-up view of a corner area of sheet assembly **512**, illustrating flanges **592** of adjacent sheets **580** being coupled to each other in accordance with an embodiment of the invention. As shown in FIG. **57B**, sheet **580a** is folded twice at approxi-

mately 90 degree angles to form a flange **592a** including a first flange portion **594a** and a second flange portion **596a**. First flange portion **594a** forms an approximately 90 degree angle with the major portion of sheet **580a**, indicated as **598a**, and second flange portion **596a** forms an approximately 90 degree angle with first flange portion **594a**. Thus, the surface of second flange portion **596a** is approximately parallel with the surface of major portion **598a** of sheet **580a**. A triangular flap **600a** is folded from first flange portion **594a** and may be affixed to second flange portion **596a** (such as by welding, for example). Similarly, sheet **580b** is folded twice at approximately 90 degree angles to form a flange **592b** including a first flange portion **594b** and a second flange portion **596b**. First flange portion **594b** forms an approximately 90 degree angle with the major portion of sheet **580b**, indicated as **598b**, and second flange portion **596b** forms an approximately 90 degree angle with first flange portion **594b**. Thus, the surface of second flange portion **596b** is approximately parallel with the surface of major portion **598b** of sheet **580b**. A triangular flap **600b** is folded from first flange portion **594b** and may be affixed to second flange portion **596b** (such as by welding, for example).

FIG. **57C** illustrates a side view of the corner of sheet assembly **512** illustrated in FIG. **57B**.

FIGS. **58A-58B** illustrate an example method of forming a particular sheet **580a**, including flanges **592**, of sheet assembly **512** in accordance with one embodiment of the invention. FIG. **58A** illustrates a generally flat sheet **610** of material, such as sheet metal or one or more polymers, for example. The sheet **610** has a generally square shape including one or more notches removed from each corner. Cuts **612** are formed in each corner at approximately 45 degrees relative to the edges **590** of sheet **610** in order to form triangular flaps **600** in the resulting sheet **580a**. From sheet **610** formed as shown in FIG. **58A**, flanges **592a** are formed by folding sheet **610** at each fold line **614** (indicated in FIG. **58A** by dashed lines) at approximately 90 degree angles. For example, flange **592a** may be formed by (a) folding the edge portion **590a** of sheet **610** approximately 90 degree inward (out of the page and toward the center of sheet **610**) at fold line **614a** to form first flange portion **594a**, and (b) folding the remaining edge portion **590a** of sheet **610** approximately 90 degree outward (to the left and down toward the page) at fold line **614b** to form second flange portion **596a**. Thus, the resulting flange **592a** extends generally out of the page. The flange **592** at opposing edge **590b** may be formed in the same manner as flange **592a**. The flanges **592** at edges **590c** and **590d** may be formed in a similar, but opposite, manner such that the flanges **592** at edges **590c** and **590d** extend generally into the page. Triangular flaps **600** may then be folded down and connected (such as by welding) to second flange portions **596** to reinforce each flange **592**. For example, triangular flap **600a** may be folded down and welded to second flange portion **596a** to reinforce flange **592a**.

FIG. **58B** illustrates the resulting sheet **580a**, including flanges **592** at each edge **590a-590d** of sheet **580a**. Flanges **592** at edges **590a** and **590b** of sheet **580a** extend in a first direction (out of the page), such that they may be coupled to flanges **592** of adjacent sheet **580b**, while flanges **592** at edges **590c** and **590d** of sheet **580a** extend in the opposite direction (into the page), such that they may be coupled to flanges **592** of adjacent sheet **580c**.

Sheets **580** may also include one or more protrusions for preventing passageways **582** or **586** between adjacent sheets **580** from being cut off, such as due to the distortion of sheets **580** during operation of heat exchanger apparatus **500** (such as due to the presence of high-pressure fluids, for example) and/or to provide additional strength or stiffening to sheets **580**. In the embodiment shown in FIGS. **58A-58B**, sheet **580a** includes a plurality of stiffening ribs, or corrugations, **620** which strengthen sheet **580a**, as well as ensure that the second

passageway 586 between sheets 580a and 580b remains intact during the operation of heat exchanger apparatus 500. Sheet 580b may also include a plurality of stiffening ribs (not expressly shown) operable to engage stiffening ribs 620 of sheet 580a. In a particular embodiment, such stiffening ribs of sheet 580b are oriented in a direction perpendicular to that of stiffening ribs 620 of sheet 580a.

FIG. 58C illustrates a cross-sectional view of sheet 580a taken along Cut A shown in FIG. 58B. FIG. 58D illustrates a cross-sectional view of sheet 580a taken along Cut B shown in FIG. 58B. Taken together with FIG. 58B, FIGS. 58C and 58D illustrate that, as discussed above, flanges 592 at edges 590a and 590b of sheet 580a extend in a first direction (out of the page), while flanges 592 at edges 590c and 590d of sheet 580a extend in the opposite direction (into the page).

As discussed above, in forming sheet assembly 512, second flange portion 596a of flange 592a of sheet 580a may be coupled to second flange portion 596b of flange 592b of sheet 580b in any suitable manner. FIG. 59 illustrates various example manners in which second flange portion 596a may be coupled to second flange portion 596b. As shown in FIG. 59, second flange portion 596a may be coupled to second flange portion 596b by a weld 630; a brazed connection 632; a crimp clamp 634; one or more fasteners 636, such as a rivet or screw for example; or a crimp connection 638, for example. For some types of couplings, a gasket 640 may be inserted in order to assure a seal between second flange portion 596a and second flange portion 596b (and thus a seal between sheets 580a and 580b at the relevant edge of 580a and 580b). In embodiments in which one or more fasteners 636 are used, stiffeners 642 may be provided to strengthen or reinforce the connection.

As discussed above, sheets 580 may be formed from any suitable material, such as sheet metal or one or more polymers, for example. Table 1 compares various polymers that could be used for the sheet-polymer assemblies. The underlined value in Table 1 is used to calculate the overall heat transfer coefficient, U, which is determined as follows:

$$U = \left[\frac{1}{h_i} + \frac{x}{k} + \frac{1}{h_o} \right]^{-1}$$

where

- h_i=inside heat transfer coefficient =3000 Btu/(h·ft²·° F.) (for boiling water)
- h_o=outside heat transfer coefficient =15,000 Btu/(h·ft²·° F.) (dropwise condensation for polymer)
- =2,000 Btu/(h·ft²·° F.) (filmwise condensation for metal)
- k=thermal conductivity of material (Btu/(h·ft·° F.))
- x=material thickness =0.01 in =500 mil=0.00083 ft

The overall heat transfer coefficient U is reported in the fifth column of Table 1. The cost of each polymer per square foot, C, is shown in the fourth column of Table 1. The ratio U/C is reported in the sixth column of Table 1, which is the overall heat transfer coefficient on a dollar basis, rather than an area basis. The ratio U/C may be referred to as the “figure of merit.” The polymers are listed in order, with the highest U/C appearing at the top and the lowest U/C appearing at the bottom. In the last column of Table 1, the U/C for each polymer is compared to that of stainless steel (SS) and titanium (Ti). Stainless steel resists corrosion for many solutions (e.g., sugar, calcium acetate), but titanium may be used for particularly corrosive solutions, such as seawater, for example.

The polymer with the highest U/C is HDPE (high-density polyethylene). Polypropylene is also very good, and it may perform well at slightly higher temperatures. Other polymers (polystyrene, PVC) may also be considered, but their U/C performance may not be quite as good as polyethylene or polypropylene. As a general rule, the thermal conductivity of the polymers is much lower than metals, but their U/C performance may be superior because of their low material cost relative to metals. In addition, polymers are typically less expensive to form into the final shape of sheets 580 and sheet assembly 512 than metals. Further, polymer structures may be easier to seal, providing an additional benefit over metals.

HDPE has a thermal conductivity comparable to stainless steel if the polymer molecules are aligned in the direction of heat flow (see third column, first row, Table 1). FIG. 60A illustrates an example method of aligning the molecules in a sample 650 of HDPE by drawing the polymer melt through a die 652. The shear orients the HDPE molecules in the flow direction, thus forming a molecularly-oriented HDPE block 654. By cutting polymer sheets 656 from such molecularly-oriented HDPE block 654 in which the molecules are aligned perpendicular to the sheet surface 658, the heat transfer performance of the HDPE sheet may be increased or maximized.

In some situations, the desired size of sheets 580 for a sheet assembly 512 may be larger than the molecularly-oriented polymer (e.g., HDPE) block 654 that may be produced due to available manufacturing equipment, equipment limitations, cost or some other reason. FIG. 60B illustrates a method of forming a sheet 580 (e.g., a relatively large sheet 580) by joining a number of polymer sheets 656. Such polymer sheets 656 may be joined in any suitable manner to form sheet 580, such as welding or heating to a relatively low temperature, for example.

In addition to providing increased heat transfer per cost as compared with metal, polymers may be more corrosion-resistant, more pliable, and more easily formed into sheets 580 and sheet assembly 512.

TABLE 1

Comparison of polymers.						
Material	Max. Working Temp. ° F.	k Thermal Conductivity Btu/(h·ft·° F.)	C \$/ft ² (10 mil thickness)	U ^b Btu/(h·ft ² ·° F.)	U/CBtu/(h·\$·° F.)	(U/C) _{plastic} / (U/C) _{metal}
HDPE (high-density polyethylene)	160 ^c 175-250 ^e	0.29 ^f 0.25 @ 70° F. ^g <u>0.20 @ 212° F.^h</u> 4.9-8.1 ^m	0.12 ^a <u>0.11^d</u>	220	2,000	2.64 (SS) 5.93 (Ti)

TABLE 1-continued

Comparison of polymers.						
Material	Max. Working Temp. ° F.	k Thermal Conductivity Btu/(h · ft · ° F.)	C \$/ft ² (10 mil thickness)	U ^b Btu/(h · ft ² · ° F.)	U/CBtu/(h · \$ · ° F.)	(U/C) _{plastic} / (U/C) _{metal}
Stainless Steel		9.4 ^v	1.68 ^g 1.49 ^d 1.43 ⁿ	1,085	759	1.00 (SS)
Titanium		12 ^x	7.4 ^h 3.29 ^o	1,108	337	1.00 (Ti)

^aK-mac Plastics (www.k-mac-plastics.net)

^bh_f = 3000 Btu/(h · ft² · ° F.)

^ch_o = 15,000 Btu/(h · ft² · ° F.) (dropwise condensation for plastic)

^dh_o = 2,000 Btu/(h · ft² · ° F.) (filmwise condensation for metal)

^eh_m = k/x

^fx = 0.01 in = 0.00083 ft

^gHubert Interactive

^hMcMaster-Carr

ⁱPerry's Handbook of Chemical Engineering (Table 23-22)

^jK-mac Plastics

^kwww.metalsdepot.com

^lwww.halpentitanium.com

^mR. M. Ogorkiewicz, Thermoplastics: Properties and Design, Wiley, London (1974) p. 133-135

ⁿR. M. Ogorkiewicz, Engineering Properties of Thermoplastics, Wiley, London (1970)

^oP. e. Powell, Engineering with Polymers, Chapman and Hall, London (1983), p. 242

^pBuilding Research Institute, Plastics in Building, National Academy of Sciences, 1955.

^qIn the direction of molecular orientation, draw direction ratio of 25 www.electronics-cooling.com/html/2001_august_techdata.html Choy C. L., Luk W. H., and Chen, F. C., 1978, Thermal Conductivity of Highly Oriented Polyethylene, Polymer, Vol. 19, pp. 155-162.

^rRickard Metals, rickardmetals.com (\$3.50/lb)

^sAstro Cosmos, 888-402-7876 (\$14/lb, Grade 2)

^t3d-cam.com

^uboedeker.com

^vbayplastics.co.uk

^wsdplastics.com

^xtstar.com

^yplasticsusa.com

^zzae-bayern.de

^{aa}toray.fr

^{ab}efunda.com

^{ac}Perry's Handbook of Chemical Engineering (Table 3-322)

FIGS. 61A-61D illustrates another example sheet assembly 512A in accordance with another embodiment of the invention. FIG. 61A illustrates a three-dimensional view of sheet assembly 512A. FIG. 61B is a blown-up view of a corner area of sheet assembly 512A, illustrating flanges 592A of adjacent sheets 580A being coupled to each other in accordance with an embodiment of the invention. FIG. 61C illustrates a side view of the corner of sheet assembly 512A illustrated in FIG. 61B. FIG. 61D illustrates the configuration of a flat sheet 610A of material, such as sheet metal or one or more polymers, for example, that may be used to form each sheet 580A of sheet assembly 512A (such as by folding sheet 610A, such as described above with regard to FIGS. 3A-3B). As shown in FIGS. 61A-61D, sheet assembly 512A is substantially similar to sheet assembly 512 shown in FIG. 57A. However, unlike sheet assembly 512, sheet assembly 512A does not include triangular flaps 600 at the corners of each sheet 580A. Thus, sheet assembly 512A may be more simple to construct, and thus less expensive, than sheet assembly 512.

Although embodiments of the invention and their advantages are described in detail, a person skilled in the art could make various alterations, additions, and omissions without departing from the spirit and scope of the present invention.

What is claimed is:

1. A jet ejector method, comprising:

providing a primary jet ejector having a primary inlet stream;

coupling one or more secondary jet ejectors to the primary jet ejector such that all of the jet ejectors are in a cascaded arrangement;

bleeding off a portion of the primary inlet stream and directing the portion of the primary inlet stream to the secondary jet ejector that is closest to the primary jet ejector in the cascaded arrangement;

directing a motive fluid into the secondary jet ejector that is farthest from the primary jet ejector in the cascaded arrangement;

at each secondary jet ejector, receiving at least some of the portion of the primary inlet stream and at least some of the motive fluid to create respective mixtures within the secondary jet ejectors; and

at each secondary jet ejector, directing at least a portion of the respective mixture to adjacent jet ejectors in the cascaded arrangement.

2. The method of claim 1, further comprising:

directing a portion of the mixture from the secondary jet ejector that is farthest from the primary jet ejector in the cascaded arrangement to a compressor; and
compressing the portion to produce the motive fluid.

3. The method of claim 2, further comprising powering the compressor with a steam turbine.

4. The method of claim 3, further comprising directing waste steam from the steam turbine to the primary jet ejector or one of the secondary jet ejectors.

5. The method of claim 2, further comprising powering the compressor with a device selected from the group consisting of an engine and an electric motor.

6. The method of claim 2, further comprising powering the compressor with a Brayton cycle engine.

27

7. The method of claim 1, wherein providing the primary jet ejector comprises providing a plurality of primary jet ejectors in series with one another.

8. The method of claim 7, further comprising providing each of the plurality of primary jet ejectors with a respective set of secondary jet ejectors.

9. The method of claim 8, wherein at least some of the secondary jet ejectors of one of the plurality of primary jet ejectors serve as at least some of the secondary jet ejectors of another one of the plurality of primary jet ejectors.

10. The method of claim 8, further comprising an equal number of stages of secondary jet ejectors in each respective set, and wherein the secondary jet ejectors comprising a particular stage are in series.

11. A jet ejector method, comprising:

providing a primary jet ejector having a primary inlet stream and an outlet stream;

coupling one or more secondary jet ejectors to the primary jet ejector such that all of the jet ejectors are in a cascaded arrangement;

bleeding off a portion of the outlet stream and directing the portion of the outlet stream to the secondary jet ejector that is closest to the primary jet ejector in the cascaded arrangement;

directing a motive fluid into the secondary jet ejector that is farthest from the primary jet ejector in the cascaded arrangement;

at each secondary jet ejector, receiving at least some of the portion of the outlet stream and at least some of the motive fluid to create respective mixtures within the secondary jet ejectors; and

at each secondary jet ejector, directing at least a portion of the respective mixture to adjacent jet ejectors in the cascaded arrangement.

12. The method of claim 11, further comprising:

directing a portion of the mixture from the secondary jet ejector that is farthest from the primary jet ejector in the cascaded arrangement to a compressor; and

compressing the portion to produce the motive fluid.

13. The method of claim 12, further comprising powering the compressor with a device selected from the group consisting of a steam turbine, an engine, and an electric motor.

14. The method of claim 11, wherein providing the primary jet ejector comprises providing a plurality of primary jet ejectors in series with one another, the outlet stream associated with the last primary jet ejector in the series.

15. The method of claim 14, wherein the secondary jet ejectors are associated with the last primary jet ejector in the series.

16. The method of claim 14, further comprising providing each of the plurality of primary jet ejectors with a respective set of secondary jet ejectors.

17. The method of claim 16, further comprising an equal number of stages of secondary jet ejectors in each respective set, and wherein the secondary jet ejectors comprising a particular stage are in series.

18. A jet ejector method, comprising:

providing a primary jet ejector having a primary inlet stream at a first pressure, a secondary inlet stream at a second pressure, and an outlet stream;

coupling one or more secondary jet ejectors to the primary jet ejector such that all of the jet ejectors are in a cascaded arrangement;

directing a motive fluid at a third pressure into the secondary jet ejector that is farthest from the primary jet ejector in the cascaded arrangement; and

28

causing a fluid flow comprised of at least some of the primary inlet stream and at least some of the motive fluid through each of the secondary jet ejectors such that the third pressure is larger than the second pressure and the second pressure is larger than the first pressure.

19. The method of claim 18, wherein a compression ratio for each of the primary and secondary jet ejectors is no more than approximately three.

20. The method of claim 18, wherein an area ratio for the primary jet ejector is selected from the group consisting of approximately three, approximately four, and approximately five.

21. A jet ejector, comprising:

a nozzle having a first stream flowing therethrough, the nozzle comprising an upstream portion, a downstream portion, and a throat disposed between the upstream portion and the downstream portion;

a plurality of sets of apertures located in a wall of the nozzle in the throat, the plurality of sets of apertures longitudinally spaced along the wall;

each of the plurality of sets of apertures having its apertures circumferentially located around the wall; and
a device operable to inject a motive fluid through the apertures and into the first stream.

22. The jet ejector of claim 21, wherein the apertures comprise circumferential slots.

23. The jet ejector of claim 21, wherein the motive fluid enters the first stream at an angle with respect to a flow direction of the first stream.

24. The jet ejector of claim 21, wherein respective pressures of the motive fluid associated with respective ones of the plurality of sets of apertures are approximately equal.

25. The jet ejector of claim 21, wherein respective pressures of the motive fluid associated with respective ones of the plurality of sets of apertures are approximately unequal.

26. The jet ejector of claim 25, wherein the respective pressures of the motive fluid increase in a downstream direction.

27. The jet ejector of claim 21, wherein the apertures comprise point sources.

28. The jet ejector of claim 27, wherein each point source is coupled to a respective fan-shaped duct formed in the wall and defined by walls diverging in the downstream direction.

29. The jet ejector of claim 28, wherein the fan-shaped ducts are NACA ducts.

30. The jet ejector of claim 21, wherein the motive fluid is selected from the group consisting of a gas, a vapor, and a liquid.

31. A jet ejector, comprising:

a nozzle having a first stream flowing therethrough, the nozzle comprising an upstream portion, a downstream portion, and a throat disposed between the upstream portion and the downstream portion;

a plurality of apertures located in a wall of the nozzle in the throat, the plurality of apertures longitudinally spaced along the wall; and

a device operable to inject a motive liquid through the plurality of apertures and into the first stream and wherein respective pressures of the motive liquid associated with each of the plurality of apertures are approximately equal.

32. The jet ejector of claim 31, wherein the apertures comprise nozzles.

33. The jet ejector of claim 31, wherein the motive liquid enters the first stream at an angle with respect to a flow direction of the first stream.

29

34. The jet ejector of claim 31, wherein respective pressures of the motive liquid associated with respective ones of the plurality of apertures are approximately unequal.

35. The jet ejector of claim 34, wherein the respective pressures of the motive liquid increase in a downstream direction.

36. The jet ejector of claim 31, wherein the apertures comprise passageways associated with one or more tubes coupled to the wall of the nozzle in the throat.

37. The jet ejector of claim 36, wherein the motive liquid enters the first stream parallel with respect to a flow direction of the first stream.

38. The jet ejector of claim 36, further comprising a plurality of receptacles coupled to the wall of the nozzle in the throat and associated with respective ones of the plurality of tubes in order to collect the motive fluid exiting therefrom.

39. A jet ejector method, comprising:
causing a first stream to flow through a nozzle; and
injecting a motive fluid into the first stream through a plurality of sets of apertures located in a wall of a throat of the nozzle, the plurality of sets of apertures longitu-

30

dinally spaced along the wall of the throat, wherein the respective pressures of the motive fluid increase in a downstream direction.

40. The method of claim 39, wherein the apertures are selected from the group consisting of circumferential slots, annular openings, and point sources.

41. The method of claim 39, further comprising causing the motive fluid to enter the first stream at an angle with respect to a flow direction of the first stream.

42. The method of claim 39, further comprising causing respective pressures of the motive fluid associated with respective ones of the plurality of sets of apertures to be approximately equal.

43. The method of claim 39, further comprising causing respective pressures of the motive fluid associated with respective ones of the plurality of sets of apertures to be approximately unequal.

44. The method of claim 39, wherein the motive fluid is selected from the group consisting of steam and liquid water.

* * * * *