



US008821138B2

(12) **United States Patent**
Holtzapple et al.

(10) **Patent No.:** **US 8,821,138 B2**
(45) **Date of Patent:** **Sep. 2, 2014**

(54) **GEROTOR APPARATUS FOR A QUASI-ISOTHERMAL BRAYTON CYCLE ENGINE**

(58) **Field of Classification Search**
USPC 418/61.3, 152, 178, 179, 166, 171
See application file for complete search history.

(75) Inventors: **Mark T. Holtzapple**, College Station, TX (US); **George A. Rabroker**, College Station, TX (US)

(56) **References Cited**

(73) Assignee: **The Texas A&M University System**, College Station, TX (US)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 155 days.

457,294 A	8/1891	Tilden
724,665 A	4/1903	Coolley
892,295 A	6/1908	Nutz
1,501,051 A	7/1924	Hill
1,854,692 A	4/1932	Cooper
2,011,338 A	8/1935	Hill
2,138,490 A	11/1938	Haller
2,240,056 A	4/1941	Schmitz
2,291,354 A	7/1942	Sibley

(Continued)

(21) Appl. No.: **12/761,432**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Apr. 16, 2010**

AU	20406/29	0/1929
DE	35 13348 A1	10/1986

(Continued)

(65) **Prior Publication Data**

US 2010/0266435 A1 Oct. 21, 2010

OTHER PUBLICATIONS

Related U.S. Application Data

PCT Written Opinion for International Application No. PCT/US03/03549; filed Feb. 5, 2003 (5 pages) Sep. 24, 2004.

(Continued)

(63) Continuation of application No. 11/681,877, filed on Mar. 5, 2007, now Pat. No. 7,726,959, which is a continuation of application No. 10/359,487, filed on Feb. 5, 2003, now Pat. No. 7,186,101.

Primary Examiner — Theresa Trieu

(60) Provisional application No. 60/397,193, filed on Jul. 18, 2002, provisional application No. 60/358,681, filed on Feb. 21, 2002, provisional application No. 60/355,636, filed on Feb. 5, 2002.



(57) **ABSTRACT**

According to one embodiment of the invention, a gerotor apparatus includes an outer gerotor having an outer gerotor chamber, an inner gerotor, at least a portion of which is disposed within the outer gerotor chamber, and a synchronizing apparatus operable to control the rotation of the inner gerotor relative to the outer gerotor. The inner gerotor includes one or more entrance passages operable to communicate a lubricant into the outer gerotor chamber.

(51) **Int. Cl.**
F03C 2/00 (2006.01)
F03C 4/00 (2006.01)
F04C 2/00 (2006.01)

(52) **U.S. Cl.**
USPC **418/61.3**; 418/152; 418/178; 418/179

20 Claims, 97 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,373,368 A 4/1945 Witchger
 2,459,447 A 1/1949 Milliken
 2,601,397 A 6/1952 Hill et al.
 2,938,663 A 5/1960 Lüick
 2,965,039 A 12/1960 Morita
 2,974,482 A 3/1961 Kelley
 3,037,348 A 6/1962 Gassmann
 3,082,747 A 3/1963 Luck
 3,121,341 A * 2/1964 Hill 74/462
 3,126,755 A 3/1964 Luck
 3,167,913 A 2/1965 Mühlberg et al.
 3,214,087 A 10/1965 Lück
 3,226,013 A 12/1965 Shoichiro et al.
 3,273,341 A 9/1966 Wildhaber
 3,295,748 A 1/1967 Leitgeb
 3,303,783 A 2/1967 Neubauer
 3,303,784 A 2/1967 Neubauer
 3,334,253 A 8/1967 Hill
 3,459,337 A 8/1969 Williamson
 3,536,426 A 10/1970 Albrecht et al.
 3,623,317 A 11/1971 Foster-Pegg
 3,657,879 A 4/1972 Ewbank et al.
 3,844,117 A 10/1974 Ryan
 3,846,987 A 11/1974 Baldwin
 3,877,218 A 4/1975 Negben
 3,894,255 A 7/1975 Newton, Jr.
 3,928,974 A 12/1975 Benson
 3,932,987 A 1/1976 Munzinger
 3,972,652 A 8/1976 Minnicino
 3,995,431 A 12/1976 Schwartzman
 4,023,366 A 5/1977 Schneider
 4,028,023 A 6/1977 Labus
 4,044,558 A 8/1977 Benson
 4,052,928 A 10/1977 Pierrat et al.
 4,058,938 A 11/1977 Harle et al.
 4,074,533 A 2/1978 Stockton
 4,111,572 A * 9/1978 Noone et al. 228/124.1
 4,127,364 A 11/1978 Eiermann et al.
 4,145,167 A 3/1979 Baatrup
 4,199,305 A 4/1980 Pareja
 4,336,686 A 6/1982 Porter
 4,355,249 A 10/1982 Kenwell
 4,392,797 A 7/1983 Ruf
 4,439,119 A 3/1984 Petersen et al.
 4,457,677 A 7/1984 Todd
 4,478,553 A 10/1984 Leibowitz et al.
 4,491,171 A 1/1985 Zenkner
 4,502,284 A 3/1985 Chrisoghilos
 4,519,206 A 5/1985 van Michaels
 4,553,513 A 11/1985 Miles et al.
 4,578,955 A 4/1986 Medina
 4,630,447 A 12/1986 Webber
 4,649,671 A * 3/1987 Erhardt et al. 451/47
 4,653,269 A 3/1987 Johnson
 4,657,009 A 4/1987 Zen
 4,674,960 A 6/1987 Rando et al.
 4,696,158 A 9/1987 DeFrancisco
 4,759,178 A 7/1988 Joy
 4,775,299 A 10/1988 Overfield et al.
 4,801,255 A 1/1989 Wankel
 4,836,760 A 6/1989 MacLeod
 4,940,394 A 7/1990 Gibbons
 4,951,790 A 8/1990 Blything
 4,958,997 A 9/1990 Harwath
 4,976,595 A 12/1990 Taniguchi
 4,986,739 A 1/1991 Child
 5,044,907 A 9/1991 Hirose et al.

5,074,110 A 12/1991 Singh
 5,101,782 A 4/1992 Yang
 5,161,728 A * 11/1992 Li 228/124.1
 5,195,882 A 3/1993 Freeman
 5,199,971 A * 4/1993 Akechi 418/179
 5,271,215 A 12/1993 Guillet
 5,284,016 A 2/1994 Stark et al.
 5,289,072 A 2/1994 Lange
 5,311,739 A 5/1994 Clark
 5,472,329 A 12/1995 Maynard et al.
 5,497,392 A * 3/1996 Sawicki et al. 372/62
 5,522,356 A 6/1996 Palmer
 5,538,073 A 7/1996 Stopa
 5,554,020 A 9/1996 Rao et al.
 5,557,921 A 9/1996 Fruttschi et al.
 5,618,171 A 4/1997 von Behr et al.
 5,622,044 A 4/1997 Bronicki et al.
 5,634,339 A 6/1997 Lewis et al.
 5,682,738 A 11/1997 Barber
 5,733,111 A 3/1998 Yu et al.
 5,755,196 A 5/1998 Klassen
 5,761,898 A 6/1998 Barnes et al.
 5,798,591 A 8/1998 Lillington et al.
 5,839,270 A 11/1998 Jirnov et al.
 5,854,526 A 12/1998 Sakamoto
 5,964,087 A 10/1999 Tort-Oropeza
 6,085,829 A 7/2000 Neuhaus et al.
 6,174,151 B1 1/2001 Yarr
 6,313,544 B1 11/2001 Mongia et al.
 6,336,317 B1 1/2002 Holtzapple et al.
 6,487,862 B1 12/2002 Doorley
 6,791,347 B2 * 9/2004 Ishizaka et al. 324/750.05
 7,008,200 B2 3/2006 Holtzapple et al.
 7,186,101 B2 3/2007 Holtzapple et al.
 2003/0011268 A1 1/2003 Even et al.

FOREIGN PATENT DOCUMENTS

DE 3812637 7/1989
 DE 4023299 2/1991
 DE 197 200 248 11/1998
 EP 02207187 8/1990
 EP 1 197 634 4/2002
 FR 2720788 12/1995
 FR 9748884 12/1997
 FR 2 812 041 7/2000
 GB 2 085 969 5/1982
 GB 2 221 258 1/1990
 JP 60128983 A * 7/1985 418/171
 JP 01147177 A * 6/1989 418/152
 JP 02-207187 8/1990
 JP 5-1674 1/1993
 JP 405079464 3/1993
 JP 0-6330875 11/1994
 WO WO/03/067030 A2 2/2003

OTHER PUBLICATIONS

Declaration of Mark T. Holtzapple (6 pages), Apr. 29, 2005.
 PCT Written Opinion for International Application No. PCT US06/14613; Aug. 16, 2007.
 PCT Written Opinion for International Application No. PCT/US/05/37802; May 6, 2008.
 Declaration of Mark Holtzapple, dated Apr. 29, 2005, 6 pages, 2005.
 EP Communication for Application No. 03737665.4; Apr. 5, 2007; Reference No. JL4578, 2007.
 Declaration of Mark Holtzapple, dated May 10, 2005 (6 pgs.), May 10, 2005.

* cited by examiner

FIG. 1A




FIG. 1B




FIG. 2A





FIG. 2B






FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B






FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50







FIG. 51






FIG. 54




FIG. 55




FIG. 56




FIG. 57A




FIG. 57B




FIG. 59A




FIG. 59B




FIG. 58




FIG. 59C




FIG. 59D








FIG. 60A






FIG. 63




FIG. 64A




FIG. 64B




FIG. 65A




FIG. 65B




FIG. 66A




FIG. 66B




FIG. 66C





FIG. 67






FIG. 68C




FIG. 69




FIG. 70A




FIG. 70B




FIG. 70C




FIG. 71B




FIG. 71A




FIG. 72




FIG. 73




FIG. 74




FIG. 75A




FIG. 75B




FIG. 75C




FIG. 76B




FIG. 76A





FIG. 77A




FIG. 77B




FIG. 78A




FIG. 78B




FIG. 78C




FIG. 79A




FIG. 79B








FIG. 80








FIG. 84A




FIG. 84B




FIG. 85A




FIG. 85B




FIG. 86




FIG. 87A




FIG. 87B




FIG. 88




FIG. 89C




FIG. 89D




FIG. 89A




FIG. 89B




FIG. 90A




FIG. 90B




FIG. 90C




FIG. 90D




FIG. 91A




FIG. 91B




FIG. 91C




FIG. 91D




FIG. 92




FIG. 93




FIG. 94




FIG. 95A




FIG. 95B





FIG. 95C






FIG. 97




FIG. 98




FIG. 99




FIG. 100




FIG. 101

1

GEROTOR APPARATUS FOR A QUASI-ISOTHERMAL BRAYTON CYCLE ENGINE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 11/681, 877, filed Mar. 5, 2007, and entitled "GEROTOR APPARATUS FOR A QUASI-ISOTHERMAL BRAYTON CYCLE ENGINE," now U.S. Pat. No. 7,726,959, which is a continuation of U.S. application Ser. No. 10/359,487, filed Feb. 5, 2003, and entitled "GEROTOR APPARATUS FOR A QUASI-ISOTHERMAL BRAYTON CYCLE ENGINE," now U.S. Pat. No. 7,186,101, which claims benefit and/or priority under 35 U.S.C. § 119(e) to U.S. Provisional Application Ser. No. 60/355,636, entitled "QUASI-ISOTHERMAL BRAYTON CYCLE ENGINE," filed Feb. 5, 2002, U.S. Provisional Application Ser. No. 60/358,681, entitled "QUASI-ISOTHERMAL BRAYTON CYCLE ENGINE," filed Feb. 21, 2002, and U.S. Provisional Application No. 60/397,193, entitled "QUASI-ISOTHERMAL BRAYTON CYCLE ENGINE," filed Jul. 18, 2002. The Applicant hereby incorporates by reference each of the above-referenced applications.

TECHNICAL FIELD OF THE INVENTION

The present invention relates to a gerotor apparatus that functions as a compressor or expander. The gerotor apparatus may be applied generally to Brayton cycle engines and, more particularly, to a quasi-isothermal Brayton cycle engine.

BACKGROUND OF THE INVENTION

For mobile applications, such as an automobile or truck, it is generally desirable to use a heat engine that has the following characteristics: internal combustion to reduce the need for heat exchangers; complete expansion for improved efficiency; isothermal compression and expansion; high power density; high-temperature expansion for high efficiency; ability to efficiently "throttle" the engine for part-load conditions; high turn-down ratio (i.e., the ability to operate at widely ranging speeds and torques); low pollution; uses standard components with which the automotive industry is familiar; multifuel capability; and regenerative braking.

There are currently several types of heat engines, each with its own characteristics and cycles. These heat engines include the Otto Cycle engine, the Diesel Cycle engine, the Rankine Cycle engine, the Stirling Cycle engine, the Erickson Cycle engine, the Carnot Cycle engine, and the Brayton Cycle engine. A brief description of each engine is provided below.

The Otto Cycle engine is an inexpensive, internal combustion, low-compression engine with a fairly low efficiency. This engine is widely used to power automobiles.

The Diesel Cycle engine is a moderately expensive, internal combustion, high-compression engine with a high efficiency that is widely used to power trucks and trains.

The Rankine Cycle engine is an external combustion engine that is generally used in electric power plants. Water is the most common working fluid.

The Erickson Cycle engine uses isothermal compression and expansion with constant-pressure heat transfer. It may be implemented as either an external or internal combustion cycle. In practice, a perfect Erickson cycle is difficult to achieve because isothermal expansion and compression are not readily attained in large, industrial equipment.

2

The Carnot Cycle engine uses isothermal compression and expansion and adiabatic compression and expansion. The Carnot Cycle may be implemented as either an external or internal combustion cycle. It features low power density, mechanical complexity, and difficult-to-achieve constant-temperature compressor and expander.

The Stirling Cycle engine uses isothermal compression and expansion with constant-volume heat transfer. It is almost always implemented as an external combustion cycle. It has a higher power density than the Carnot cycle, but it is difficult to perform the heat exchange, and it is difficult to achieve constant-temperature compression and expansion.

The Stirling, Erickson, and Carnot cycles are as efficient as nature allows because heat is delivered at a uniformly high temperature, T_{hot} , during the isothermal expansion, and rejected at a uniformly low temperature, T_{cold} , during the isothermal compression. The maximum efficiency, η_{max} , of these three cycles is:

$$\eta_{max} = 1 - \frac{T_{cold}}{T_{hot}}$$

This efficiency is attainable only if the engine is "reversible," meaning that the engine is frictionless, and that there are no temperature or pressure gradients. In practice, real engines have "irreversibilities," or losses, associated with friction and temperature/pressure gradients.

The Brayton Cycle engine is an internal combustion engine that is generally implemented with turbines and is generally used to power aircraft and some electric power plants. The Brayton cycle features very high power density, normally does not use a heat exchanger, and has a lower efficiency than the other cycles. When a regenerator is added to the Brayton cycle, however, the cycle efficiency increases. Traditionally, the Brayton cycle is implemented using axial-flow, multi-stage compressors and expanders. These devices are generally suitable for aviation in which aircraft operate at fairly constant speeds; they are generally not suitable for most transportation applications, such as automobiles, buses, trucks, and trains, that must operate over widely varying speeds.

The Otto cycle, the Diesel cycle, the Brayton cycle, and the Rankine cycle all have efficiencies less than the maximum because they do not use isothermal compression and expansion steps. Further, the Otto and Diesel cycle engines lose efficiency because they do not completely expand high-pressure gases, and simply throttle the waste gases to the atmosphere.

Reducing the size and complexity, as well as the cost, of Brayton cycle engines is important. In addition, improving the efficiency of Brayton cycle engines and/or their components is important. Manufacturers of Brayton cycle engines are continually searching for better and more economical ways of producing Brayton cycle engines.

SUMMARY OF THE INVENTION

According to one embodiment of the invention, a gerotor apparatus includes a housing, an outer gerotor disposed within the housing, an inner gerotor disposed within the outer gerotor, and a valve plate rigidly coupled to the housing that has a first surface positioned adjacent an end of the outer gerotor. This gerotor apparatus may include many different features depending on its application and use. For example, the valve plate may include an inlet port, an exhaust port, and

a compression control element slidably engaged with either the inlet port or exhaust port to control a compression ratio of the gerotor apparatus.

As another example, the gerotor apparatus may include a proximity sensor coupled to the valve plate to sense a gap between an end of the outer gerotor and the surface of the valve plate and means for adjusting the gap between the end of the outer gerotor and the valve plate. The gerotor apparatus may also include a sealing ring disposed around a perimeter of the first surface of the valve plate and an actuation system operable to control a gap between the sealing ring and the end of the outer gerotor to control leakage of gas into a lubricant.

As another example, the gerotor apparatus may include a seal plate having a circular hole formed therein rigidly coupled to the outer gerotor, a seal plug disposed within the circular hole of the seal plate, wherein the seal plug has a circular hole formed therein, and a first bearing disposed within the circular hole of the seal plug. The first bearing supports the outer gerotor.

As another example, the gerotor apparatus may include a gearing system operable to drive the outer and inner gerotors that is either external or internal. In one embodiment, a gear housing is disposed within the inner gerotor and houses at least one gear operable to synchronize a rotation of the outer gerotor with a rotation of the inner gerotor.

According to one embodiment of the invention, a gerotor apparatus includes an outer gerotor having an outer gerotor chamber, an inner gerotor, at least a portion of which is disposed within the outer gerotor chamber, and a synchronizing apparatus operable to control the rotation of the inner gerotor relative to the outer gerotor. The inner gerotor includes one or more entrance passages operable to communicate a lubricant into the outer gerotor chamber.

Embodiments of the invention provide a number of technical advantages. Embodiments of the invention may include all, some, or none of these advantages. One technical advantage is a more compact and lightweight Brayton cycle engine having simpler gas flow paths, less loads on bearings, and lower power consumption. Some embodiments have fewer parts than previous Brayton cycle engines. Another advantage is that some embodiments of the invention introduce a simpler method for regulating leakage from gaps. An additional advantage is that the oil path is completely separated from the high-pressure gas preventing heat transfer from the gas to the oil. A further advantage is that precision alignment between the inner and outer gerotors may be achieved through a single part (e.g., a rigid shaft). A still further advantage is that drive mechanisms disclosed herein have small backlash and low wear.

Other technical advantages are readily apparent to one skilled in the art from the following figures, descriptions, and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the invention, and for further features and advantages, reference is now made to the following description, taken in conjunction with the accompanying drawings, in which:

FIGS. 1 and 2 both illustrate block diagrams of various embodiments of a quasi-isothermal Brayton cycle engine;

FIG. 3 shows a small-diameter gerotor apparatus using spring-loaded seals according to an embodiment of the invention;

FIG. 4 shows a medium-diameter gerotor apparatus using spring-loaded seals on the inner diameter and sealing rings at the outer diameter according to an embodiment of the invention;

FIG. 5 shows a large-diameter gerotor apparatus using spring-loaded seals on the inner diameter and sealing rings on the middle and outer diameters according to an embodiment of the invention;

FIG. 6A shows one embodiment of a circular spring-loaded face seal;

FIG. 6B shows a gerotor-shaped spring-loaded face seal;

FIG. 7 shows a sealing ring according to an embodiment of the invention;

FIG. 8A shows a ceramic coating on the outer surface of gerotor teeth according to one embodiment of the invention;

FIG. 8B shows a different embodiment for attaching a ceramic coating to gerotor teeth formed from metal;

FIG. 9 illustrates a system for controlling the compression ratio of a gerotor compressor using a slider on the face plate according to one embodiment of the invention;

FIGS. 10 through 46 illustrate various embodiments of a gerotor apparatus of a quasi-isothermal Brayton cycle engine;

FIG. 47 shows a method for balancing the pressure across an outer gerotor according to an embodiment of the invention;

FIGS. 48 through 52 illustrate various embodiments of a gerotor apparatus of a quasi-isothermal Brayton cycle engine; FIGS. 53A and 53B illustrate side and top views, respectively, of an anti-backlash gear system;

FIGS. 54 through 58 illustrate various embodiments of a gerotor apparatus including a lubricant to reduce friction between an inner gerotor and an outer gerotor;

FIGS. 59 through 63 illustrate various embodiments of a gerotor apparatus including alignment guides and alignment members;

FIGS. 64A and 64B illustrate an inner gerotor having a hypocycloid shape;

FIGS. 65A and 65B illustrate an inner gerotor having an epicycloid shape;

FIGS. 66 through 69 illustrate various embodiments of an engine system having an integral gerotor compressor and gerotor expander;

FIGS. 70 through 79 illustrate various embodiments of an engine system including a gerotor apparatus having an outer gerotor comprising openings allowing gases to travel through the outer perimeter of the outer gerotor;

FIGS. 80 through 83 illustrate various methods of manufacturing a gerotor apparatus;

FIGS. 84 through 87 illustrate various methods of a gerotor apparatus including an electric motor or generator integral with the gerotor apparatus;

FIGS. 88 through 91 illustrate methods of generating patterns for alignment tracks in an outer gerotor or an inner gerotor of a gerotor apparatus;

FIG. 92 illustrates an engine system including a compressor, an expander, one or more additional compressors and/or expanders, and a drive apparatus, in which the compressor and expander are separately clutched from the drive apparatus according to an embodiment of the invention;

FIGS. 93 through 94 illustrate example embodiments of a gerotor apparatus including an outer gerotor, and inner gerotor, and a synchronization system operable to synchronize the relative rotation of the outer gerotor and inner gerotor;

FIG. 95 illustrates a gerotor apparatus in which gases may flow into and out of the gerotor apparatus through an opening in a central shaft; and

FIGS. 96 through 101 illustrate various embodiments of a gerotor apparatus of a quasi-isothermal Brayton cycle engine.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS OF THE INVENTION

FIGS. 1 through 101 below illustrate example embodiments of a gerotor apparatus within the teachings of the present invention. Generally, the following detailed description describes gerotor apparatuses as being used in the context of a gerotor compressor; however, the following gerotor apparatuses may function equally as well as gerotor expanders or other suitable gerotor apparatuses. In addition, the present invention contemplates that the gerotor apparatuses described below may be utilized in any suitable application; however, the gerotor apparatuses described below are particularly suitable for a quasi-isothermal Brayton cycle engine, such as the one described in U.S. Pat. No. 6,336,317 B1 (“the ‘317 patent”) issued Jan. 8, 2002, and assigned to the Texas A&M University System. The ‘317 patent, which is herein incorporated by reference, describes the general operation of a gerotor compressor and/or a gerotor expander. Hence, the operation of the gerotor apparatuses described below are not described in detail.

An example of an application in which the gerotor apparatuses described herein may be utilized is illustrated in FIGS. 1 and 2. FIGS. 1 and 2 both show block diagrams of quasi-isothermal brayton cycle engines. FIG. 1 illustrates two embodiments of a single shaft arrangement and FIG. 2 illustrates two embodiments of a split shaft arrangement. Referring to FIG. 1, ambient air 400 is received and compressed in a compressor 402. The compressed air is then countercurrently heated in a heat exchanger 404 using the thermal energy from exhaust gases 406. In a combustor 408, a fuel 410 is introduced into the prewarmed air and ignited. The high pressure combustion gases flow into an expander 412 where work is produced, as denoted by generator 414. After air expands in expander 412, the hot air flows through heat exchanger 404 and preheats the air flowing from compressor 402 before it reaches combustor 408. The air exits heat exchanger 404 as exhaust gas 406. To minimize work requirements for compressor 402, atomized liquid water may be sprayed into ambient air 400, cooling ambient air 400 during compression in compressor 402. The outlet temperature from compressor 402 is nearly the same as the inlet temperature. Thus, the compression is considered to be “quasi-isothermal.” The operation as described above for FIG. 1 is substantially similar for the block diagrams of FIG. 2, except FIG. 2 includes clutches and gears to facilitate the split shaft arrangement.

Embodiments of the invention may provide a number of technical advantages, such as a more compact and lightweight design of a gerotor compressor or expander having simpler gas flow paths, less loads on bearings, and lower power consumption. In addition, some embodiments of the invention introduce a simpler method for regulating leakage from gaps, provide for precision alignment between the inner and outer gerotors, and introduce drive mechanisms that have small backlash and low wear. These technical advantages may be facilitated by all, some, or none of the embodiments described below.

FIGS. 3 through 5 illustrate various embodiments of a gerotor apparatus 1a. FIG. 3 illustrates a relatively small diameter gerotor apparatus, FIG. 4 illustrates a relatively medium diameter gerotor apparatus, and FIG. 5 illustrates a relatively large diameter gerotor apparatus. Referring to FIG. 3, gerotor apparatus 1a includes a housing 2a, an outer gerotor 4a disposed within housing 2a, and an inner gerotor 6a disposed within outer gerotor 4a. In addition, a valve plate 8 is rigidly coupled to housing 2a and includes a first surface 9

positioned adjacent an end of outer gerotor 4a. Outer gerotor 4a is cantilevered at the top of housing 2a by a bearing 10, which allows outer gerotor 4a to be rotatably coupled to housing 2a. A bearing 12 also supports outer gerotor 4a. Bearing 12 is coupled to a shaft 14 that is rigidly coupled to valve plate 8 at a lower end and rotatably coupled to outer gerotor 4a by bearing 12 at its upper end. Inner gerotor 6a is rotatably coupled to shaft 14 with a bearing 18. Inner gerotor 6a includes an inner gear 20 coupled thereto that meshes with an outer gear 22 on outer gerotor 4a. Inner gear 20 is rotatably coupled to shaft 14 via a bearing 24.

In general, a rotation of shaft 16 (as denoted by arrow 26) rotates outer gerotor 4a within housing 2a. The rotation of outer gerotor 4a causes a rotation of inner gerotor 6a through outer gear 22 and inner gear 20. Since the embodiments illustrated in FIGS. 3 through 5 show gerotor apparatus 1a as an expander, high-pressure air enters gerotor apparatus 1a through a gas inlet 28 into a chamber 29 disposed between inner gerotor 6a and outer gerotor 4a and eventually exits a gas outlet (not explicitly shown), as denoted by reference numeral 30. Because of the moving parts associated with bearings and gears, an oil or other suitable lubricant is typically circulated through appropriate portions of gerotor apparatus 1a. As denoted by reference numeral 32, oil may be circulated into gerotor apparatus 1a. The oil works its way past bearing 18 and into a gear chamber 34 in order to lubricate gears 20 and 22 as well as bearing 24. Because of centrifugal forces the coolant will be located on an outer periphery of gear chamber 34, as denoted by reference numeral 36. A dip tube 38 or other suitable device transports the oil back down through the wall of outer gerotor 4 so that it may exit an exit port, as denoted by reference numeral 40.

To prevent any oil from leaking into the gas contained in chamber 29, seals are often utilized. In the embodiment illustrated in FIG. 3, spring loaded seals 42 are utilized. Spring loaded seals 42 may be any suitable spring loaded seals, such as standard face seals that are typically made of graphite or some other low friction solid. Face seals reduce the leakage of oil or other lubricant into the gas contained in chamber 29. As illustrated in FIG. 3, spring loaded seals 42 are used between inner gerotor 6a and outer gerotor 4a, between inner gerotor 6a and surface 9 of valve plate 8, and between outer gerotor 4a and surface 9 of valve plate 8. Spring loaded seals 42 may have any suitable shape; however, two example shapes are shown in FIGS. 6A and 6B.

A circular spring loaded seal 42 is illustrated in FIG. 6A, and a gerotor-shaped spring loaded seal 42 is illustrated in FIG. 6B. A gerotor-shaped spring loaded seal may be utilized where surface velocities are relatively low, such as between inner gerotor 6a and outer gerotor 4a or between inner gerotor 6a and surface 9 of valve plate 8. A circular spring loaded seal may also be used in these places in addition to being used between outer gerotor 4a and surface 9 of valve plate 8, which experiences greater surface velocities based on its distance from the center of gerotor apparatus 1a. Because gerotor apparatus 1a in FIG. 3 is a relatively small diameter gerotor apparatus, spring loaded seals 42 may be utilized where the surface velocities are higher. However, as the diameter of gerotor apparatus 1a increases, then a spring loaded seal 42 may not be adequate to provide proper sealing. In this case, a different type of sealing system may be needed.

Both FIGS. 4 and 5 illustrate a sealing ring 44 that may be utilized where surface velocities are high within gerotor apparatus 1a. The details of sealing ring 44 are described below in conjunction with FIG. 7. Sealing ring 44, in one embodiment,

is associated with valve plate 8; however, in other embodiments sealing ring 44 may be located in other suitable locations.

FIG. 7 illustrates an actuation system 45 that may be associated with sealing ring 44 according to one embodiment of the present invention. In the illustrated embodiment, actuation system 45 includes sealing ring 44, an air supply source 47, a hot wire anemometer 48, a controller 49, and an actuator 50.

Sealing ring 44 may be any suitable shape and formed from any suitable material; however, in one embodiment, sealing ring 44 is generally a circular seal formed from metal. Sealing ring 44 has a plurality of apertures 51 formed therein. Any suitable number of apertures 51 may be utilized and they may be spaced around sealing ring 44 in any suitable manner. Apertures 51 are coupled to air supply 47 via any suitable conduit 52. Air supply source 47 is operable to deliver air or other suitable gas through conduit 52, through apertures 51, and into a gap 53 existing between sealing ring 44 and a rotating surface 46, which in this case may be considered to be an end of outer gerotor 4a. In order to control gap 53, hot wire anemometer 48, which may be any suitable flow-measurement device, measures the rate of air being delivered into gap 53. Hot wire anemometer 48 is coupled to controller 49 and sends the measured rate to controller 49 so that controller 49 may control actuator 50 in order to translate sealing ring 44 either toward or away from rotating surface 46. Controller 49 may any suitable controller operable to energize actuator 50 and actuator 50 may be any suitable actuator operable to translate sealing ring 44. It is preferable that gap 53 be relatively small to minimize any leakage of oil or other lubricant into the gas being either compressed or expanded. Actuation system 45 is only one example of an actuation system that may be utilized to control gap 53. The present invention contemplates other actuation systems that are suitable to control gap 53.

It may also be important to control the gaps between the teeth of gerotors. FIGS. 8A and 8B show gerotors with two layers. As a non-limiting example, FIG. 8A shows a gerotor with a metal layer and a ceramic layer. More particularly, FIG. 8A illustrates one embodiment of a ceramic coating 54 applied to the outer surface of a tooth 55 of a gerotor, which may generally correspond to an inner gerotor or an outer gerotor. Materials other than ceramic having low coefficients of thermal expansion may also be utilized on the teeth. A low coefficient of thermal expansion is considered to be no more than approximately 2.times.10.sup.-6 m/(mK). Ceramic coating 54 may be coupled to the teeth of a inner gerotor in any suitable manner. In an illustrated embodiment, ceramic coating 54 is held in place by knobs 56. In addition, the ceramic coating 54 may also be segmented (as illustrated) to allow for different thermal expansion of coating 54 and the material used for the gerotors inner.

As another non-limiting example, FIG. 8B shows another gerotor with a metal layer and a ceramic layer. More particularly, FIG. 8B shows a different embodiment for attaching a ceramic coating 54 to the teeth of an inner gerotor. In this embodiment, the ceramic coating 54 forms the shape of the teeth while the bulk of inner gerotor has protrusions 57 thereon that couple ceramic coating 54 thereto. In other embodiments, the entire inner gerotor 6a may be formed from a ceramic material or other suitable material having a low coefficient of thermal expansion.

FIG. 9 illustrates a system for controlling the compression ratio of gerotor apparatus 1a using a compression control element 58 with valve plate 8 according to one embodiment of the present invention. As illustrated in FIG. 9, a compression

control element 58 is associated with gas outlet 30 of valve plate 8. Also illustrated is gas inlet 28 of valve plate 8. As described above in conjunction with FIGS. 3 through 5, air or other suitable gas enters gerotor apparatus 1a through gas inlet 28 and eventually exits out of gerotor apparatus 1a through gas outlet 30. The shape and size of gas inlet 28 and gas outlet 30 may be formed in valve plate 8 in order to optimize the efficiency and operation of gerotor apparatus 1a. However, in the illustrated embodiment, the shape and size of gas outlet 30 may be changed by compression control element 58. For example, compression control element 58 may be slidably engaged with valve plate 8 in any suitable manner. This allows compression control element 58 to control the compression ratio of gerotor apparatus 1a based on its position within gas outlet 30. As illustrated in the upper figure, gas outlet 30 has a greater area than gas outlet 30 in the lower figure, which means that the gas exiting gerotor apparatus 1a through gas outlet 30 in the lower figure is compressed more than the gas flowing out of gerotor apparatus 1a in the upper figure.

FIGS. 10 through 15 illustrate various embodiments of a gerotor apparatus 1b. With reference to FIG. 10, gerotor apparatus 1b includes a housing 2b, an outer gerotor 4b disposed within housing 2b, and an inner gerotor 6b disposed within outer gerotor 4b. Gerotor apparatus 1b also includes an inner shaft 60 rigidly coupled at a first end to housing 2b, a hollow shaft 62 rotatably coupled to inner shaft 60 via bearings 63 and 64, and an offset support plate 65 coupled to a second end of inner shaft 60. Inner gerotor 6b is rigidly coupled to hollow shaft 62 and an inner gear 66 is rigidly coupled to an end of hollow shaft 62. Inner gear 66 meshes with an outer gear 67 that is coupled to outer gerotor 4b. Outer gerotor 4b is rotatably coupled to offset support plate 65 via a bearing 68 and also rotatably coupled to an end of housing 2b via bearings 69 and 70 through a rotating shaft 71. Generally, when rotating shaft 71 rotates, it rotates outer gerotor 4b, which rotates inner gerotor 6b via gears 66 and 67.

A seal plate 72 is also coupled to outer gerotor 4b. Seal plate 72 has a concentrically located circular hole formed therein. A seal plug 73 is positioned within the hole formed in seal plate 72 by means of a bearing 74. Seal plug 73 has an eccentrically located circular hole 75 formed therein. Hole 75 is concentric with hollow shaft 62. Seal plug 73 also rotatably couples to hollow shaft 62 via a bearing 76. In the illustrated embodiment, both bearings 74 and 76 used for rotatably mounting seal plug 73 are "soft mounted," meaning they are mounted to seal plate 72 and hollow shaft 62 in a manner that is compliant in the radial direction but rigid in the axial direction. This prevents, among other things, excessive forces from being applied to bearings 74 and 76 due to misalignment. Seal plug 73 along with bearings 74 and 76 also provide additional support for outer gerotor 4b to reduce some of the "cantilevering" effect.

Because outer gerotor 4b is mounted in a cantilevered manner, bearings 69 and 70 may be subject to very high loads, which may shorten their life. To minimize this effect, bearings 69 and 70 may be substantially unloaded by applying a high pressure gas to a portion of the outer surface of outer gerotor 4b. Any suitable pressurized air source 77 may be utilized and the pressurized air enters housing 2b via any suitable port 78 formed in a perimeter of housing 2b. The loads on bearings 69 and 70 result from radial forces coming from the portion of outer gerotor 4b that has high-pressure gases acting on its inner surface. These loads may be substantially reduced by applying high-pressure air 77 into a portion of the outside surface of outer gerotor 4b that opposes the high pressure gas on the inside of outer gerotor 4b. A natural source of this

natural gas 77 would be the high pressure gas produced by the compressor. This ensures that the two counteracting pressures are substantially the same during transient.

Gas leakage from high pressure regions to low pressure regions in gerotor apparatus 1b may be reduced by carefully controlling gaps between various components. Gaps may change from two actions: centrifugal forces and thermal growth. Centrifugal forces affect only in the radial direction, so they affect leakage through gaps at the gerotor tips. This may be minimized by using hole patterns in inner gerotor 6b and outer gerotor 4b that make each component equally compliant so they both expand together. Thermal growth may be regulated by ensuring that inner gerotor 6b and outer gerotor 4b are substantially the same temperature. The working surfaces of inner gerotor 6b and outer gerotor 4b experience substantially the same temperatures from the working gases. The outer surfaces of outer gerotor 4b is cooled by housing 2b and the inner surface of inner gerotor 6b is cooled by the flowing lubricating oil. By controlling the oil temperature the temperatures of the two components may be matched. A proximity sensor 80 may be located on housing 2b to measure the gap between outer gerotor 4b and the inside surface of housing 2b. Oil temperature may then be controlled as needed to regulate this gap. Proximity sensor 80 may provide feedback to any suitable controller to allow the controller to set a desired temperature for the lubricating oil.

Another way of controlling gas leakage from high pressure regions to low pressure regions in gerotor apparatus 1b, especially past gerotor tips and faces, is to roughen the surfaces of one or more components of gerotor apparatus 1b. Any suitable roughening may be employed, such as dimpling the surfaces with small holes, sandblasting, or other suitable surface roughening techniques. This surface roughening may be applied to surfaces in contact with the gas, such as outer gerotor 4b, inner gerotor 6b, seal plate 72, seal plug 73, etc. The present invention contemplates that this surface roughening may apply to any of the embodiments of the gerotor apparatuses described in this detailed description.

FIG. 11 illustrates another embodiment of gerotor apparatus 1b in which the offset support plate 65 is non-existent. In this embodiment, the end of inner shaft 60 that was previously supported by offset support plate 65 is now supported by bearings 74 and 76 of seal plug 73. In one embodiment, bearing 63 is substantially in the same plane as bearings 74 and 76, to provide support to outer gerotor 4b.

FIG. 12 illustrates another embodiment of gerotor apparatus 1b. This embodiment is substantially similar to the embodiment illustrated in FIG. 11; however, in the embodiment illustrated in FIG. 12 outer gerotor 4b is not rotatably coupled to the housing via bearings 69 and 70. Instead, outer gerotor 4b is supported by bearings 74 and 76 of seal plug 73. In addition, there is no support for outer gerotor 4b at the top of housing 2b. Therefore, seal plug 73 includes additional bearings 81 and 82. This embodiment requires that both seal plate 72 and seal plug 73 be thicker than the previous embodiments illustrated in FIGS. 10 and 11. To provide additional stability for outer gerotor 4b, inner shaft 60 is coupled to seal plug 73 via an anti-rotation mount 83. Anti-rotation mount 83 may any suitable configuration in order to carry out its function of coupling inner shaft 60 to seal plug 73.

FIG. 13 illustrates another embodiment of gerotor apparatus 1b. The embodiment illustrated in FIG. 13 is substantially similar to the embodiment illustrated in FIG. 12; however, the embodiment illustrated in FIG. 13 does away with seal plug bearings 81 and 82 and instead uses a large diameter bearing 84 disposed around an outer periphery of the end of outer gerotor 4b.

FIG. 14 illustrates another embodiment of gerotor apparatus 1b. The embodiment illustrated in FIG. 14 is substantially similar to the embodiment illustrated in FIG. 12; however, anti-rotation mount 83 does not exist in the embodiment of FIG. 14. Instead, a reference wheel 85 prevents rotation of seal plug 73. Reference wheel 85 is rotatably mounted to housing 2b with a bearing 86. An outer periphery of reference wheel 85 engages rotating shaft 71 that is coupled to outer gerotor 4b. Making the diameter of reference wheel 85 large relative to the shaft diameter slows the rotation rate of reference wheel 85, thereby extending its life.

FIG. 15 illustrates another embodiment of gerotor apparatus 1b. In this embodiment, inner shaft 60 is rigidly coupled to both ends of housing 2b by using an offset support plate 65 similar to the one used in the embodiment of FIG. 10. Accordingly, rotating shaft 71 is off-center and in order to rotate outer gerotor 4b rotating shaft 71 includes a drive gear 88 that couples to a driven gear 89 that couples to outer gerotor 4b. Rotating shaft 71 is rotatably coupled to housing 2b via bearing 90 and 91.

FIGS. 16 through 20 illustrate various embodiments of a gerotor apparatus 1c. As illustrated in FIG. 16, gerotor apparatus 1c includes a housing 2c, an outer gerotor 4c disposed within housing 2c, and an inner gerotor 6c disposed within outer gerotor 4c. Gerotor apparatus 1c also includes a hollow shaft 94 rigidly coupled to housing 2c, and an inner shaft 95 disposed within hollow shaft 94 and rotatably coupled to each end of housing 2c by a pair bearings 96 and 110. Inner gerotor 6c is rigidly coupled to inner shaft 95 and an inner gear 97 is also coupled to inner shaft 95. Inner gear 97 meshes with an outer gear 98 that is rigidly coupled to outer gerotor 4c. Outer gerotor 4c is rotatably coupled to hollow shaft 94 via a pair of bearings 99 and 100. Similar to gerotor apparatus 1b of FIGS. 10 through 15, outer gerotor 4c also includes a seal plate 101 coupled thereto and a seal plug 102 disposed in a hole in seal plate 101 by bearings 103 and 104.

In general, in this embodiment, inner shaft 95 rotates, which rotates inner gerotor 6c in addition to inner gear 97, which rotates outer gear 98 and outer gerotor 4c. Gerotor apparatus 1c may also have a pressurized air source 105 coupled to a perimeter of housing 2c that is operable to deliver pressurized air through a port 106 and into housing 2c to supply a force to at least a portion of an outside perimeter of outer gerotor 4c. Gerotor apparatus may also have a proximity sensor 107 that functions in a similar manner as proximity sensor 80 of gerotor apparatus 1b, as described above.

FIG. 17 illustrates another embodiment of gerotor apparatus 1c. This embodiment is substantially similar to the embodiment illustrated in FIG. 16; however, in the embodiment illustrated in FIG. 17 seal plug 102 and corresponding bearing 103 and 104 do not exist. In this case, sealing is accomplished simply by maintaining a small gap between inner gerotor 6c and seal plate 101.

FIG. 18 illustrates another embodiment of gerotor apparatus 1c. This embodiment is substantially similar to the embodiment illustrated in FIG. 17; however, in the embodiment illustrated in FIG. 18 seal plate 101 is coupled to inner gerotor 6c instead of outer gerotor 4c. In this case, sealing is accomplished simply by maintaining a small gap between outer gerotor 4c and seal plate 101.

FIG. 19 illustrates another embodiment of gerotor apparatus 1c. This embodiment is substantially similar to the embodiment illustrated in FIG. 16; however, in the embodiment illustrated in FIG. 19 embodiment, hollow shaft 94 is coupled to housing 2c with anti-rotation pin 108 instead of being rigidly coupled to housing 2c as in FIG. 16. Anti-rotation pin 108 facilitates a "floating" arrangement for hol-

11

low shaft **94**. In other words, housing **94** has a small amount of movement in both the axial and radial directions; however, hollow shaft **94** is prevented from rotating by anti-rotation pin **108** that fits within an aperture **109** in housing **2c**. This allows hollow shaft **94** to be referenced to inner shaft **94** rather than housing **2c**, which reduces the precision requirements of housing **2c**.

FIG. **20** illustrates another embodiment of gerotor apparatus of **1c**. This embodiment is substantially similar to the embodiment illustrated in FIG. **19**; however, in the embodiment illustrated in FIG. **20** gerotor apparatus **1c** is a more compact design in which hollow shaft **94** is much shorter than in previous embodiments. And hollow shaft **94** is also coupled to seal plug **102** via a connector **111**. Because connector **111** couples hollow shaft **94** and seal plug **102**, plug bearings **103** and **104** are “hard mounted” in this embodiment in order to support outer gerotor **4c**, thereby facilitating the shortening of the length of gerotor apparatus **1c**.

FIGS. **21** through **24** illustrate various embodiments of a gerotor apparatus **1d**. Referring to FIG. **21**, gerotor apparatus **1d** includes a housing **2d**, an outer gerotor **4d** disposed within housing **2d**, and an inner gerotor **6d** disposed within outer gerotor **4d**. Gerotor apparatus **1d** also includes a gear housing **115** disposed within inner gerotor **6d**. Gear housing **115** houses an idler gear **116** that is operable to synchronize a rotation of outer gerotor **4d** with a rotation of inner gerotor **6d**, as described below.

Outer gerotor **4d** is rigidly coupled to an upper shaft **117**, which is rotatably coupled to housing **2d** and inner gerotor **6d** is rigidly coupled to a lower shaft **118** that is rotatably coupled to housing **2d**. Upper shaft **117** has a gear **119** coupled at an end thereof that is disposed within gear housing **115** and lower shaft **118** includes a gear **120** that is also disposed within gear housing **115**. Both gear **119** and gear **120** are coupled to idler gear **116**. Therefore, a rotation of upper shaft **117** as denoted by arrow **121** rotates gear **119**, which rotates idler gear **116**, which rotates gear **120**, which rotates lower shaft **118**, which rotates inner gerotor **6d**. The rotation of upper shaft **117** also rotates outer gerotor **4d**. Idler gear **117** may be coupled to gear housing **115** in any suitable manner, such as by bearings. The gear ratio between gears **119** and **120** is suitably selected to give the proper relative rotation between inner gerotor **6d** and outer gerotor **4d**. An advantage of having gear housing **115** disposed within inner gerotor **6d** is compactness.

Similar to previous gerotor apparatuses described above, gerotor apparatus **1d** may also include a pressurized air source **122** coupled to a port **123** formed in a perimeter of housing **2d**. Pressurized air source **122** is operable to deliver pressurized air through port **123** and into housing **2d** to supply a force to at least a portion of an outside perimeter of outer gerotor **4d**. In addition, gerotor apparatus **1d** may also include a proximity sensor **124** that functions in the same manner as previous proximity sensors as described above.

FIG. **22** illustrates another embodiment of gerotor apparatus of **1d**. In this embodiment, upper shaft **117** and lower shaft **118** are rigidly coupled to housing **2d** instead of rotatably coupled as in FIG. **21**. In addition, upper shaft **117** and lower shaft **118** are both rigidly coupled to gear housing **115**. In order to rotate both outer gerotor **4d** and inner gerotor **6d**, an upper hollow shaft **125** is rotatably coupled to upper shaft **117** and rigidly coupled to outer gerotor **4d**, while a lower hollow shaft **126** is rotatably coupled to lower shaft **118** and rigidly coupled to inner gerotor **6d**. In order to drive outer gerotor **4d**, upper hollow shaft **125** includes a driven gear **127** that meshes with a drive gear **128** that is coupled to a rotating shaft **129**. Rotating shaft **129** rotatably couples to housing **2d** with bear-

12

ings **130** and **131**. Accordingly, the rotation of rotating shaft **129** as denoted by arrow **132** rotates drive gear **128**, which rotates driven gear **127**, which rotates upper hollow shaft **125**, which rotates outer gerotor **4d**. In addition, the rotation of upper hollow shaft **125** rotates a gear **133** disposed within gear housing **115** which rotates an idler gear **134** that is rotatably coupled to gear housing **115**, which rotates a gear **135** that is rigidly coupled to lower housing shaft **126**, thereby rotating inner gerotor **6d**. An advantage of the embodiment illustrated in FIG. **22** is that housing **2d** does not have to be made in a precise manner. The centers of rotation are established through the precision of shafts, which is relatively easy to achieve.

FIG. **23** illustrates another embodiment of gerotor apparatus of **1d**. The embodiment illustrated in FIG. **23** is substantially similar to the embodiment illustrated in FIG. **21**; however, in the embodiment in FIG. **23**, neither upper shaft **117** nor lower shaft **118** have gears at their ends. Instead, idler gear **116** couples a gear **136** that is coupled to a seal plate **137** of outer gerotor **4d** and a gear **138** that couples to inner gerotor **6d**. Idler gear **116** is rotatably coupled to gear housing **115** in a similar manner and may be any suitable idler gear. Because there are two different centers of rotation on gear housing **115**, gear housing **115** cannot rotate and is held stationary.

FIG. **24** illustrates another embodiment of gerotor apparatus **1d**. The embodiment illustrated in FIG. **24** is similar to the embodiment illustrated in FIG. **23**; however, in the embodiment in FIG. **24** both upper shaft **117** and lower shaft **118** are rigidly coupled to housing **2d** instead of being rotatably coupled. In this case, inner gerotor **6d** is rotatably coupled to lower shaft **118** via bearings **139** and **140** and outer gerotor **4d** is rotatably coupled to upper shaft **117** with a hollow shaft **141** and pair of bearings **142** and **143**. In addition, hollow shaft **141** has a driven gear **144** rigidly coupled thereto that meshes with a drive gear **145** that couples to rotating shaft **146**, which is rotatably coupled with housing **2d** with a pair of bearings **147** and **148**. Thus, a rotation of rotating shaft **146** (as denoted by reference number **149**) rotates drive gear **145**, which drives driven gear **144**, which rotates both hollow shaft **141** and outer gerotor **4d**, which rotates outer gear **136**, which rotates idler gear **116**, which rotates inner gear **138**, which then rotates inner gerotor **6d**. An advantage of this embodiment is that housing **2d** does not have to be made in a precise manner. The centers of rotation are established through the precision of the shafts, which is relatively easy to achieve.

FIG. **25** illustrates an embodiment of a gerotor apparatus **1e**. Gerotor **1e** includes a housing **2e**, an outer gerotor **4e** disposed within housing **2e** and an inner gerotor **6e** disposed within outer gerotor **4e**. Gerotor apparatus **1e** also includes an upper shaft **150** that is rotatably coupled to housing **2e** and an inner shaft **151** rotatably coupled to housing **2e**. Shaft **150** is rigidly coupled to outer gerotor **4e** and inner shaft **151** is rigidly coupled to inner gerotor **6e**.

The rotation of both outer gerotor **4e** and inner gerotor **6e** is facilitated by an external gearing system **152** that includes a rotating shaft **153** having a first gear **154** and a second gear **155**. First gear **154** meshes with and drives an upper gear **156** and second gear **155** meshes with and drives a lower gear **157**. Upper gear **156** rigidly couples to upper shaft **150** while lower gear **157** rigidly couples to inner shaft **151**, thereby providing the rotation of outer gerotor **4e** and inner gerotor **6e**, respectively. Hence, a rotation of shaft **153** as denoted by reference numeral **158** rotates both first and second gears **154** and **155**. These rotations facilitate the rotation of upper gear **156** and lower gear **157**, respectively, which rotates both outer gerotor **4e** and inner gerotor **6e**, respectively. As in previous gerotor apparatuses, gerotor apparatus **1e** may also include a pressur-

ized air source **159** coupled to a port **160** formed in a perimeter of housing **2e**. Pressurized air source **159** is operable to deliver pressurized air through port **160** and into housing **2e**. In addition, gerotor apparatus **1e** may also include a proximity sensor **161** that functions in the same manner as previous proximity sensors described above. Alternatively, the input power could be delivered through shafts **150** or **151**.

FIGS. **26** through **28** illustrate various embodiments of a gerotor apparatus **1f**. Referring to FIG. **26**, gerotor apparatus **1f** includes a housing **2f**, an outer gerotor **4f** disposed within housing **2f**, and an inner gerotor **6f** disposed within outer gerotor **4f**. In addition, gerotor **1f** includes a hollow shaft **165** rigidly coupled to housing **2f**, and an inner shaft **166** disposed within hollow shaft **165** and rotatably coupled to hollow shaft **165** with a bearing **167** and a bearing **168**. Inner gerotor **6f** is rigidly coupled to an end of inner shaft **166**. Inner gerotor **6f** includes a seal plate **169** coupled thereto and an inner gear **170** that meshes with an outer gear **171** that is rigidly coupled to outer gerotor **4f**. Thus, rotation of inner shaft **166** as denoted by arrow **172** rotates inner gerotor **6f**, which in turn rotates outer gerotor through the meshing of inner gear **170** and outer gear **171**.

Also illustrates in FIG. **26** is an oil sump **173** coupled to housing **2f**. Oil or other suitable lubricant enters through a port **174** in housing **2f** to lubricate the bearings within housing **2f**. Due to centrifugal force, the oil collects in oil sump **173** and exits an outlet port **175** formed in the perimeter of oil sump **173** and may be recycled to the bearings through a pump (not explicitly shown).

As in previous gerotor apparatuses, gerotor apparatus **1f** may also include a pressurized air source **176** coupled to a port **177** formed in a perimeter of housing **2f**. Pressurized air source **176** is operable to deliver pressurized air through port **177** and into housing **2f** to supply a force to at least a portion of an outside perimeter of outer gerotor **4f**. In addition, gerotor apparatus **1f** may include a proximity sensor **178** that functions in the same manner as previous proximity sensors described above. A gap between an outer gerotor **4f** and housing **2f** may be adjusted using at least one screw **179** that is coupled to housing **2f**. A similar approach may be taken to adjust a gap between inner gerotor **6f** and housing **2f**.

According to the embodiment illustrated in FIG. **26**, bearings **168** and **181** are in a circumferential plane that is substantially the same as a circumferential plane passing through the axial centers of both inner gerotor **6f** and outer gerotor **4f**. This eliminates moments that could act on rigid shaft **165**, inner shaft **166**, and/or housing **2f** to prevent their flexure. This facilitates tight tolerances to be maintained between inner gerotor **6f** and outer gerotor **4f**. Bearings **167** and **180** experience relatively negligible loads and basically provide alignment for inner gerotor **6f** and outer gerotor **4f**.

FIG. **27** illustrates another embodiment of gerotor apparatus **1f**. The embodiment illustrated in FIG. **27** is essentially the same as the embodiment illustrated in FIG. **26**; however, in the embodiment in FIG. **27** bearings **168** and **181** are no longer in the same circumferential plane as the axial centers of inner gerotor **6f** and outer gerotor **4f**. Instead they exist above inner gerotor **6f**. Although an advantage of having bearings **168** and **181** in this location is that they do not experience temperatures based on the gas being compressed or expanded by gerotor apparatus **1f**, additional moments acting on bearings **168** and **181** may cause hollow shaft **165**, rotating shaft **166**, and/or housing **2f** to flex, which may open up a gap between inner gerotor **6f** and outer gerotor **4f**.

FIG. **28** illustrates an additional embodiment of gerotor apparatus **1f**. The embodiment illustrated in FIG. **28** is essentially a hybrid of the embodiments illustrated in FIGS. **26** and

27 in that bearing **168** exists in a circumferential plane that is substantially the same as a circumferential plane passing through the axial centers of both inner gerotor **6f** and outer gerotor **4f**, but bearing **181** exists at a location above inner gerotor **6f**. One advantage of this design is that it may be implemented with a small inner gerotor **6f**.

FIGS. **29** through **33** illustrate various embodiments of a gerotor apparatus **1g**. Gerotor apparatus **1g** includes a housing **2g**, an outer gerotor **4g** disposed within housing **2g**, and an inner gerotor **6g** disposed within outer gerotor **4g**. Gerotor apparatus **1g** also includes a hollow shaft **190** rigidly coupled to housing **2g** and an inner shaft **192** disposed within hollow shaft **190** and rotatably coupled thereto by a first bearing **193** and a second bearing **194**. Inner gerotor **6g** is rotatably coupled to hollow shaft **190** via a bearing **195** and a bearing **196**. Inner gerotor **6g** has a seal plate **197** attached thereto along with an inner gear **198**. Inner gear **198** meshes with an outer gear **199** that rigidly couples to outer gerotor **4g**. Similar to the embodiments illustrated in FIGS. **26** through **28**, gerotor apparatus **1g** also includes an oil sump **200** that functions to collect oil or other suitable lubricant circulated through gerotor apparatus **1g** so that it may be recirculated and needed.

Generally, an inner shaft **192** is rotated as noted by arrow **201**, which rotates outer gerotor **4g**, which rotates outer gear **199**, which rotates inner gear **198**, which rotates inner gerotor **6g**. According to an aspect of this embodiment, bearing **193** and **195** and bearings **194** and **196** are substantially equidistant from a circumferential plane passing through the axial centers of outer gerotor **4g** and inner gerotor **6g**. This eliminates moments that may act on hollow shaft **190**, inner shaft **192**, and/or housing **2g** to prevent their flexure, which allows tight tolerances to be maintained between outer gerotor **4g** and inner gerotor **6g**. Because of the symmetry, each set of bearings takes approximately half the load.

Gerotor apparatus **1g** may also include an air source **202** coupled to a perimeter of housing **2g** via a port **203**. Air source **202** is operable to deliver air or other suitable gas into housing **2g** on the outside of outer gerotor **4g** to control the temperature of outer gerotor **4g**. The controlling of the temperature of outer gerotor **4g** determines the gap between outer gerotor **4g** and housing **2g**. An air outlet **204** allows air within housing **2g** to exit housing **2g**. A proximity sensor **205** may provide feedback to a suitable controller to set the desired air flow rate of air source **202**.

FIG. **30** illustrates another embodiment of gerotor apparatus **1g**. The embodiment illustrated in FIG. **30** is substantially similar to the embodiment illustrated in FIG. **29**; however, in the embodiment in FIG. **30** instead of seal plate **197** being coupled to inner gerotor **6g**, seal plate **197** is coupled to outer gerotor **4g**. The advantage of this embodiment is that it more effectively isolates oil from the gas being compressed.

FIG. **31** illustrates another embodiment of gerotor apparatus **1g**. The embodiment illustrated in FIG. **31** is substantially similar to the embodiment illustrated in FIG. **29**; however, in the embodiment in FIG. **31**, the outer diameter of shaft **190** is minimized to reduce the outer bearing diameter (namely, bearings **195** and **196**) and thereby reduce power loss. One way of accomplishing this, as illustrated in FIG. **31**, is to provide a circumferential recess **206** on hollow shaft **190**. In addition, bearings **193** and **194** may also be positioned in recesses in the end of hollow shaft **190**.

FIG. **32** illustrates another embodiment of gerotor apparatus **1g**. The embodiment is substantially similar to the embodiment illustrated in FIG. **31**; however, in the embodiment in FIG. **32**, instead of seal plate **197** being coupled to gerotor apparatus **1g**, the seal plate **197** is outer gerotor **4g**.

15

FIG. 33 illustrates another embodiment of gerotor apparatus 1g. This embodiment is substantially similar to the embodiment illustrated in FIG. 32; however, in the embodiment in FIG. 33, bearing 193 and 194 are positioned in a recess that is formed on the inside of hollow shaft 190. In addition, bearing 196 is even smaller than the previous embodiments, which helps to reduce power loss.

FIGS. 34 through 42 illustrate various embodiments of a gerotor apparatus 1h. Gerotor apparatus 1h includes a housing 2h, an outer gerotor 4h disposed within housing 2h, and an inner gerotor 6h disposed within outer gerotor 4h. Gerotor apparatus 4h also includes a lower shaft 210 rigidly coupled to housing 2h and an upper shaft 212 rotatably coupled to housing 2h with a bearing 213. Gerotor apparatus 1h may also include a shaft 214 rotatably coupled to shaft 210 via a bearing 215. Upper shaft 212 and shaft 214 may be separate shafts coupled to outer gerotor 4h or may be integral with one another, thereby comprising one shaft. Inner gerotor 6h is rotatably coupled to lower shaft 210 via bearings 216 and 217. Inner gerotor 6h has a seal plate 218 coupled thereto and an inner gear 219 coupled thereto. Inner gear 219 couples to an outer gear 220 that is rigidly coupled to outer gerotor 4h. Similar to previous embodiments described above in conjunction with FIGS. 26 through 33, gerotor apparatus 1h also includes an oil sump 221 that functions in a similar manner.

Similar to the embodiments described above in conjunction with FIGS. 29 through 33, gerotor apparatus 1h may also include an air source 223 coupled to a perimeter of housing 2h via a port 224. Air source 223 is operable to deliver cooled air into housing 2h and circulated around the outside of outer gerotor 4h in order to control the temperature of outer gerotor 4h. The cooled air enters housing 2h through port 224 and exits a port 225. A proximity sensor 226 may also be coupled to housing 2h and function in a similar manner to the embodiments described above in conjunction with FIGS. 29 through 33. In general operation, when upper shaft 212 is rotated as denoted by arrow 226, then outer gerotor 4h rotates, which rotates outer gear 220, which rotates inner gear 219, which rotates inner gerotor 6h. An advantage of the embodiment illustrated in FIG. 34 is that bearing 215, being supported by lower shaft 210, reduces the cantilevering effect of outer gerotor 4h.

FIG. 35 illustrates another embodiment of gerotor apparatus 1h. This embodiment is substantially similar to the embodiment illustrated in FIG. 34; however, in the embodiment in FIG. 35, shaft 214 is hollow instead of being solid. The hollowed portion of shaft 214 allows an upper hollow shaft 227 to be disposed therein and upper hollow shaft 227 is rigidly coupled to housing 2h. Accordingly, shaft 212 is then rotatably coupled to upper hollow shaft 227. One advantage of this embodiment is the loads on bearing 215 are reduced because the loads are taken by the bearings mounted in upper hollow shaft 227.

FIG. 36 illustrates an additional embodiment of gerotor apparatus 1h. This embodiment is substantially similar to the embodiment illustrated in FIG. 35; however, in the embodiment in FIG. 36, shaft 212 is not rotatably coupled to lower shaft 210. As a result, in this embodiment, the precision of gerotor apparatus 1h is designed into housing 2h.

FIG. 37 illustrates an additional embodiment of gerotor apparatus 1h. In this embodiment, lower shaft 210 extends further than in previous embodiments so that a hollow shaft 228 may rotatably couple to lower shaft 210 via bearings 229 and 230. In addition, bearing 213 that functions to couple upper shaft 212 to housing 2h is removed in this embodiment. In this embodiment, the majority of the precision is built into housing 2h and lower shaft 210.

16

FIG. 38 illustrates an additional embodiment of gerotor apparatus 1h. In this embodiment, bearing 213 exists again to rotatably couple upper shaft 212 to housing 2h. Rigid shaft 210, instead of rigidly coupling to the bottom of housing 2h, pivotally couples to the bottom of housing 2h with a pivot 232. In this embodiment, the precision of inner gerotor 6h and outer gerotor 4h is essentially based on lower shaft 210. An anti-rotation pin 233 loosely couples to the bottom of housing 2h to prevent lower shaft 210 from rotating during operation.

FIG. 39 illustrates an additional embodiment of gerotor apparatus 1h. The embodiment illustrated in FIG. 39 is substantially similar to the embodiment illustrated in FIG. 38; however, in the embodiment in FIG. 39, instead of pivot 232 and anti-rotation pin 233, lower shaft 210 couples to the bottom of housing 2h with a rubber mount 235. Rubber mount 235 functions in a similar manner to the combination of pivot 232 and anti-rotation pin 233 in FIG. 38.

FIG. 40 illustrates an additional embodiment of gerotor apparatus 1h. The embodiment illustrated in FIG. 40 is substantially similar to the embodiment illustrated in FIG. 37; however, in the embodiment in FIG. 40 bearing 213 is utilized to rotatably couple upper shaft 212 to the top of housing 2h. This embodiment requires the precision to be designed into housing 2h.

FIG. 41 illustrates an additional embodiment of gerotor apparatus 1h. The embodiment illustrated in FIG. 41 is substantially similar to the embodiment illustrated in FIG. 34; however, in the embodiment in FIG. 41 bearing 215 rotatably couples to an outside surface of lower shaft 210 instead of coupling to a recessed portion of lower shaft 210, as in the embodiment illustrated in FIG. 34.

FIG. 42 illustrates another embodiment of gerotor apparatus 1h. In this embodiment, lower shaft 210 is no longer cantilevered and couples to both the top and bottom of housing 2h. This facilitates having a drive system 237 comprising upper shaft 212 rotatably coupled to housing 2h with bearings 238 and 239, and a drive gear 240 meshing with a driven gear 241 that rigidly couples to a hollow shaft 242 that rotatably couples to shaft 210. The advantage of this embodiment is that shaft 210 is strongly supported at each end, which reduces flexing thus maintaining precision.

FIGS. 43 through 46 illustrate various embodiments of a gerotor apparatus 1j. Gerotor apparatus 1j includes a housing 2j, an outer gerotor 4j disposed within housing 2j, and an inner gerotor 6j disposed within outer gerotor 4j. Gerotor apparatus 1j, as shown in FIGS. 43 through 46, have a “pancake” geometry that reduces cantilevered effects, as described further below. Referring to FIG. 43, gerotor apparatus 1j includes a lower shaft 250 rigidly coupled to the bottom of housing 2j. Gerotor apparatus 1j also includes an upper shaft 252 rotatably coupled to an upper portion of housing 2j by a pair of bearings 253 and 254. Upper shaft 252 couples to outer gerotor 4j, which includes a seal plate 255 and an outer gear 256. Outer gear 256 meshes with an inner gear 258 that couples to inner gerotor 6j. Inner gerotor 6j rigidly couples to lower shaft 250 with bearings 259 and 260. Generally, when rotating shaft 252 rotates, as denoted by arrow 261, outer gerotor 4j rotates, which rotates outer gear 256, which rotates inner gear 258, which rotates inner gerotor 6j.

In one embodiment, bearings 259 and 260 are located equidistant from an axial center of inner gerotor 6j so that each of the bearings takes approximately half of the load. Bearings 253 and 254, in one embodiment, are greased bearings rather than oil lubricated bearings so that no oil distribution system is required. In other embodiments, an oil distribution system may be employed.

17

FIG. 44 illustrates an additional embodiment of gerotor apparatus 1j. The embodiment illustrated in FIG. 44 is substantially similar to the embodiment illustrated in FIG. 43; however, in the embodiment of FIG. 44, upper shaft 252 may be shorter because the gas pressure acting on the inside of outer gerotor 4j is balanced by having a plurality of conduits 270 formed therein. This is described in greater detail below in conjunction with FIG. 47.

Referring to FIG. 47, a method for balancing pressures across outer gerotor 4j is illustrated. As illustrated, conduits 270 are formed in a wall 272 of outer gerotor 4j in a substantially radial direction. Conduits 270 allow some gas to leak from a chamber 274 within outer gerotor 4j to the outside of outer gerotor 4j in order to balance the loads acting on outer gerotor 4j to make it more stable during operation. Housing 2j includes a plurality of protrusions 276 that form a plurality of small chambers 278 each associated with a respective conduit 270. During operation, the gas leaks from chamber 274 through conduits 270 into chambers 278. Protrusions 276 may have any suitable spacing. In addition, conduits 270 may have any suitable shape and any suitable dimensions.

FIG. 45 illustrates an additional embodiment of gerotor apparatus 1j. This embodiment is substantially similar to the embodiment illustrated in FIG. 44; however, in the embodiment in FIG. 45, a retaining ring 280 couples to an upper portion of housing 2j. Retaining ring 280 couples to housing 2j with one or more adjustment screws 282. Retaining ring 280 engages bearing 253 and bearing 253 rests on a collar 284 that is integral with shaft 252. This setup allows an adjustment of a gap between the bottom of outer gerotor 4j and housing 2j. A proximity sensor 286 may be utilized to measure the gap between outer gerotor 4j and housing 2j.

FIG. 46 illustrates an additional embodiment of gerotor apparatus 1j. The embodiment illustrated in FIG. 46 is substantially similar to the embodiment illustrated in FIG. 44; however, in the embodiment in FIG. 46 there is a slightly different gearing arrangement. More specifically, an idler gear 290 couples an inner gear 292 that is associated with inner gerotor 6j to an outer gear 294 that is associated with outer gerotor 4j. Idler gear 290 is rotatably coupled to lower shaft 250 with bearings 295 and 296.

FIGS. 48 through 53 illustrate various embodiments of a gerotor apparatus 1k. Gerotor apparatus 1k includes a housing 2k, an outer gerotor 4k disposed within housing 2k, and an inner gerotor 6k disposed within outer gerotor 4k. Gerotor apparatus 1k includes a lower shaft 320 rigidly coupled to an end of housing 2k that includes a gas inlet port 322 and a gas exhaust 324. A gear housing 326 is coupled to lower shaft 320 and an upper shaft 328 couples to gear housing 326 and extends upwards towards the top of housing 2k. A rotating shaft 330 is rotatably coupled to housing 2k by a bearing 332. Shaft 330 couples to outer gerotor 4k and also couples to upper shaft 328 via a hollow shaft 334 and bearings 335 and 336. Inner gerotor 6k is rotatably coupled to lower shaft 320 via a bearing 337 and a bearing 338.

Gear housing 326 includes an idler gear 340 coupling a first gear 342 that is associated with outer gerotor 4k and a second gear 344 that is associated with inner gerotor 6k. Idler gear 340 is rotatably coupled to gear housing 326 in any suitable manner, such as by bearings 345 and 346. In general operation, when shaft 330 rotates, as denoted by arrow 347, it rotates outer gerotor 4k, which rotates first gear 342, which rotates idler gear 340, which rotates second gear 344, which rotates inner gerotor 6k. The advantage of the embodiment illustrated in FIG. 48 is that it employs large gears that are not constrained to be located within inner gerotor 6k.

18

FIG. 49 illustrates an additional embodiment of gerotor apparatus 1k. The embodiment illustrated in FIG. 49 is substantially similar to the embodiment illustrated in FIG. 48; however, in the embodiment of FIG. 49, upper shaft 328 is rigidly coupled to the top of housing 2k. Accordingly, a drive system 350 exists off-center of housing 2k. Drive system 350 includes rotating shaft 330 that is rotatably coupled to housing 2k via bearings 351 and 352. Rotating shaft 330 includes a drive gear 353 meshing with a driven gear 354 that is rigidly coupled to hollow shaft 334 of outer gerotor 4k. An advantage of this embodiment is that both lower shaft 320 and upper shaft 328 are rigidly attached to housing 2k, thus providing strength and rigidity.

FIG. 50 illustrates an additional embodiment of gerotor apparatus 1k. The embodiment illustrated in FIG. 50 is substantially similar to the embodiment illustrated in FIG. 48; however, in the embodiment of FIG. 50, a retaining ring 360 is coupled to an upper portion of housing 2k with one or more adjustment screws 362. This embodiment requires little precision in housing 2k; shaft alignment is achieved when screws 362 are tightened.

FIG. 51 illustrates an additional embodiment of gerotor apparatus 1k. The embodiment illustrated in FIG. 51 is substantially similar to the embodiment illustrated in FIG. 50; however, in the embodiment of FIG. 51, gear housing 326 is now disposed within inner gerotor 6k. This facilitates more of a “pancake” arrangement so that the cantilevering effect of outer gerotor 4k is reduced.

FIG. 52 illustrates an additional embodiment of gerotor apparatus 1k. The embodiment illustrated in FIG. 52 is substantially similar to the embodiment illustrated in FIG. 51; however, in the embodiment of FIG. 52, a jacket 370 exists around a perimeter of housing 2k. Jacket 370 has an inlet 372 and an exit 374 that function to recirculate any suitable fluid around the perimeter of housing 2k to control the temperature of housing 2k, thereby regulating its length and controlling a gap between the end of outer gerotor 4k and housing 2k. A proximity sensor 376 may be used to measure the gap. Proximity sensor 376 may be coupled to a suitable controller (not shown) that controls the flow of fluid through jacket 370 to regulate the gap to a predetermined distance. The present invention contemplates other methods to regulate the gap between outer gerotor 4k and housing 2k. Jacket 370, as illustrated in FIG. 52, may be used in any of the embodiments of the gerotor apparatuses described in this detailed description.

FIGS. 53A and 53B illustrate side and top views, respectively, of an anti-backlash gear system 300. Anti-backlash gearing system 300 includes a free spinning gear 302 and a gear 304 rigidly coupled to a rotating shaft 306. Free spinning gear 302 rotatably couples to rotating shaft 306 with one or more bearings 308. One or more springs 310 are biased against both free spinning gear 302 and gear 304. When the teeth of free spinning gear 302 and gear 304 are aligned, springs 310 compress. Then, when the aligned gear teeth are inserted or meshed with a mating gear (not shown), then contact is made on both faces of a single tooth, thereby preventing backlash. The present invention contemplates other anti-backlash gear systems.

FIG. 54 illustrates an example embodiment of a gerotor apparatus 1L in which a lubricant is used to reduce friction. Gerotor apparatus 1L comprises a housing 2L, an outer gerotor assembly 3L, and an inner gerotor assembly 5L. Outer gerotor assembly 3L comprises an outer gerotor 4L and an outer gerotor shaft 508. Similarly, inner gerotor assembly 5L comprises an inner gerotor 6L and an inner gerotor shaft 514. Outer gerotor shaft 508 may be rotatably coupled to housing

2L by one or more bearings, such as first bearing 516 and second bearing 518 shown in FIG. 54. Similarly, inner gerotor shaft 514 may be rotatably coupled to housing 2L by one or more bearings, such as third bearing 520 and fourth bearing 522 shown in FIG. 54.

Outer gerotor 4L comprises an outer gerotor chamber 524. As shown in FIG. 54, at least a portion of inner gerotor 6L may be disposed within outer gerotor chamber 524. Gerotor apparatus 1L may also include a valve plate 526 operable to allow gas to enter into and exit from outer gerotor chamber 524. Valve plate 526 may include one or more gas inlet ports 528 allowing gas to enter outer gerotor chamber 524 and one or more gas outlet ports 530 allowing gas to exit outer gerotor chamber 524.

Outer gerotor 4L and inner gerotor 6L are operable to rotate relative to each other such that gerotor apparatus 1L may function as a compressor or an expander. For example, in an embodiment in which gerotor apparatus 1L functions as a compressor, a volume of gas at a first pressure may enter outer gerotor chamber 524 through gas inlet port 528, be compressed by the relative rotation of inner gerotor 6L and outer gerotor 4L, and exit outer gerotor chamber 524 through gas outlet port 530 at a second pressure higher than the first pressure. Alternatively, in an embodiment in which gerotor apparatus 1L functions as an expander, pressurized or relatively high pressure gas may enter outer gerotor chamber 524 through gas outlet port 530, expand within outer gerotor chamber 524 while causing rotation of inner gerotor 6L and/or outer gerotor 4L in order to drive inner gerotor shaft 514 and/or outer gerotor shaft 508, and exit outer gerotor chamber 524 through gas inlet port 528.

Inner gerotor assembly 5L comprises one or more entrance passages 532 operable to communicate a lubricant 534 through inner gerotor 6L and into outer gerotor chamber 524 in order to reduce friction between inner gerotor 6L and outer gerotor 4L. For example, as shown in FIG. 54, inner gerotor shaft 514 may include a shaft entrance passage 536 coupled to an inner gerotor entrance passage 538 which opens into outer gerotor chamber 524. Lubricant 534 may comprise any suitable type or types of lubricating oil, such as motor oil, lubricating grease, water, fuel, or any other type of lubricant suitable to reduce friction between inner gerotor 6L and outer gerotor 4L.

As inner gerotor 6L rotates, lubricant 534 may travel outwardly along entrance passages 532 and into outer gerotor chamber 524 due to centrifugal forces. As discussed in greater detail with reference to FIG. 55, as lubricant 534 exits inner gerotor 6L, portions of the outer perimeter, or the tips, of inner gerotor 6L may be lubricated. In this embodiment, lubricant 534 may contact and/or mix with gases within outer gerotor chamber 524, including gas entering into outer gerotor chamber 524 through gas inlet port 528. In some embodiments, outer gerotor chamber 524 is substantially enclosed, such as by housing 2L and/or valve plate 526, such that at least a portion of lubricant 534 that is introduced into outer gerotor chamber 524 is contained within outer gerotor chamber 524 at least temporarily.

FIG. 55 illustrates a cross-section of outer gerotor 4L and inner gerotor 6L taken along line A-A of FIG. 54. For illustrative purposes, housing 2L is not shown in FIG. 55. As shown in FIG. 55, outer gerotor chamber 524 may include a plurality of notches 540 located around the perimeter of outer gerotor chamber 524. Inner gerotor 6L may include a plurality of protrusions, or tips, 542. Tips 542 may be shaped and/or sized such that they generally fit within notches 540 as inner gerotor 6L and outer gerotor 4L rotate relative to one another.

As discussed above, inner gerotor 6L may include one or more inner gerotor entrance passages 532. As shown in FIG. 55, inner gerotor 6L may include an inner gerotor entrance passage 538 extending generally from the center of inner gerotor 6L toward each tip 542 of inner gerotor 6L. Each tip 542 may include one or more tip openings 544 operable to allow lubricant 534 to enter outer gerotor chamber 524 via inner gerotor entrance passages 532. Although inner gerotor 6L comprises a star shape based upon a hypocycloid having four tips 542 and outer gerotor chamber 524 comprises a star shape having five notches 540 in the embodiment shown in FIG. 55, inner gerotor 6L and outer gerotor chamber 524 may have any other suitable shape or configuration without departing from the scope of the present invention. For example, the shape may be based on an epicycloid, or the number of tips and notches may be altered.

FIG. 56 illustrates an example embodiment of a gerotor apparatus 1M in which lubricant 534 may be expelled from outer gerotor chamber 524 and kept at least substantially separate from gases entering outer gerotor chamber 524 through gas inlet port 528. As shown in FIG. 56, gerotor apparatus 1M comprises a housing 2M, an outer gerotor assembly 3M comprising an outer gerotor 4M, an inner gerotor assembly 5M comprising an inner gerotor 6M, and a synchronizing system 7M. Synchronizing system 7M comprises an outer gerotor portion 8M and an inner gerotor portion 9M. Inner gerotor 6M may function along with outer gerotor 4M to provide compressor or expander functions while synchronizing system 7M may be used to synchronize inner gerotor 6M and outer gerotor 4M.

In particular embodiments, such as shown in FIG. 56 for example, inner gerotor 6M is disposed generally with first section 556 of outer gerotor chamber 524 and inner gerotor portion 9M of synchronizing system 7M is disposed generally within second section 558 of outer gerotor chamber 524. In addition, in some embodiments, inner gerotor 6M may comprise a star shape, such as shown in FIGS. 55 and 57A, while inner gerotor portion 9M of synchronizing system 7M may comprise a different shape, such as the cross shape shown in FIG. 57B, for example.

Inner gerotor portion 9M of synchronizing system 7M comprises one or more entrance passages 532 allowing lubricant 534 to be introduced into portion 558 of outer gerotor chamber 524. Outer gerotor portion 8M of synchronizing system 7M comprises one or more exit passages 550 operable to allow such lubricant 534 introduced into portion 558 to escape portion 558 of outer gerotor chamber 524. For example, as outer gerotor assembly 3M rotates, exit passages 550 may communicate lubricant 534 from inside portion 558 of outer gerotor chamber 524 to an area 554 external to outer gerotor 4M.

In addition, gerotor apparatus 1M may comprise a seal plate 552 operable to at least substantially separate or seal a first portion 556 of outer gerotor chamber 524 comprising lubricant 534 from a second portion 558 of outer gerotor chamber 524 in which gases are received through gas inlet port 528. In this manner, lubricant 534 may be kept from mixing with gases entering first portion 556 of outer gerotor chamber 524 through gas inlet port 528. The advantage of this embodiment is the gases are substantially free of lubricants.

FIGS. 57A and 57B illustrate two example cross sections of synchronizing system 7M taken along line B-B of FIG. 56. FIG. 57A shows a portion of inner gerotor portion 9M of synchronizing system 7M disposed within outer gerotor portion 8M of synchronizing system 7M. In this embodiment, inner gerotor portion 9M comprises a star shape having a plurality of protrusions, or tips, 560, and second portion 558

of outer gerotor chamber 524 comprises a plurality of notches 562 located proximate the perimeter of outer gerotor portion 8M. As discussed above, outer gerotor portion 8M comprises exit passages 550 operable to allow lubricant 534 introduced into second section 558 of outer gerotor chamber 524 to escape outer gerotor chamber 524. For example, lubricant 534 may be introduced into a central portion 564 of inner gerotor portion 9M, travel outward along entrance passages 532 (such as due to centrifugal forces caused by the rotation of inner gerotor 6M, for example), enter into second portion 558 of outer gerotor chamber 524, and exits outer gerotor portion 9M through exit passages 550. In some embodiments, such as those shown in FIGS. 57A and 57B, exit passages 550 may be located proximate notches 562 in outer gerotor chamber 524. In such embodiments, one or more notches 562 may include an exit opening 566 opening into an exit passage 550.

FIG. 57B illustrates one alternative to the embodiment shown in FIG. 57A. As shown in FIG. 57B, inner gerotor portion 9M of synchronizing system 7M comprises a cross shape including a center 568 and a plurality of arms 570 projecting outwardly from center 568. Each arm 570 comprises a tip 572 which may be shaped and/or sized to fit generally within notches 562 of second section 558 of outer gerotor chamber 524. Each tip 572 may comprise one or more openings 574 allowing entrance passages 532 to communicate lubricant 534 into second section 558 of outer gerotor chamber 524. An advantage of the embodiment illustrated in FIG. 57B is there are fewer losses due to gas compression in the second portion 558 of outer gerotor chamber 524.

FIGS. 58 through 63 illustrate various example embodiments of gerotor apparatuses including a synchronizing system having one or more alignment members and/or alignment guides for controlling and/or insuring the proper rotation and/or alignment of the inner gerotor and outer gerotor. An advantage of these embodiments is they may provide two alignment surfaces, which reduces loads at the contact points.

FIG. 58 illustrates an embodiment of a gerotor apparatus 1N comprising a housing 2N, an outer gerotor assembly 3N comprising an outer gerotor 4N, an inner gerotor assembly 5N comprising an inner gerotor 6N, and a synchronizing system 7N. Like the other various gerotor apparatuses discussed herein, gerotor apparatus 1N may be designed to function as a compressor and/or an expander, depending on the particular embodiment. Inner gerotor 6N may function along with outer gerotor 4N to provide compressor or expander functions while synchronizing system 7N may be used to synchronize inner gerotor 6N and outer gerotor 4N.

Synchronizing system 7N comprises an outer gerotor portion 8N and an inner gerotor portion 9N, such as described above with reference to FIGS. 56, 57A and 57B. Outer gerotor portion 8N comprises a plurality of alignment guides 580 and inner gerotor portion 9N comprises a plurality of alignment members 582 positioned in alignment with alignment guides 580. One or more alignment members 582 may comprise an alignment member passage 584 operable to communicate a lubricant, such as lubricant 534 for example, toward or into one or more alignment guides 580. As shown in FIG. 58, each alignment member passage 584 may be coupled to an appropriate entrance passage 532 formed in inner gerotor 6N such that lubricant 534 may be introduced into inner gerotor assembly 5N, travel toward alignment members 582 (such as due to centrifugal forces caused by the rotation of inner gerotor 6N, for example), and release into alignment guides 580 in order to provide lubrication between alignment members 582 and alignment guides 580 during the rotation of inner gerotor 6N relative to outer gerotor 4N. In the embodiment shown in FIG. 58, lubricant 534 may contact and/or mix

with gases within outer gerotor chamber 524, including gases entering into outer gerotor chamber 524 through gas inlet port 528. In some embodiments, outer gerotor chamber 524 is substantially enclosed such that at least a portion of lubricant 534 that is introduced into outer gerotor chamber 524 is contained within outer gerotor chamber 524 at least temporarily.

FIG. 59A illustrates an exploded cross-sectional view of a portion of synchronizing system 7N taken along line C-C shown in FIG. 58, with outer gerotor portion 8N shown separate from inner gerotor portion 9N. Inner gerotor portion 9N may be at least partially integral with inner gerotor 6N. FIG. 59B illustrates a side view of a portion of outer gerotor portion 8N and inner gerotor portion 9N shown in FIG. 59A assembled for operation (such as shown in FIG. 58).

As shown in FIGS. 59A and 59B, alignment guide 580 may comprise an alignment track 586 and alignment members 582 may comprise knob devices 588 operable to move along alignment track 586 as inner gerotor assembly 5N rotates relative to outer gerotor assembly 3N. Knob device 588 may comprise a knob, protrusion, or other suitable member rigidly coupled to inner gerotor portion 9N of synchronizing system 7N such that knob device 588 does not rotate relative to inner gerotor portion 9N. In alternative embodiments, such as shown in FIGS. 60 through 62, knob device 588 may comprise a wheel device rotatably coupled to inner gerotor portion 9N.

As discussed above, each alignment member 582, or knob device 588, may comprise one or more alignment member passages 584 operable to communicate lubricant 534 toward, or into, alignment track 586. In this manner, lubricant 534 may travel outwardly along inner gerotor entrance passages 532, through alignment member passages 584, and into alignment guide 586 in order to reduce friction between knob devices 588 and alignment track 586.

Alignment track 586 is defined at least in part by an inner surface 594 and an outer surface 596, and may comprise a plurality of alignment guide notches 598 in the embodiment shown in FIG. 59A, the width of alignment track 586 is at least substantially uniform around the perimeter of alignment track 586. In alternative embodiments, such as the embodiments shown in FIGS. 59C and 59D, for example, alignment track 586 may comprise one or more breaks or may have a substantially non-uniform width.

Outer gerotor portion 8N may comprise one or more exit passages 592 operable to allow lubricants, such as lubricant 534, to exit alignment track 586. It should be noted that exit passages 592 are not shown in FIG. 58, but are shown in FIGS. 59A and 59B. As shown in FIG. 59A, exit passages 592 may be located proximate alignment track notches 598. In operation, lubricant 534 entering alignment track 586 through alignment member passages 584 may be removed from alignment track 586 through exit passages 592.

FIG. 59C illustrates an exploded cross-sectional view of a portion of synchronizing system 7N taken along line C-C shown in FIG. 58, with outer gerotor portion 8N shown separate from inner gerotor portion 9N, in an alternative embodiment of the invention. As discussed above, inner gerotor portion 9N may be at least partially integral with inner gerotor 6N.

As shown in FIG. 59C, alignment track 586 may be intermittent, or contain one or more breaks 600. In some embodiments, as alignment members 582 travel along alignment track 586, they may provide rotational torque when located in a notch 598 in alignment track 586. When alignment members 582 are located in notches 598, the relative motion of the alignment member 582 and alignment track 586 is relatively

23

small, and thus friction between the two may be relatively small. In contrast, when an alignment member **582** is proximate a valley of alignment track **586**, the alignment member **582** provides little rotational torque but because the relative motion of the alignment member **582** with alignment track **586** is relatively large, the friction between the two is also relatively large. Thus, the intermittent alignment track **586** shown in FIG. **59C** removes the valleys of alignment track **586** because such valleys serve little useful function and contribute to friction losses.

FIG. **59D** illustrates an exploded cross-sectional view of a portion of synchronizing system **7N** taken along line C-C shown in FIG. **58**, with outer gerotor portion **8N** shown separate from inner gerotor portion **9N**, in another alternative embodiment of the invention. As shown in FIG. **59D**, alignment track **586** comprises a relatively non-uniform width around the perimeter of alignment track **586**. In particular, the width of alignment track **586** may be greater proximate the valleys of alignment track **586** than proximate notches **598** of alignment track **586**. In this manner, alignment members **582** may be kept from contacting alignment guide **586** when alignment members **582** are located proximate the valleys of alignment track **586** in order to reduce friction between the two, as discussed above with reference to FIG. **59C**.

FIGS. **60A** and **60B** illustrate an example of a synchronizing system **7N** in accordance with yet another embodiment of the present invention. FIG. **60A** illustrates an exploded cross-sectional view similar to those shown in FIGS. **59A**, **59C** and **59D**, while FIG. **60B** illustrates a partial side view similar to that of FIG. **59B**. In this embodiment, alignment members **582** may comprise rollers, or wheels, **604** rotatably coupled to inner gerotor portion **9N** of synchronizing system **7N**, such as by pegs or shafts **604**. As shown in FIG. **60B**, each roller **602** rotates with the aid of a bearing **606**. The rollers can be hollow to reduce weight. Rollers **602** are operable to rotate relative to inner gerotor portion **9N** as rollers **602** travel along alignment track **586**. As shown in FIG. **60A**, alignment track **586** may be defined at least in part by an inner surface **608** and an outer surface **610**. As rollers **602** travel along alignment track **586**, individual rollers **602** may roll along inner surface **608** and/or outer surface **610** at various locations of alignment track **586**. Rollers **602** may be advantageous as they may reduce friction between alignment members **582** and alignment guide **580**.

FIGS. **61A** and **61B** illustrate another example of a synchronizing system **7N** in accordance with yet another embodiment of the present invention. This embodiment is similar to the embodiment shown in FIGS. **60A** and **60B**, without the inner surface of alignment guide **580**. Such a configuration may eliminate friction between rollers **602** and an inner surface of alignment guide **580**, which may be advantageous.

FIGS. **62A**, **62B** and **62C** illustrate an embodiment of a synchronizing system **7M** which may be viewed in conjunction with the embodiment shown in FIG. **56**. As discussed above regarding FIG. **56**, gerotor apparatus **1M** comprises a housing **2M**, an outer gerotor assembly **3M** comprising an outer gerotor **4M**, an inner gerotor assembly **5M** comprising an inner gerotor **6M**, and a synchronizing system **7M**. Synchronizing system **7M** comprises an outer gerotor portion **8M** and an inner gerotor portion **9M**.

As discussed above regarding FIG. **56**, inner gerotor portion **9M** of synchronizing system **7M** is disposed generally within a second section **558** of outer gerotor chamber **524**. Second section **558** of outer gerotor chamber **524** may comprise a plurality of notches **614** and an inner perimeter surface **616**.

24

Inner gerotor portion **9M** may comprise a star shape including a center region **618** and a plurality of protrusions **620** extending outwardly from center region **618**. A knob device **622** is coupled to each of the protrusions **620** of inner gerotor portion **9M**. In the embodiments shown in FIGS. **62A**, **62B** and **62C**, knob devices **622** comprise roller devices rotatably coupled to each protrusion **620**. In alternative embodiments, however, knob devices **622** may comprise other suitable types of devices rigidly coupled to inner gerotor portion **9M**.

Knob devices **622** may be sized and/or shaped such that they generally fit within notches **614** of outer gerotor chamber **524**. Knob devices **622** may contact and/or roll along inner perimeter surface **616** of second section **558** of outer gerotor chamber **524** as inner gerotor assembly **5M** rotates relative to outer gerotor assembly **3M**. Gerotor apparatus **1M** may be designed to function as a compressor or an expander depending on the particular embodiments.

FIG. **62B** illustrates a side view of a roller device **622** rotatably coupled to a protrusion **620** of inner gerotor portion **9M** of synchronizing system **7M** in accordance with one embodiment. In this embodiment, protrusion **620** comprises a protuberance **624** and roller device **622** comprises a first roller **626** and a second roller **628** rotatably coupled on opposite sides of protuberance **624**. Protuberance **624** may comprise an outer tip **630** and roller device **622** may extend beyond tip **630** such that protuberance **624** does not contact inner perimeter surface **616** of second section **558** of outer gerotor chamber **524**.

FIG. **62C** illustrates a side view of a roller device **622** rotatably coupled to a protrusion **620** of inner gerotor portion **9M** of synchronizing system **7M** in accordance with another embodiment of the present invention. In this embodiment, protrusion **620** includes a slot **634** and roller device **622** is disposed at least partially within slot **634**. Protrusion **620** may comprise a leading tip **636** and roller device **622** may extend beyond leading tip **636** such that protrusion **620** does not contact inner perimeter surface **616** of second section **558** of outer gerotor chamber **524**.

FIG. **63** illustrates another embodiment of a gerotor apparatus **1Q** in which a lubricant may be introduced between alignment members and alignment guide of a synchronizing system and kept at least substantially separate from gases being introduced into gerotor apparatus **1Q**. Gerotor apparatus **1Q** comprises a housing **2Q**, an outer gerotor assembly **3Q** comprising an outer gerotor **4Q**, an inner gerotor assembly **5Q** comprising an inner gerotor **6Q**, and a synchronizing system **7Q**. Synchronizing system **7Q** comprises an outer gerotor portion **8Q** and an inner gerotor portion **9Q**.

Inner gerotor **6Q** is disposed at least partially within a first section **642** of outer gerotor chamber **524** while inner gerotor portion **9M** of synchronizing system **7M** is disposed at least partially within a second section **646** of outer gerotor chamber **524**. Outer gerotor portion **8Q** of synchronizing system **7M** comprises one or more alignment guides **580**, and inner gerotor portion **9Q** of synchronizing system **7M** comprises one or more alignment members **582** disposed in alignment with alignment guide **580**. Inner gerotor **6Q** may include one or more entrance passages **532** operable to communicate a lubricant, such as lubricant **534** for example, toward inner gerotor portion **9Q** of synchronizing system **7M**. Alignment members **582** may comprise alignment member passages **584** coupled to inner gerotor entrance passages **532** and operable to communicate lubricant **534** into alignment guide **580** in order to reduce friction between alignment members **582** and alignment guide **580**.

Outer gerotor portion 8Q of synchronizing system 7M may comprise one or more exit passages 592 operable to allow lubricant 534 present within second section 626 of outer gerotor chamber 524 to escape or exit from outer gerotor assembly 3Q. In some embodiments, outer gerotor assembly 3Q includes a barrier or seal, such as a seal plate, 628 operable to at least substantially separate first and second sections 642 and 646 of outer gerotor chamber 524. In this manner, seal plate 628 may be operable to substantially keep lubricant 534 introduced into second section 646 from entering into first section 642 and contacting and/or mixing with gases entering first section 642 through gas inlet port 528.

FIG. 64A illustrates an embodiment of an inner gerotor 6R having a shape based on a hypocycloid. Inner gerotor 6R comprises a cross-sectional shape 650 based at least in part on a hypocycloid shape 652. In the embodiment shown in FIG. 64A, cross-sectional shape 650 of inner gerotor 6R comprises a substantially uniform offset from hypocycloid shape 652 with a plurality of curved tips 654. An advantage of the embodiment illustrated in FIG. 64A is that the inner and outer gerotors may achieve a high compression ratio in a single stage.

FIG. 64B illustrates a method of generating a hypocycloid shape, such as hypocycloid shape 652, for example.

FIG. 65A illustrates an embodiment of an inner gerotor 6S having a shape based at least in part on an epicycloid. Inner gerotor 6S comprises a cross-sectional shape 656 based at least in part on an epicycloid shape 658. For example, as shown in FIG. 65A, cross-sectional shape 656 of inner gerotor 6S comprises a substantially uniform offset from epicycloid shape 658 and a plurality of curved protuberances 660. An advantage of the embodiment illustrated in FIG. 65A is when small numbers of teeth are employed, it has a large volumetric capacity.

FIG. 65B illustrates a method of generating an epicycloid shape, such as epicycloid 658, for example.

FIGS. 66 through 74 illustrate example embodiments of an engine system comprising a pair of gerotor apparatuses which work together to perform one or more engine functions. Although each of the embodiments shown in FIGS. 66 through 74 are described such that the pair of gerotor apparatuses includes an expander and a compressor, in alternative embodiments the pair of gerotor apparatuses may include a pair of expanders or a pair of compressors. In addition, in alternative embodiments, a component of the engine system may comprise any suitable number of inter-related expanders, compressors, or any combination thereof. An advantage of the embodiments illustrated in FIGS. 66 through 74 is compactness.

FIG. 66A illustrates an engine system 700A in accordance with one embodiment to the present invention. Engine system 700A comprises a compressor 702A at least partially integrated with an expander 704A and disposed at least partially within a housing 706A. Compressor 702A comprises a compressor outer gerotor 708A and a compressor inner gerotor 710A. Similarly, expander 704A comprises an expander outer gerotor 712A and an expander inner gerotor 714A. As shown FIG. 66A, compressor outer gerotor 708A and expander outer gerotor 712A may be at least partially integrated within an outer gerotor assembly 716A. Similarly, compressor inner gerotor 710A and expander inner gerotor 714A may be at least partially integrated within an inner gerotor assembly 718A. Some embodiments, outer gerotor assembly 716A comprises a barrier or seal, such as a seal plate, 720A that substantially separates a first section 744 of an outer gerotor chamber from a section 746 of the outer

gerotor chamber. In this manner, seal 720A may substantially separate compressor 702A from expander 704A.

As shown in FIG. 66A, inner gerotor 718A may be rigidly coupled to an inner gerotor shaft 722A which may be rotatably coupled to housing 706A. For example, in the embodiment shown in FIG. 66A, shaft 722A is rotatably coupled to housing 706A by first bearing 724A and a second bearing 726A. Similarly, outer gerotor assembly 716A may be rotatably coupled to housing 706A. For example, outer gerotor assembly 716A may be rotatably coupled to housing 706A by a third bearing 728A and a fourth bearing 730A. In this manner, inner gerotor assembly 714A and outer gerotor 716A may rotate relative to housing 706A in order to perform the functions of compressor 702A and expander 704A.

As shown in FIG. 66A, engine system 700A comprises a first valve plate 732A allowing gases to flow in and out of compressor 702A and a second valve plate 734A allowing gases to flow in and out of expander 704A. First valve plate 732A comprises a compressor gas inlet port 736A and a compressor gas outlet port 738A. Compressor gas inlet port 736A allows gas at a first pressure to enter compressor 702A. These gases are then compressed by the rotation of compressor inner gerotor 710A relative to compressor outer gerotor 708A before exiting or being expelled from compressor 702A through compressor gas outlet port 738A.

Similarly, second valve plate 734A comprises an expander gas inlet port 740A and an expander gas outlet port 742A. Expander gas inlet port 740A allows gases to enter expander 704A. These gases expand within expander 704A as expander inner gerotor 714A rotates relative to expander outer gerotor 712A before exiting or being expelled from expander 704A through expander gas outlet port 742A. The expansion of these gases within expander 704A may at least partially drive the rotation of inner gerotor assembly 718A and/or outer gerotor assembly 716A.

FIG. 66B illustrates a cross section of compressor 702A taken along line C-C shown in FIG. 66A, while FIG. 66C illustrates a cross section of expander 704A taken along line D-D shown in FIG. 66A. As shown in FIG. 66B, compressor 702A comprises compressor inner gerotor 710A disposed substantially within outer gerotor chamber 744 of compressor outer gerotor 708A. Similarly, as shown in FIG. 66C, expander 704A comprises expander inner gerotor 714A disposed substantially within outer gerotor chamber 746 of expander outer gerotor 712A. In the embodiment shown in FIGS. 66B and 66C, compressor inner gerotor 710A may comprise one or more entrance passages 748 operable to communicate a lubricant, such as lubricant 534, into outer gerotor chamber 744, while expander inner gerotor 714A does not include such entrance passages for communicating a lubricant into outer gerotor chamber 746. This configuration may be appropriate in an embodiment in which it is desirable or acceptable for lubricant 534 to contact and/or mix with relatively low temperature gases traveling through outer gerotor chamber 744 of compressor outer gerotor 708A but not desirable or acceptable for a lubricant to contact and/or mix with relatively high temperature gases traveling through outer gerotor chamber 746 of expander outer gerotor 712A. However, in alternative embodiments, neither or both of compressor inner gerotor 710A and expander inner gerotor 714A may include entrance passages for introducing a lubricant into outer gerotor chambers 744 or 746.

FIG. 67 illustrates another embodiment of an engine system 700B comprising a compressor 702B at least partially integrated with a compressor 704B. Engine system 700B is similar to engine system 700A shown FIG. 66A; however, in engine system 700B, third bearing 728B and fourth bearing

730B which rotatably couple outer gerotor assembly 716B to housing 706B are disposed inwardly and between compressor 702B and expander 704B. This configuration may allow a reduced diameter or outer perimeter of housing 706B as compared with housing 706A shown in FIG. 66A, assuming the outer diameters of outer gerotor assemblies 716A and 716B are the same. In addition, because the diameters of third and fourth bearings 728B and 730B shown in FIG. 67 are generally smaller than the diameters of third and fourth bearings 728A and 730A shown in FIG. 66A, the configuration of engine system 700B may be more appropriate for high rotational speed applications than the configuration of engine system 700A shown in FIG. 66A. It should be noted that cross sections of engine system 700B taken along line C-C and line D-D shown in FIG. 67 may, in some embodiments, be represented by the cross sections shown in FIGS. 66B and 66C, respectively.

FIG. 68A illustrates a side view of an embodiment of an engine system 700D comprising an outer gerotor assembly 716D, and inner gerotor assembly 718D, and a synchronizing system 760D operable to control the rotation of inner gerotor assembly 718D relative to outer gerotor assembly 716D and/or to physically align inner gerotor assembly 718D relative to outer gerotor assembly 716D. As shown in FIG. 68A, engine system 700D may be similar to engine system 700A shown in FIG. 66A, with the addition of synchronizing system 760D.

Synchronizing system 760D comprises a drive plate 762D, a cam plate 764D, and an alignment plate 766D. Cam plate 764D comprises one or more alignment guides 768D. Alignment plate 768D comprises one or more alignment members, such as knobs, rollers or pegs, 770D generally disposed in alignment with alignment guide 768D of cam plate 764D. Alignment guide 768D and alignment members 770D may be designed and/or positioned such that inner gerotor assembly 718D is maintained in alignment with outer gerotor assembly 716D as inner gerotor assembly 718D rotates relative to outer gerotor assembly 716D. In alternative embodiments, the synchronizing system 760D may include gears, such as those described in above embodiments.

As shown in FIG. 68A, cam plate 764D also comprises one or more notches, or grooves, 772D. Drive plate 762D comprises one or more drive members, such as knobs, rollers or pegs, 774D disposed within notches 772D when drive plate 762D is mated with cam plate 764D. As described below with reference to FIG. 68C, notches 772D and drive members 774D may be designed to allow thermal expansion or contraction of drive plate 762D and/or cam plate 764D. Although not shown in FIG. 68A, drive plate 762D may be coupled to a drive mechanism operable to at least partially control the rotation of drive plate 762D. Drive members 774D of drive plate 762D fit within notches 772D of cam plate 764D such that drive plate 762D may at least partially control the rotation of cam plate 764D.

FIG. 68B illustrates a cross section of engine system 700D taken along each line J-J shown in FIG. 68A. In other words, FIG. 68B illustrates a cross section of both compressor 702D and expander 704D.

FIG. 68C illustrates cross sectional views of the various components of synchronizing system 760D taken along line A-A shown in FIG. 68A. As discussed above, cam plate 764D comprises alignment guide 768D such as an alignment track, for example, and a plurality of notches 772D disposed around the perimeter of cam plate 764D. Cam plate 764D may also comprise one or more exit passages 776 operable to communicate a lubricant away from alignment guide 768D. Peg plate 766D comprises a plurality of alignment members 770D, as discussed above. In addition, peg plate 766D comprises one

or more entrance passages 778 operable to communicate a lubricant, such as lubricant 534 for example, into alignment guide 768D to reduce friction between alignment members 770D and alignment guide 768D.

Drive plate 762D comprises a plurality of drive members 774D operable to generally fit within notches 772D in cam plate 764D. Using such a configuration of drive members 774D and notches 772D, drive plate 762D and/or cam plate 764D may expand and/or contract, such as due to thermal changes, for example. FIG. 68C also illustrates two example alternative configurations 780 and 782 of cam plate notches 772D and drive members 774D. In such alternative embodiments, notches 772D may be located at any suitable position in cam plate 764D. In addition, in alternative embodiments (not shown), drive plate 762 may comprise notches similar to notches 772D and cam plate 764D may comprise drive members similar to drive members 774D.

An advantage of the embodiment illustrated in FIGS. 68A, 68B and 68C is that lubricating oil is isolated from the gases flowing through the compressor and expander.

FIG. 69 illustrates another embodiment of an engine system 700E. Engine system 700E is similar to engine system 700D shown in FIG. 68A; however, third and fourth bearings 728E and 730E of engine system 700E are disposed inwardly and between compressor 702E and expander 704E as compared with third and fourth bearings 728D and 730D shown in FIG. 68A. As discussed above with regard to third and fourth bearings 728B and 730B of engine system 700B shown in FIG. 67, because third and fourth bearings 728E and 730E of engine system 700E may be smaller in diameter than third and fourth bearings 728D and 730D of engine system 700D, the configuration of engine system 700E may be more suitable or desirable for high rotation speed applications than the configuration of engine system 700D. In addition, because third and fourth bearings 728E and 730E are located inwardly from the outer perimeter of outer gerotor assembly 716E, housing 706E may have a smaller outer diameter or perimeter than that of housing 706D, assuming outer gerotor assemblies 716D and 716E have the same outer diameter.

FIG. 70A illustrates an embodiment of an engine system 700F comprising a compressor 702F and an expander 704F in which gases enter and exit compressor 702F and expander 704F through openings in the outer perimeter of compressor 702F and expander 704F. Similar to several of the embodiments discussed above, engine system 700F comprises compressor 702F, expander 704F, and a housing 706F. An outer gerotor assembly 716F comprises a compressor outer gerotor 708F and an expander outer gerotor 712F. An inner gerotor assembly 718F comprises a compressor inner gerotor 710F and an expander inner gerotor 714F.

Outer gerotor assembly 716F comprises an outer gerotor shaft 790F, and inner gerotor assembly 718F comprises an inner gerotor shaft 792F. Outer gerotor shaft 790F is rotatably coupled to housing 706F by a first bearing 794F and to inner gerotor shaft 792F by a second bearing 796F. Inner gerotor shaft 792F is rigidly attached to housing 706F. Inner gerotor shaft 792F is rotatably coupled to outer gerotor assembly 716F by a third bearing 798F. Inner gerotor assembly 718F is rotatably coupled to inner gerotor shaft 792F by a fourth bearing 800F and a fifth bearing 802F. With this configuration, outer gerotor assembly 716F and inner gerotor assembly 718F may rotate relative to each other and relative to housing 706F.

Unlike engine systems 700A-700E described above, engine system 700F is configured such that gases may enter into and exit from compressor 702F and expander 704F through openings in the outer perimeter of compressor outer

29

gerotor **708F** and expander outer gerotor **712F**. A portion of housing **706F**, which may comprise a first valve plate **804F**, comprises a compressor gas inlet port **736F** and an expander gas inlet port **740F**. Another portion of housing **706F**, which may comprise a second valve plate **806F**, comprises a compressor gas outlet port **738F** and an expander gas outlet port **742F**.

Regarding compressor **702F**, gas enters housing **706** through compressor gas inlet port **736F**, enters an outer gerotor chamber **744F** through one or more openings **808F** (shown in greater detail in FIGS. **70B** and **70C**), becomes compressed due to the rotation of compressor inner gerotor **710F** in relation to compressor outer gerotor **708F**, exits outer gerotor chamber **744F** through one or more of the openings in compressor outer gerotor **708F**, and exits housing **706F** through compressor gas outlet port **738F**. Generally, gas enters compressor gas inlet port **736F** at a first, relatively low, pressure and exits through compressor gas outlet port **738F** at a second, relatively high, pressure.

Regarding expander **704F**, gas enters housing **706F** through expander gas inlet port **740F**, enters an outer gerotor chamber **746F** through one or more openings **810F** in expander outer gerotor **712F**, expands as expander inner gerotor **714F** rotates relative to expander outer gerotor **712F**, exits outer gerotor chamber **746F** through one or more of the openings **810F** in expander outer gerotor **712F**, and exits housing **706F** through expander gas outlet port **742F**. Generally, gases enter expander gas inlet port **740F** at a first, relatively high, pressure and exits through expander gas outlet port **742F** at a second, relatively low, pressure.

FIG. **70B** illustrates a cross sectional view of compressor **702F** taken along line A-A shown in FIG. **78**. Compressor inner gerotor **710F** is disposed generally within outer gerotor chamber **744F** of compressor outer gerotor **708F**. Outer gerotor chamber **744F** comprises a plurality of notches **812F** disposed proximate a perimeter **814F** of compressor outer gerotor **708F**. Openings **808F** comprise openings in perimeter **814F** which are coupled to notches **812F** of outer gerotor chamber **744F** such that gases may enter into or exit from outer gerotor chamber **744F** through openings **808F** in perimeter **814F**.

Housing **706F** comprises a first inlet opening **816F** operable to receive gases from compressor gas inlet port **736F** and a first outlet opening **818F** operable to communicate gases received from outer gerotor chamber **744F** toward compressor gas outlet port **738F**. The shape, configuration and/or dimensions of first inlet opening **816F** and first outlet opening **818F** may be selected to achieve a particular compression ratio or a range of compression ratios of gases traveling through compressor **702F**. As compressor inner gerotor **708F** rotates, gases within outer gerotor chamber **744F** may be forced toward notches **812F** and into first outlet opening **818F** through openings **808F** at least in part due to centrifugal forces caused by the rotation of expander inner gerotor **708F**.

Compressor inner gerotor **710F** may comprise one or more entrance passages **748F** operable to communicate a lubricant, such as lubricant **534** for example, into outer gerotor chamber **744F** in order to reduce friction between compressor inner gerotor **710F** and compressor outer gerotor **708F**.

FIG. **70C** illustrates a cross sectional view of expander **704F** taken along line B-B shown in FIG. **70A**. Outer gerotor chamber **746F** of expander outer gerotor **712F** comprises a plurality of notches **820F** disposed adjacent a perimeter **822F** of expander outer gerotor **712F**. Openings **810F** comprise openings in perimeter **822F** which are coupled to notches **820F** of outer gerotor chamber **746F** such that gases may

30

enter into and exit from outer gerotor chamber **746F** through openings **810F** in perimeter **822F**.

Housing **706F** may comprise a second inlet opening **824F** operable to receive gases from expander gas inlet port **740F**, and a second outlet opening **826F** operable to communicate gases received from outer gerotor chamber **746F** toward expander gas outlet port **742F**. The shape, configuration and/or dimensions of second inlet opening **824F** and second outlet opening **826F** may be selected to achieve a particular expansion ratio or range of expansion ratios of gases passing through expander **704F**. As expander inner gerotor **712F** rotates, gases within outer gerotor chamber **746F** may be forced toward notches **820F** and into second outlet opening **826F** through openings **810F** at least in part due to centrifugal forces caused by the rotation of expander inner gerotor **712F**. In addition, in some embodiments (not shown), expander inner gerotor **714F** comprises one or more entrance passages (such as entrance passages **748F** shown in FIG. **70B**) operable to communicate a lubricant into outer gerotor chamber **746F** to reduce friction between expander inner gerotor **714F** and expander outer gerotor **712F**.

An advantage of the embodiment illustrated in FIGS. **70A**, **70B** and **70C** is that capacity may be increased by adding length if the diameter is constrained.

FIG. **70D** illustrates an alternative embodiment in which engine system **700F** comprises either compressor **702F** or expander **704F**, rather than both compressor **702F** and expander **704F**.

FIG. **71A** illustrates another embodiment of an engine system **700G**. Engine system **700G** comprises a compressor **712G**, an expander **704G**, a housing **706G**, an outer gerotor assembly **716G** and an inner gerotor assembly **718G**. Engine system **700G** is similar to engine system **700F** shown in FIG. **70A**; however, engine system **700G** additionally includes a synchronizing system **760G** operable to control the relative rotation and/or align inner gerotor assembly **718G** with outer gerotor assembly **716G** as inner gerotor assembly **718G** rotates relative to outer gerotor assembly **716G**. Synchronizing system **760G** may be similar to synchronizing system **760D** described above with reference to FIGS. **68A** and **68C**. In particular, **760G** comprises a cam plate **764G** and an alignment plate **766G**. In addition, in some embodiments, synchronizing system **760G** may include a drive plate similar to drive plate **762D** discussed above with reference to FIGS. **68A** and **68C**. In alternative embodiments, synchronizing system **760G** may include gears, such as described in above embodiments.

FIG. **71B** illustrates an exploded cross section of cam plate **764G** and alignment plate **766G** taken along line A-A shown in FIG. **71A**. The cross-sections of compressor **702G** and expander **704G** taken along line H-H and line I-I of FIG. **71A** may be similar or identical to the cross sections of compressor **702F** and expander **704F** illustrated in FIGS. **70B** and **70C**, respectively.

FIG. **72** illustrates another embodiment of an engine system **700H** comprises a compressor **702H**, an expander **704H** and a synchronizing system **760H**. Engine system **700H** is similar to engine system **700G** shown in FIG. **71A**; however, synchronizing system **760H** of engine system **700H** is disposed on a first side of both compressor **702H** and expander **704H**, rather than being disposed between compressor **702H** and expander **704H**. The cross sections of compressor **702H** and expander **704H** taken along line H-H and line I-I, respectively, shown in FIG. **72** may be similar or identical to cross sections of compressor **702F** and expander **704F** shown in FIGS. **70B** and **70C**, respectively. In addition, cross sections of synchronizing system **760H** taken along line A-A shown in

31

FIG. 72 may be similar or identical to the cross sections of synchronizing system 760G shown in FIG. 71B or the cross sections of 760D shown in FIG. 68C. In alternative embodiments, synchronizing system 760G may include gears, such as described in previous figures.

FIG. 73 illustrates another embodiment of an engine system 700J comprising a compressor 702J, and expander 704J and a synchronizing system 760J. Engine system 700J is similar to engine system 700H shown in FIG. 72; however, synchronizing system 760J of engine system 700J is disposed on the opposite side of both compressor 702J and expander 704J as compared to the location of synchronizing system 760H of engine system 700H.

FIG. 74 illustrates another embodiment of an engine system 700K having a different configuration of bearings and shafts as compared with engine system 700G, 700H and 700J shown in FIGS. 71A, 72 and 73, respectively. As shown in FIG. 74, engine system 700K comprises an outer gerotor assembly 716K and inner gerotor assembly 718K, and an inner gerotor shaft 792K. Inner gerotor assembly 718K is rigidly coupled to inner gerotor shaft 792K, which is rotatably coupled to housing 706K by a first bearing 830K and a second bearing 832K. Outer gerotor assembly 716K is rotatably coupled to housing 706K by a third bearing 834K and a fourth bearing 836K. In this manner, inner gerotor assembly 718K and outer gerotor assembly 716K may rotate relative to each other and relative to housing 706K. Engine system 700K also comprises a synchronizing system 760K operable to synchronize and/or align inner gerotor assembly 718K and outer gerotor 716K, such as discussed above with reference to synchronizing system 760D, for example. As shown in FIG. 74, synchronizing system 760K includes cams and pegs. It may also include gears, as described in earlier figures.

FIG. 75A illustrates another embodiment of an engine system 700L comprising a gerotor apparatus 1L, which may comprise a compressor and/or an expander. Assuming in the embodiment shown in FIG. 75A that gerotor apparatus 1L comprises a compressor 702L, engine system 700L comprises an outer gerotor assembly 716L comprising a compressor outer gerotor 708L and an outer gerotor shaft 790L, and an inner gerotor assembly 718L comprising a compressor inner gerotor 710L and an inner gerotor shaft 792L.

Engine system 700L also comprises a housing 706L comprising a compressor gas inlet port 736L and a compressor gas outlet port 738L allowing gases to enter into an exit from compressor 702L. In some embodiments, compressor gas inlet port 736L and compressor gas outlet port 738L may be formed in a first valve plate 804L and a second valve plate 806L, respectively, which may be integral with or coupled to housing 706L. Inner gerotor shaft 792L is rotatably coupled to housing 706L by a first bearing 830L and a second bearing 832L. Outer gerotor shaft 790L is rotatably coupled to housing 706L by a third bearing 834L and a fourth bearing 836L. In this manner, inner gerotor assembly 718L and outer gerotor assembly 716L may rotate relative to each other and relative to housing 706L.

Engine system 700L may also comprise a synchronizing system 760L operable to synchronize and/or align inner gerotor assembly 718L and outer gerotor assembly 716L. Compressor outer gerotor 708L comprises an outer gerotor chamber 744L. Compressor outer gerotor 708L may also comprise one or more openings 808L in the perimeter of compressor outer gerotor 708L operable to allow gases to enter into and exit from outer gerotor chamber 744L. Inner gerotor assembly 718L may include one or more entrance passages 778L operable to communicate a lubricant, such as lubricant 534

32

for example, into synchronizing system 760L in order to reduce friction between inner gerotor assembly 718L and outer gerotor assembly 716L.

In addition, housing 706L may comprise an inlet passage 840L and an outlet passage 842L operable to allow gases to enter into and exit from outer gerotor chamber 744L. Some embodiments, inlet passage 840L and outlet passage 842L are defined at least in part by a first opening 844L and a second opening 846L formed in a valve plate 848L which may be integral or coupled to housing 706L. Thus, gases entering through compressor gas inlet port 736L may enter outer gerotor chamber 744L through inlet passage 840L as well as through openings 808L formed in the perimeter of compressor outer gerotor 708L. Similarly, gases may exit outer gerotor chamber 744L through outlet passage 842L as well as through openings 808L formed in the perimeter of compressor outer gerotor 708L. This embodiment may allow increased volumes of gases to pass through compressor 702L as compared with one or more other embodiments described above.

FIG. 75B illustrates a cross sectional view of engine system 700L taken along line B-B shown in FIG. 75A. As discussed above, compressor outer gerotor 708L comprises one or more openings 808L in the outer perimeter of compressor outer gerotor 708L which allow gases to enter into and exit from outer gerotor chamber 744L. Housing 706L comprises a first barrier 850L and a second barrier 852L operable to at least substantially prevent the flow of gases around the outer perimeter of compressor outer gerotor 708L. First and second barriers 850L and 852L at least partially define a perimeter gas inlet area 854L and a perimeter gas outlet area 856L. The shape, configuration and size of first and second barriers 850L and 852L may be selected to achieve a desired shape, configuration and size of perimeter gas inlet opening 854L and perimeter gas outlet opening 856L, which may be selected to achieve a desired compression ratio or range of compression ratios of gases passing through 702L.

An advantage of the embodiment illustrated in FIGS. 75A, 75B and 75C is a free-breathing design that has a high volumetric capacity.

FIG. 75C illustrates a cross sectional view of engine system 700L taken along line C-C shown in FIG. 75A. FIG. 75C illustrates inlet passage 840L and outlet passage 842L formed by first opening 844L and second opening 846L, respectively, in housing 706L. As discussed above, in some embodiments, first opening 844L and second opening 846L may be formed in a valve plate 848L integral or coupled to housing 706L. Viewing FIGS. 75B and 75C together, it can be seen that gases entering compressor gas inlet port 736L may enter into gerotor outer chamber 744L through openings 808L in the outer perimeter of compressor outer gerotor 708L as well as through inlet passage 840L formed by first opening 844L in housing 706L. Similarly, it can be seen that gases may exit outer gerotor chamber 744L through openings 808L and the outer perimeter of compressor outer gerotor 708L as well as through outlet passage 842L formed by second opening 846L in housing 706L.

FIG. 76A illustrates another embodiment of an engine system 700M comprising a gerotor apparatus 1M which may comprise a compressor or an expander. In the embodiment shown in FIG. 76A, gerotor apparatus 1M comprises a compressor 702M comprising a compressor outer gerotor 708M and a compressor inner gerotor 710M. Engine system 700M comprises a housing 706M. Engine system 700M is similar to engine system 700L shown in FIG. 75A; however, housing 706M of engine system 700M is configured differently than

housing 706L of engine system 700L, providing a different flow of gases through compressor 702M as compared with compressor 702L.

Housing 706M of engine system 700M comprises a first opening 844M allowing gases to enter into an outer gerotor chamber 744M of compressor 702M. Opening 844M in housing 706M generally provides a compressor gas inlet port 736M. In some embodiments, first opening 844M comprises an opening in a first valve plate 848M, which may be integral or coupled to housing 706M. Unlike with engine system 700L shown in FIG. 75A, gases generally do not enter into outer gerotor chambers 744M through openings in the outer perimeter of compressor outer gerotor 708M.

Gases may exit outer gerotor chamber 744M through one or more openings 808M in the outer perimeter of compressor outer gerotor 708M. Unlike engine system 700L shown in FIG. 75A, engine system 700M does not include an output passage adjacent outer gerotor chamber 744M similar to outlet passage 842L shown in FIG. 75A. It should be noted that as discussed above with regard to gerotor apparatus 1L shown in FIG. 75A, gerotor apparatus 1M shown in FIG. 76A may alternatively comprise an expander rather than compressor 702M.

FIG. 76B illustrates a cross sectional view of engine system 700M taken along line D-D shown in FIG. 76A. As shown in FIG. 76B, housing 706M may be shaped to form an outlet opening 858M allowing gases to exit outer gerotor chambers 744M through openings 808M in the outer perimeter of compressor outer gerotor 708M. The shape, configuration and size of outlet opening 858M may be selected to achieve a desired compression ratio or range of compression ratios of gases traveling through compressor 702M.

FIG. 76C illustrates a cross sectional view of engine system 700M taken along line E-E shown in FIG. 76A. FIG. 76C illustrates compressor gas inlet port 736M formed by first opening 844M in housing 706M. First opening 844M allows gases to enter into outer gerotor chamber 744M. As discussed above, first opening 844M may be formed in first valve plate 848M, which may be integral or coupled to housing 706M.

FIGS. 77A and 77B illustrate an alternative embodiment of the cross section shown in FIG. 76B. Housing 706N comprises a barrier coupling portion 860 and adjustable barrier 862 slidably coupled to barrier coupling portion 860. Adjustable barrier 862 is shaped such that it may be adjusted relative to barrier coupling portion 860 in order to change the shape and or size of output opening 858N. The shape and or size of output 858N may be adjusted using adjustable barrier 862 in order to control the compression ratio of gases exiting outer gerotor chamber 744N through openings 808N. For example, FIG. 77A illustrates a cross section in which adjustable barrier 862 is in a first position, and FIG. 77B illustrates a cross section in which adjustable barrier 862 is in a second position. An advantage of the embodiment illustrated in FIGS. 77A and 77B is the compression ratio is infinitely adjustable allowing compressor or expander efficiency to be maximized.

FIG. 78A illustrates another embodiment of an engine system 700P. Engine system 700P is similar to engine system 700M shown in FIG. 76A; however, engine system 700P comprises a gerotor apparatus 1P which comprises an expander 704P rather than a compressor. Expander 704P comprises an expander outer gerotor 712P comprising an outer gerotor chamber 746P, and an expander inner gerotor 714P.

Engine system 700P comprises a housing 706P which includes a first opening 844P forming an expander gas inlet port 740P operable to allow gases to enter into outer gerotor chamber 746P. First opening 844P may be formed in a first

valve plate 848P, which may be integral or coupled to housing 706P. Gases may exit outer gerotor chamber 746P through one or more openings 808P in the outer perimeter of expander outer gerotor 708P. The gases may then exit housing 706P through an expander gas outlet port 742P. FIG. 78B illustrates a cross sectional view of engine system 700P taken along line F-F shown in FIG. 78A.

Housing 706P is configured to form an outlet opening 858P allowing gases to exit outer gerotor chamber 746P through openings 808P in the outer perimeter of expander outer gerotor 712P. The shape, configuration, and size of outlet opening 858P may be selected based on the desired expansion ratio of gases exiting outer gerotor chamber 746P and or a desired amount of torque applied to expander outer gerotor 712P caused by the expansion of gases within outer gerotor chamber 746P.

FIG. 78C illustrates a cross sectional view of engine system 700P taken along line G-G shown in FIG. 78A. FIG. 78C illustrates expander gas inlet port 740P formed by a first opening 844P formed in housing 706P. First opening 844P allows gases to enter outer gerotor chamber 746P through expander gas inlet port 740P. As discussed above, first opening 844P may be formed in first valve plate 848P, which may be integral or coupled to housing 706P. First opening 844P may be shaped and or sized to allow a desired level of gas flow into expander 704P.

FIGS. 79A and 79B illustrate three-dimensional views of two embodiments of a compressor outer gerotor 708 or an expander outer gerotor 712, such as compressor outer gerotor 708 or expander outer gerotor 712 shown in FIGS. 70 and 75-78, for example. As shown in FIG. 79A, outer gerotor 708 or 712 comprises a base section 864 and a plurality of openings 808 formed in the perimeter of outer gerotor 708 or 712. As shown in FIG. 79B, outer gerotor 708 or 712 may also comprise a support ring 866 to provide support or rigidity to outer gerotor 708 or 712.

FIG. 80 illustrates an embodiment of a gerotor apparatus 870 comprising an outer gerotor 872 and an inner gerotor 874. Outer gerotor 872 may comprise an outer gerotor skin 876 supported by an outer gerotor web 878. Inner gerotor 874 may comprise an inner gerotor web 880 supported by an inner gerotor web 882. Outer gerotor web 878 and inner gerotor web 882 may be formed by extrusion, and may comprise any material suitable for extrusion, such as aluminum or plastic, for example. In one embodiment, outer gerotor web 878 and inner gerotor web 882 may each be extruded as a single piece.

FIG. 81A illustrates an alternative embodiment of gerotor apparatus 870 shown in FIG. 80. In the embodiment shown in FIG. 81A, outer gerotor web 878 comprises a plurality of outer gerotor web sections 878A-878F. Similarly, inner gerotor web 882 comprises a plurality of inner gerotor web sections 882A-882E. Inner gerotor web sections 882A-882E may be coupled to each other and to an inner gerotor support structure 884.

FIG. 81B illustrates a particular outer gerotor web section 878A, a particular inner gerotor web section 882A, and inner gerotor support structure 884 in accordance with one embodiment. Outer gerotor web sections 878A-878F may be coupled to each other by tongue-and-groove couplers 886. Similarly, inner gerotor web sections 882A-882E may be coupled to each other and to inner gerotor support structure 884 using tongue-and-groove couplers 886. As shown in FIG. 81A, a support sleeve 888 may be disposed around outer gerotor web sections 878A-878F to provide support and or rigidity to outer gerotor web 878.

FIG. 82 illustrates another embodiment of gerotor apparatus 870, in which outer gerotor web 878 comprises a plurality

of web openings **890** into which magnets or ferromagnetic material may be inserted, such as discussed below.

FIG. **83** illustrates gerotor apparatus **870** shown in FIG. **82**, in which masses of ferromagnetic material **892** are disposed within each web opening **890**. Ferromagnetic masses **892** may be used in connection with a motor or generator, such as described below. Ferromagnetic masses **892** may comprise one or more ferromagnetic materials, such as iron, nickel or cobalt, for example.

FIG. **84A** illustrates an example embodiment of a gerotor apparatus **870A** comprising an outer gerotor **872A**, an inner gerotor **874A**, and an electric motor or generator **900A**. In the embodiment shown in FIG. **84A**, electric motor or generator **900A** comprises a switched reluctance machine (SRM), which may be used as either a motor or a generator. Switched reluctance machine **900A** comprises a plurality of ferromagnetic masses **892A** (such as shown in FIG. **83**) and a plurality of coils **902A** disposed around the outer perimeter of outer gerotor **872A**. In one embodiment, coils **902A** are C-shaped coils which extend over ferromagnetic masses **892A** on each side of outer gerotor **872A**, as shown in FIG. **84B** and discussed below.

In an embodiment in which switch reluctance machine **900A** is a switched reluctance motor, coils **902A** and ferromagnetic masses **892A** may interact to at least partially control the rotation of outer gerotor **872A**. Alternatively, in an embodiment in which switched reluctance machine **900A** is a switched reluctance generator, coils **902A** and ferromagnetic masses **892A** may interact to generate electricity as outer gerotor **872A** rotates. In some embodiments, as shown in FIG. **84A** for example, the number of coils **902A** does not match the number of ferromagnetic masses **892A**, which allows the firing sequence of coils **902A** to be adjusted for relatively smooth operation of electric motor or generator **900A**.

FIG. **84B** illustrates a schematic side view of gerotor apparatus **870A** shown in FIG. **84A**, including electric motor or generator **900A**. As shown in FIG. **84B**, ferromagnetic masses **892A** may extend across the thickness of outer gerotor **872A**. Coils **902A** may comprise C-shaped coils having a first end **914A** adjacent a first side **916A** of outer gerotor **872A** and a second end **918A** adjacent a second side **920A** of outer gerotor **872A**. A controller **922A** may be coupled to each coil **902A** and operable to control the timing of the firing of each coil **902A** within electric motor or generator **900A**. A shaft **924A** may be coupled to outer gerotor **872A** or inner gerotor **874A**. An optional position sensor **926A** may be disposed proximate shaft **924A** and operable to detect the position of one or more position targets **928A** as the shaft **924A** rotates. Optional position sensor **926** may be operable to communicate with each controller **922A** in order to properly control the timing of the firing of each of the coils **902A** according to the rotational position of outer gerotor **872A**.

An advantage of the embodiment illustrated in FIGS. **84A** and **84B** is low cost and the ability to operate at high speeds.

FIGS. **85A** and **85B** illustrate another embodiment of a gerotor apparatus **870B** comprising an outer gerotor **872B**, an inner gerotor **874B**, and an electric motor or generator **900B**. Like electric motor or generator **900A** shown in FIG. **84A**, electric motor or generator **900B** shown in FIG. **85A** comprises a plurality of ferromagnetic masses **892B** and plurality of coils **902B**. However, ferromagnetic masses **983B** are coupled or embedded to the outer perimeter of outer gerotor **872B**.

FIG. **85B** illustrates a blown up cross section of a particular ferromagnetic mass **892B** aligned with a particular coil **902B**. As shown in FIG. **85B**, coiled **902B** may comprise a C-shaped

coil. An advantage of the embodiment illustrated in FIGS. **85A** and **85B** is a more compact coil.

FIG. **86** illustrates another embodiment of a gerotor apparatus **870C** comprising an outer gerotor **872C**, an inner gerotor **874C**, and an electric motor or generator **900C**. Electric motor or generator **900C** comprises a permanent magnet motor or generator comprising a plurality of coils **902C** and a plurality of permanent magnets **904C** coupled around the outer perimeter of outer gerotor **872C**. In an embodiment in which electric motor or generator **900C** comprises a permanent magnet motor, coils **902C** and permanent magnets **904C** interact to at least partially control the rotation of outer gerotor **872C**. Alternatively, in an embodiment in which electric motor or generator **900C** comprises a permanent magnet generator, coils **902C** and permanent magnets **904C** interact to generate electricity as outer gerotor **872C** rotates. An advantage of the embodiment illustrated in FIG. **86** is high efficiency.

FIG. **87A** illustrates a cross section of another embodiment of a motor or generator apparatus **870D** comprising an outer gerotor **872D**, an inner gerotor **874D**, and a squirrel-cage induction motor or generator comprising a plurality of coils **902D** and a squirrel-cage **906** disposed around outer gerotor **872D**.

FIG. **87B** illustrates a three-dimensional view of an example squirrel-cage **906D**. Squirrel-cage **906D** comprises a plurality of parallel cage bars **908D**, each coupled to a first ring support **910D** and a second ring support **912D**. FIG. **87A** illustrates a cross-section of the plurality of cage bars **908D**, which may or may not be coupled to outer gerotor **872D**.

In an embodiment in which electric motor or generator **900D** comprises a squirrel-cage motor, coils **902D** and squirrel-cage **906D** interact in order to at least partially control the rotation of outer gerotor **872D**. Alternatively, in an embodiment in which electric motor or generator **900D** comprises a squirrel-cage generator, coils **902D** and squirrel-cage **906D** interact to generate electricity as squirrel-cage **906D** rotates along with outer gerotor **872D**.

FIG. **88** illustrates a configuration of an example gerotor apparatus **870E** used to generate various alignment tracks to control the movement of components of gerotor apparatus **870E**. Gerotor apparatus **870E** comprises an outer gerotor **872E**, an inner gerotor **874E**, and a radial bar **930E** rigidly coupled to inner gerotor **874E**. As inner gerotor **874E** and outer gerotor **872E** rotate, various points along radial bar **930E** may be used to trace patterns for alignment tracks in outer gerotor **872E**, such as shown in FIGS. **89** and **90**, for example. If radial bar **930E** is rigidly attached to outer gerotor **872E**, the alignment tracks are traced on inner gerotor **874E**.

For example, a first point A on radial bar **930E** may trace a pattern for an alignment track in outer gerotor **872E**, such as shown in FIGS. **89A-89D**. As another example, a second point B on radial bar **930E** may be used to trace an alignment track in outer gerotor **874E**, such as shown in FIGS. **90A-90D**.

FIG. **89A** illustrates a cross-section of an embodiment of a gerotor apparatus **870F** comprising an inner gerotor **874F**, an outer gerotor **872F**, and a synchronizing system **871F** coupled to and/or integrated with inner gerotor **874F** and/or outer gerotor **872F**. Synchronizing system **871F** comprises an alignment guide, or track, **932F** formed in outer gerotor **872F** having a shape defined by the pattern traced by point A, as described above with reference to FIG. **88**. In the embodiment shown in FIG. **89A**, the opening in outer gerotor **872F** comprises six notches **873F** and alignment track **932F** comprises six notches **933F**.

Synchronizing system 871F also comprises a plurality of alignment members 934F, such as knobs, rollers or pegs, for example, coupled to, or integral with, inner gerotor 874F (as shown in FIG. 89B) and aligned within alignment track 932F. In the embodiment shown in FIG. 89A, inner gerotor 874F comprises five protrusions, or tips, 875F, and five alignment members 934F are coupled to inner gerotor 874F. As inner gerotor 874F and outer gerotor 872F rotate relative to each other, alignment members 934F travel along alignment track 932F in order to provide alignment between inner gerotor 874F and outer gerotor 872F.

FIG. 89B illustrates a side view of gerotor apparatus 870F shown in FIG. 89A. As shown in FIG. 89B, alignment members 934F are coupled to inner gerotor 874F by a first plate 936F. Alignment members 934F are generally disposed within and travel along alignment track 932F as inner gerotor 874F rotates relative to outer gerotor 872F.

FIG. 89C illustrates a three-dimensional view of an outer gerotor 872G including an alignment track 932G similar to outer gerotor 872F and alignment track 932F (shown in FIGS. 89A and 89B). However, in this embodiment, outer gerotor 872G comprises seven notches 873G whereas outer gerotor 872F comprises six notches 873F (as shown in FIG. 89A). Similarly, alignment track 932G comprises seven notches 933G whereas alignment track 932F comprises six notches 933F (as shown in FIG. 89A).

FIG. 89D illustrates a three-dimensional view of an inner gerotor 874G and a plurality of alignment members 934G coupled to inner gerotor 874G similar to inner gerotor 874F and alignment members 934F (shown in FIGS. 89A and 89B). However, in this embodiment, inner gerotor 874G comprises six protrusions 875G whereas inner gerotor 874F comprises five protrusions 875F (as shown in FIG. 89A). Similarly, the embodiment shown in FIG. 89D includes six alignment members 934G as opposed to the embodiment shown in FIG. 89A which includes five alignment members 934F.

An advantage of the embodiment illustrated in FIGS. 89A-89D is a compact design with short axial length.

FIG. 90A illustrates a cross sectional view of another embodiment of a gerotor apparatus 870H comprising an outer gerotor 872H, an inner gerotor 874H, an outer gerotor 872H, and a synchronizing system 871H coupled to and/or integrated with inner gerotor 874H and/or outer gerotor 872H. Synchronizing system 871H comprises an alignment track 932H formed in outer gerotor 872H having a shape defined by the pattern traced by point B on radial bar 930E shown in FIG. 88. In the embodiment shown in FIG. 90A, the opening in outer gerotor 872H comprises six notches 873H and alignment track 932H comprises six loops 933H.

Synchronizing system 871F also comprises a plurality of alignment members 934H, such as knobs, rollers, or pegs, for example, are coupled to inner gerotor 874H and generally disposed in alignment with alignment track 932H. In the embodiment shown in FIG. 90A, inner gerotor 874H comprises five protrusions, or tips, 875H, and five alignment members 934H are coupled to inner gerotor 874H. As inner gerotor 874H rotates relative to outer gerotor 872H, alignment members 934H and alignment track 932H interact to provide alignment between inner gerotor 874H and outer gerotor 872H.

FIG. 90B illustrates a side view of gerotor apparatus 870H shown in FIG. 90A. As shown in FIG. 90B, alignment members 934H are coupled to inner gerotor 874H and aligned within alignment track 932H.

FIG. 90C illustrates a three-dimensional view of an outer gerotor 872J including an alignment track 932J similar to

outer gerotor 872H and alignment track 932H (shown in FIGS. 90A and 90B). However, in this embodiment, outer gerotor 872J comprises seven notches 873G whereas outer gerotor 872H comprises six notches 873J (as shown in FIG. 90A). Similarly, alignment track 932J comprises seven loops 933J whereas alignment track 932H comprises six loops 933H (as shown in FIG. 90A).

FIG. 90D illustrates a three-dimensional view of an inner gerotor 874J and a plurality of alignment members 934J coupled to inner gerotor 874J similar to inner gerotor 874H and alignment members 934H (shown in FIGS. 90A and 90B). However, in this embodiment, inner gerotor 874J comprises six protrusions 875J whereas inner gerotor 874H comprises five protrusions 875H (as shown in FIG. 90A). Similarly, the embodiment shown in FIG. 90D includes six alignment members 934J as opposed to the embodiment shown in FIG. 90A which includes five alignment members 934H.

An advantage of the embodiment illustrated in FIGS. 90A-90D is a compact design with very short axial length.

The following discussion, taken in conjunction with FIGS. 91A and 91B, describes an example method of generating the patterns for alignment tracks 932G and 932J shown in FIGS. 89C and 90C, respectively. In other words, the following discussion illustrates a method of determining various alignment tracks for an embodiment in which the outer gerotor comprises seven notches (such as notches 873G or 873J shown in FIGS. 89C and 90C, respectively) and the inner gerotor comprises six protrusions, or tips (such as protrusions 875G or 875J shown in FIGS. 89D and 90D, respectively).

Considering FIG. 91A, because the angular velocity of the outer gerotor and inner gerotor should have a constant ratio of 6:7, theta and phi can be related by the following equation:

$$\phi = \frac{6}{7}\theta \tag{Eq. (1)}$$

The point PO is located on circle 1 and moves as that part rotates. The coordinate values, X_{1t} and Y_{1t} , relative to a fixed set of coordinate axes are:

$$\begin{aligned} X_{1t} &= R \cos(\theta) \\ Y_{1t} &= R \sin(\theta) \end{aligned} \tag{Eq. (2)}$$

To plot the path, point P needs to be tracked with respect to circle 2. The coordinates of point Pt using point C2 as the origin are:

$$\begin{aligned} X_{2t} &= X_{1t} + S \\ Y_{2t} &= Y_{1t} \end{aligned} \tag{Eq. (3)}$$

Note the sign convention on the X value
With these defined, the length D can be found by using the Pythagorean theorem:

$$\begin{aligned} D &= \sqrt{X_{2t}^2 + Y_{2t}^2} \\ D &= \sqrt{(R \cos(\theta) + S)^2 + (R \sin(\theta))^2} \\ D &= \sqrt{R^2 \cos^2(\theta) + 2RS \cos(\theta) + S^2 + R^2 \sin^2(\theta)} \\ D &= \sqrt{R^2 + 2RS \cos(\theta) + S^2} \end{aligned} \tag{Eq. (4)}$$

however, plotting the path of the point on circle 2 cannot be done with the fixed coordinate system, since circle 2 is also

rotating. The coordinate system must rotate with the circle. Thus, the actual path on a stationary disk would be:

$$\begin{aligned} X &= D \cos(\Psi) \\ Y &= D \sin(\Psi) \end{aligned} \tag{Eq. (5)}$$

Psi and Theta must now be related to one another to allow parametric equations to be written for X and Y in terms of theta.

$$\eta = \phi + \Psi \tag{Eq. (6)}$$

Using the law of cosines on triangle C1, C2, Pt illustrated in FIG. 91B provides:

$$R^2 = S^2 + D^2 - 2SD \cos(\eta) \tag{Eq. (7)}$$

Solving Equation (7) for eta:

$$\eta = \cos^{-1} \left(\frac{R^2 - S^2 - D^2}{2SD} \right) \tag{Eq. (8)}$$

Substituting Equation (4) into Equation (8) provides:

$$\begin{aligned} \eta &= \cos^{-1} \left(\frac{R^2 - S^2 - (R^2 + 2RS\cos(\theta) + S^2)}{2S\sqrt{R^2 + 2RS\cos(\theta) + S^2}} \right) \\ \eta &= \cos^{-1} \left(\frac{-R\cos(\theta) - S}{\sqrt{R^2 + 2RS\cos(\theta) + S^2}} \right) \end{aligned} \tag{Eq. (9)}$$

Combining Equations (1), (6) and (9) provides:

$$\begin{aligned} \cos^{-1} \left(\frac{R\cos(\theta)}{\sqrt{R^2 + 2RS\cos(\theta) + S^2}} \right) &= \frac{6}{7}\theta + \psi \\ \psi &= \cos^{-1} \left(\frac{R\cos(\theta)}{\sqrt{R^2 + 2RS\cos(\theta) + S^2}} \right) - \frac{6}{7}\theta \end{aligned} \tag{Eq. (10)}$$

Using Equations (4), (5) and (10), the values for X and Y can be solved (such as by using a spreadsheet, for example) and the path of point P can be plotted as if circle 2 was stationary.

For example, a spreadsheet may be used to calculate one lobe of the path by varying theta from 0 to 360° in small increments. To plot the entire path, the same D values may be used with psi incremented by 2(π)/7 for each lobe. An example of a complete plot is shown in FIG. 91C. By changing the peg radius, R (for example, to R=2 inches), the track shown in FIG. 91D may be generated. Alignment tracks 932G and 932J shown in FIGS. 89C and 90C, respectively, may be generated using the method described above.

FIG. 92 illustrates a schematic of an example embodiment of an engine system 940. Engine system 940 comprises a gerotor compressor 942, a gerotor expander 944, a heat exchanger 946, a combustor 948, a pressure tank 950, a drive apparatus 952, and one or more additional compressor/expanders 954. Engine system 940 also comprises an expander clutch 956 coupled to gerotor expander 944 and operable to engage and disengage gerotor expander 944 from drive apparatus 952, a compressor clutch 958 coupled to gerotor compressor 942 and operable to engage and disengage gerotor compressor 942 from drive apparatus 952, and a compressor/expander clutch 960 coupled to each additional compressor/expander 954 and operable to engage and disengage each additional compressor/expander 954 from drive assembly 952. In some embodiments, expander clutch 956 operates

independently from compressor clutch 958. In particular embodiments, clutches 956, 958 and 960 each function independently to engage or disengage from drive apparatus 952.

In operation, during steady state, gerotor compressor 942 receives a volume of gas, such as a volume of ambient air for example, compresses the gas, and communicates the compressed gas toward heat exchanger 946 along path 962 shown in FIG. 92. The compressed gas travels through a first valve 964, which is generally open during steady-state operation, travels through heat exchanger 946 and combustor 948, where the compressed gas is heated. The heated compressed gas enters gerotor expander 944 and drives shaft 966 as it expands within gerotor expander 944. The expanded, or decompressed, gas exits gerotor expander 944 along path 968, travels through heat exchanger 946 where the gas is cooled, and exits engine system 940 as exhaust. During steady-state operation, a second valve 970 between gerotor compressor 942 and the one or more additional compressor/expanders 954 remains closed. In addition, during steady-state operation, expander clutch 956 and compressor clutch 958 are generally engaged with drive apparatus 952. Compressor/expander clutches 960 may be disengaged from drive apparatus 952.

During a braking state (such as when a vehicle including engine system 940 is braking, for example), expander clutch 956 may disengage from drive apparatus 952 while compressor clutch 958 remains engaged with drive apparatus 952. The kinetic energy of drive apparatus 952 (such as caused by kinetic energy of the vehicle) continues to drive gerotor compressor 942. In addition, compressor/expander clutches 960 are engaged with drive apparatus 952 during the braking state. In addition, first valve 964 is closed and second valve 970 is opened during the braking state such that compressed gases exiting gerotor compressor 942 are communicated along path 972 toward the one or more additional compressor/expanders 954, which may further process the compressed gases. For example, in an embodiment in which engine system 940 comprises an additional compressor 954, compressed gases communicated to the additional compressor 954 along path 972 may be further compressed by the additional compressor 954 and communicated into pressure tank 950. Using additional compressors 954 along with gerotor compressor 942, gases may be relatively highly compressed before being stored in pressure tank 950, which may reduce the required volume or size of pressure tank 950. Each additional compressor 954 may be similar or identical to gerotor compressor 942. Similarly, in an embodiment in which engine system 940 comprises one or more additional expanders 954, each additional expander 954 may be similar or identical to gerotor expander 944.

In a startup state (such as when the vehicle including engine system 940 starts up, for example), compressed gas from the pressure tank 950 flows through one or more expanders 954 while clutch 960 is engaged. Valves 970 and 964 are open allowing gas to travel through heat exchanger 946 and combustor 948 in order to drive gerotor expander 944. In some embodiments, during the startup state, expander clutch 956 is engaged with drive apparatus 952, while compressor clutch 958 is disengaged from drive apparatus 952 for at least a portion of the startup state.

FIG. 93 illustrates an embodiment of a gerotor apparatus 870K comprising an outer gerotor 872K, in inner gerotor 874K, a housing 976K, and a synchronizing system 978K operable to control the rotation of outer gerotor 872K relative to the rotation of inner gerotor 874K. An outer gerotor shaft 980K is rigidly coupled to outer gerotor 872K and rotatably coupled housing 976K by a first bearing 982K and a second

bearing **984K**. Similarly, an inner gerotor shaft **986K** is rigidly coupled to inner gerotor **874K** and rotatably coupled housing **976K** by a third bearing **988K** and a second bearing **990K**.

Synchronizing system **978K** comprises a first rotational object **992K** coupled to outer gerotor shaft **980K**, a second rotational object **994K** coupled to inner gerotor shaft **986K**, and a third rotational object **996K** and a fourth rotational object **998K** coupled to a synchronizing system shaft **1000K**. First rotational object **992K** and third rotational object **996K** are coupled to each other by a first belt device **1002K**, and second rotational object **994K** and fourth rotational object **998K** are coupled to each other by a second belt device **1004K**.

First and second belt devices **1002K** and **1004K** may comprise any device suitable to drive rotational objects **992K**, **994K**, **996K** and **998K**. For example, in some embodiments (such as shown in FIG. **93**, for example), rotational objects **992K**, **994K**, **996K** and **998K** comprise pulleys and first and second belt devices **1002K** and **1004K** comprises timing belts **1002K** and **1004K**. Timing belts **1002K** and **1004K** may comprise Kevlar or carbon fiber belts, or any other substantially rigid belts, such cable belts that are able to resist stretching. In other embodiments, rotational objects **992K**, **994K**, **996K** and **998K** comprise gear sprockets and first and second belt devices **1002K** and **1004K** comprises chains **1002K** and **1004K** operable to interact with gear sprockets **992K**, **994K**, **996K** and **998K**.

As discussed above, synchronizing system **978K** is generally operable to control the rotation of outer gerotor **872K** relative to the rotation of inner gerotor **874K**. This may be achieved by appropriately selecting the size (or number of sprockets) of rotational objects **992K**, **994K**, **996K** and **998K** relative to each other. For example, as shown in FIG. **93**, third rotational object **994K** is smaller in diameter than first rotational object **992K** such that inner gerotor **874K** rotates at a greater speed than outer gerotor **872K**.

FIG. **94** illustrates another embodiment of a gerotor apparatus **870L** comprising an outer gerotor **872L**, an inner gerotor **874L**, a housing **976L**, and a synchronizing system **978L** operable to control the rotation of outer gerotor **872L** relative to the rotation of inner gerotor **874L**. An outer gerotor shaft **980L** is rigidly coupled to outer gerotor **872L** and rotatably coupled housing **976L** by a first bearing **982L** and a second bearing **984L**. Similarly, an inner gerotor shaft **986L** is rigidly coupled to inner gerotor **874L** and rotatably coupled housing **976L** by a third bearing **988L** and a second bearing **990L**.

Synchronizing system **978L** comprises a first rotation object **992L** rigidly coupled to outer gerotor shaft **980L**, a second rotation object **994L** is rigidly coupled to inner gerotor shaft **986L**, and a belt device **1002L** coupling first rotation object **992L** with second rotation object **994L**. Belt device **1002L** and rotation objects **992L** and **994L** may comprise any suitable devices, such as those discussed above regarding belt devices **1002K** and **1004K** and rotational objects **992K**, **994K**, **996K** and **998K** shown in FIG. **93**, for example.

FIGS. **95A**, **95B** and **95C** illustrate an embodiment of a gerotor apparatus **870M** in which gas enters into and exits from the gerotor apparatus **870M** through a central shaft. Gerotor apparatus **870M** may comprise a compressor or an expander, depending on the embodiment. As shown in FIG. **95A**, gerotor apparatus **870M** comprises an outer gerotor **872M**, an inner gerotor **874M**, an alignment mechanism **1015M**, and a housing **976M**. The alignment mechanism **1015M** shown here may be similar to that shown in FIG. **55**, but other alignment mechanisms, such as gears, may be used also. Outer gerotor **872M** is rotatably coupled to housing

976M by a first bearing **982M** and a second bearing **984M**. Inner gerotor **874M** is rigidly coupled to an inner gerotor shaft **986M**, which is rotatably coupled to housing **976M** by a third bearing **998M** and a fourth bearing **990M**.

Outer gerotor **872M** comprises an outer gerotor chamber **1010M** in which gases are compress or expanded, depending on whether gerotor apparatus **870M** comprised a compressor or an expander. Inner gerotor shaft **986M** comprises an inside opening **1012M** through which gases may enter into and exit from outer gerotor chamber **1010M**. A separator **1014M** is disposed within inside opening **1012M** and is configured such that it is substantially separates a first, intake section **1016M** of inside opening **1012M** from a second, exit section **1018M** of inside opening **1012M**, as shown in FIGS. **95B** and **95C**. Intake section **1016M** of inside opening **1012M** is operable to receive and communicate gases into outer gerotor chamber **1010M** through one or more passages **1020M** in inner gerotor **874M**, as shown in FIGS. **95B** and **95C**. Similarly, exit section **1018M** is operable to receive gases from outer gerotor chamber **1010M** through one or more passages **1020M** and release such received gases away from gerotor apparatus **870M**, as shown in FIGS. **95B** and **95C**.

In an embodiment in which gerotor apparatus **870M** comprises a compressor (such as the embodiment shown in FIGS. **95A**, **95B** and **95C**), intake section **1016M** of inside opening **1012M** communicates relatively low pressure gases into outer gerotor chamber **1010M** through passages **1020M** in inner gerotor **874M**. As outer gerotor **872M** and an inner gerotor **874M** rotate relative to each other, gases within intake section **1016M** become compressed. The compressed gases may then enter exit section **1018M** of inside opening **1012M** through passages **1020M** and escape away from gerotor apparatus **870M**.

FIGS. **96** through **101** illustrate various embodiments of a gerotor apparatus **1r**. Gerotor apparatus **1r** includes a housing **2r**, an outer gerotor **4r** disposed within housing **2r**, and an inner gerotor **6r** disposed within outer gerotor **4r**. Gerotor apparatus **1r** includes a lower shaft **450** coupled to an end of housing **2k** that includes a gas inlet port **452** and a gas exhaust **454**. A gear housing **456** is coupled to lower shaft **450** and an upper shaft **458** couples to gear housing **456** and extends upwards towards the top of housing **2r**. A rotating shaft **460** is rotatably coupled to housing **2r** by a bearing **461**. Shaft **460** couples to outer gerotor **4r** and also rotatably couples to upper shaft **458** via a hollow shaft **462** and suitable bearings. Inner gerotor **6r** is rotatably coupled to lower shaft **450** via suitable bearings.

Gear housing **456** includes an idler gear **464** coupling a first gear **466** that is associated with outer gerotor **4r** and a second gear **468** that is associated with inner gerotor **6r**. Idler gear **464** is rotatably coupled to gear housing **456** in any suitable manner, such as by bearings. In the illustrated embodiment, both first and second gears are ring gears having interior gear teeth. In general operation, when shaft **460** rotates, as denoted by arrow **469**, it rotates outer gerotor **4r**, which rotates first gear **466**, which rotates idler gear **464**, which rotates second gear **468**, which rotates inner gerotor **6r**. An advantage of the embodiment illustrated in FIG. **96** is compactness.

Also illustrated in FIG. **96** is a jacket **470** that exists around a perimeter of housing **2r**. Jacket **470** has an inlet **471** and an exit **472** that function to recirculate any suitable fluid around the perimeter of housing **2r** to control the temperature of housing **2r**, thereby regulating its length and controlling the gap. A proximity sensor **474** measures a gap between the end of outer gerotor **4r** and housing **2r**. Proximity sensor **474** may be coupled to a suitable controller (not shown) that controls the flow of fluid through jacket **470** to regulate the gap to a

predetermined distance. The present invention contemplates other methods to regulate the gap between outer gerotor **4r** and housing **2r**. For example, gerotor apparatus **1r** may have a retaining ring **476** coupled to an upper portion of housing **2r** with one or more adjustment screws **477**. Retaining ring **476** may allow an adjustment of the gap between the bottom of outer gerotor **4r** and housing **2r** via adjustment screws **477**.

FIG. **97** illustrates an additional embodiment of gerotor apparatus **1r**. The embodiment illustrated in FIG. **97** is substantially similar to the embodiment illustrated in FIG. **96**; however, in the embodiment of FIG. **97**, second gear **468** is a spur gear instead of a ring gear having interior teeth. Accordingly, a pair of idler spur gears **478** replace idler gear **464** in order to couple first gear **466** to second gear **468**.

FIG. **98** illustrates an additional embodiment of gerotor apparatus **1r**. The embodiment illustrated in FIG. **98** is substantially similar to the embodiment illustrated in FIG. **96**; however, in the embodiment of FIG. **98**, idler gear **464** is rotatably coupled to gear housing **456** with a U-shaped bracket **480**. An advantage of using U-shaped bracket **480** is that it allows idler gear **464** to be relatively large, which aids in slowing its rotational speed.

FIGS. **99** and **100** illustrate additional embodiments of gerotor apparatus **1r**. The embodiments illustrated in FIGS. **99** and **100** are substantially similar to the embodiment illustrated in FIG. **98**; however, in the embodiment of FIGS. **99** and **100**, lower shaft **450** is coupled to housing **2r** with a flexible mount to allow the entire drive shaft assembly to pivot slightly. As illustrated in FIG. **99**, the flexible mount is a flexible ring **482** formed from any suitable material, such as rubber or plastic. As illustrated in FIG. **100**, the flexible mount is a flexible disk **484** formed from any suitable material, such as rubber or plastic.

FIG. **101** illustrates an additional embodiment of gerotor apparatus **1r**. The embodiment illustrated in FIG. **101** is substantially similar to the embodiment illustrated in FIGS. **99** and **100**; however, in the embodiment of FIG. **101**, lower shaft **450** is coupled to housing **2r** with a suitable pivot **486**. For example, lower shaft **450** may have a rounded end that engages a rounded hole formed in housing **2r**. An anti-rotation pin **488** loosely couples to the bottom of housing **2r** to prevent lower shaft **450** from rotating during operation. To ensure that a relatively tight fit exists at pivot **486**, a collar **490** may be coupled to shaft **460** and a collar **491** may be coupled to upper shaft **458**. Collar **490** is engaged with a bearing **492** that is hard mounted to retaining ring **476** and collar **491** is engaged with a bearing **493** hard mounted to hollow shaft **462**. Therefore, adjustment screws **477** may be utilized to ensure a tight fit at pivot **486**.

Although embodiments of the invention and their advantages are described in detail, a person skilled in the art could make various alterations, additions, and omissions without departing from the spirit and scope of the present invention.

What is claimed is:

1. A gerotor apparatus, comprising:

a housing;

an outer gerotor disposed within the housing; and

an inner gerotor disposed within the outer gerotor;

wherein:

at least one of the inner gerotor and the outer gerotor is configured to rotate with respect to the other,

at least one of the inner gerotor and the outer gerotor has first and second layers,

the first layer is a ceramic, and

the second layer is a non-ceramic;

wherein a combination of the housing, the outer gerotor, and the inner gerotor is configured for at least a compression or an expansion of fluid;

wherein at least one of the inner gerotor and the outer gerotor further comprises protrusions or knobs coupling the first layer to the second layer; and

wherein the protrusions or knobs either extend from the first ceramic layer into the second non-ceramic layer or extend from a common point in one of the layers radially outward into the other of the layers.

2. The gerotor apparatus of claim **1**, wherein the at least one of the inner gerotor and the outer gerotor having the first and second layers further comprises a plurality of teeth at least partially formed from each of the first and second layers.

3. The gerotor apparatus of claim **1**, wherein both of the inner gerotor and the outer gerotor have two layers.

4. The gerotor apparatus of claim **1**, wherein:

a receiving portion of one of the first or second layer is configured to receive a portion of the other of the first or second layer to couple the first layer to the second layer, and

the receiving portion is either the second non-ceramic layer or an outer layer of the inner gerotor.

5. The gerotor apparatus of claim **1**, wherein:

at least one of the first layer or the second layer comprises a plurality of segments, and

each of the plurality of segments is coupled to the other of the first layer or the second layer by at least one of the protrusions or knobs.

6. The gerotor apparatus of claim **1**, wherein the ceramic in the first layer has a coefficient of thermal expansion less than 2×10^{-6} m/(mK).

7. The gerotor apparatus of claim **1**, wherein the second layer is metallic.

8. A gerotor apparatus, comprising:

a housing;

an outer gerotor disposed within the housing; and

an inner gerotor disposed within the outer gerotor;

wherein:

at least one of the inner gerotor and the outer gerotor is configured to rotate with respect to the other when viewed from a cross section of the inner gerotor and the outer gerotor,

at least one of the inner gerotor and the outer gerotor has two layers, and

at least one of the two layers is segmented into a plurality of segments when viewed from the cross section.

9. The gerotor apparatus of claim **8**, wherein a segmented layer of the two layers is configured to allow a different thermal expansion between the segmented layer of the two layers and the other of the two layers.

10. The gerotor apparatus of claim **8**, wherein the at least one of the inner gerotor and the outer gerotor having the two layers further comprises a plurality of teeth at least partially formed from each of the two layers.

11. The gerotor apparatus of claim **8**, wherein at least one of the inner gerotor and the outer gerotor further comprises protrusions or knobs coupling the two layers.

12. The gerotor apparatus of claim **8**, wherein

a portion of one of the two layers is configured to receive a portion of the other of the two layers to couple the layers.

13. The gerotor apparatus of claim **8**, wherein at least one of the two layers has a coefficient of thermal expansion less than 2×10^{-6} m/(mK).

14. The gerotor apparatus of claim **8**, wherein at least one of the two layers is metallic.

15. A gerotor apparatus, comprising:
 a housing;
 an outer gerotor disposed within the housing; and
 an inner gerotor disposed within the outer gerotor;
 wherein: 5
 at least one of the inner gerotor and the outer gerotor has
 two layers,
 at least one of the two layers is segmented into a plurality
 of segments, and
 each of the plurality of segments in a segmented layer of 10
 the two layers is coupled to the other of the two layers
 by at least one of a knob or a protrusion.

16. The gerotor apparatus of claim 15, wherein one of the
 two layers is ceramic and another of the two layers is non-
 ceramic. 15

17. The gerotor apparatus of claim 16, wherein the non-
 ceramic layer is metallic.

18. The gerotor apparatus of claim 15, wherein both of the
 inner gerotor and the outer gerotor have two layers.

19. The gerotor apparatus of claim 15, wherein the at least 20
 one of the inner gerotor and the outer gerotor having the two
 layers further comprises a plurality of teeth at least partially
 formed from each of the two layers.

20. The gerotor apparatus of claim 15, wherein the seg- 25
 mented layer of the two layers is configured to allow a differ-
 ent thermal expansion between the segmented layer of the
 two layers and the other of the two layers.

* * * * *