

**TEXAS LOANSTAR  
MONITORING AND ANALYSIS PROGRAM**

**REPORT TO**

**THE MONITORING ADVISORY  
AND REVIEW COMMITTEE**

**VOLUME ONE**


**Presentations**

**August 19-20, 1991  
Austin, Texas**

**Presentations by:**

**W. D. Turner  
David E. Claridge  
Aamer Athar  
Kelly Kissock  
Agami Reddy  
David Ruch  
Jeff Haberl  
Srinivas Katipamula**

**Dean Willis  
Robert López  
Robert Sparks  
John Bryant  
Dennis O'Neal  
Warren M. Heffington  
Merwin Brown**



**ENERGY SYSTEMS  
LABORATORY**

Department of Mechanical Engineering  
Texas Engineering Experiment Station  
Texas A&M University

College Station, Texas 77843

**TEXAS LOANSTAR  
MONITORING AND ANALYSIS PROGRAM**

**REPORT TO**

**THE MONITORING ADVISORY  
AND REVIEW COMMITTEE**

**VOLUME ONE**

**Presentations**

**August 19-20, 1991  
Austin, Texas**

**Presentations by:**

**W. D. Turner  
David E. Claridge  
Aamer Athar  
Kelly Kissock  
Agami Reddy  
David Ruch  
Jeff Haberl  
Srinivas Katipamula**

**Dean Willis  
Robert López  
Robert Sparks  
John Bryant  
Dennis O'Neal  
Warren M. Heffington  
Merwin Brown**

**Energy Systems Laboratory  
Department of Mechanical Engineering  
Texas A&M University  
College Station, Texas**

# VOLUME 1 - PRESENTATIONS

## Table of Contents

### **Agenda**

#### **LoanSTAR MAP Overview - W. D. Turner**

#### **Task 5 - Analysis and Reporting**

Overview Analysis and Reporting - David Claridge

Reporting the Data - David Claridge

Agency Contact - Aamer Athar

Preliminary Savings Analysis - Kelly Kissock

Uncertainty in Savings Analysis - Agami Reddy

NAC for Linear and Change-Point Models - David Ruch

DOE-2 Calibration Procedures - Jeff Haberl

Simplified Systems Modeling for Savings Analysis - Srinivas Katipamula

Summary of Analysis Developments and Results - David Claridge

#### **Task 4 - Communications Testbench and Technical Support**

Systems Support - Dean Willis

Data Base - Robert López

Programming and Test Bench - Robert Sparks

Communications and Data Summary - Jeff Haberl

#### **Task 2 - Metering Installation**

Summary of Installation Progress - John Bryant

Building Monitoring--Lessons Learned - Dennis O'Neal

#### **Task 3 - Calibration Laboratory**

Calibration Laboratory - W. D. Turner

Flowmeter Calibration - Jeff Haberl

#### **Task 1 - Desktop Audit Review and Training**

Audit Progress and Reviews - Warren M. Heffington

#### **MARC Member Report**

Pacific Gas and Electric--Act<sup>2</sup> Program - Merwin Brown

## **Preface**

The LoanSTAR program has now completed its second prototype year. This report is Volume I of a two volume set that documents the progress since the January 1991 MARC meeting.

This first volume contains photocopies of the material presented at the Monitoring and Advisory Review Committee (MARC) meeting held in Austin, Texas, on August 19-20, 1991.

The second volume contains papers and supporting material prepared by the LoanSTAR staff and faculty at Texas A&M University, as well as other supporting material.

This material is intended to be for discussion purposes only.

## Final Agenda

### MARC Meeting - August 19-20, 1991

Monday, August 19, 1991

#### REVIEW OF MONITORING AND ANALYSIS PROGRESS

- 8:00 - 8:30 a.m.**      **Continental Breakfast**
- 8:30 - 8:40 a.m.      Welcome - Dan Turner
- 8:40 - 8:55 a.m.      Governor's Energy Office Overview - Carol Tombari
- 8:55 - 9:05 a.m.      Discussion of LoanSTAR Program - Mel Roberts
- 9:05 - 9:30 a.m.      LoanSTAR MAP Overview - Dan Turner
- 9:30 - 10:20 a.m.      Task 5 - Overview Analysis and Reporting - David Claridge  
--Reporting the Data - David Claridge  
--Agency Contact - Aamer Athar
- 10:20 - 10:35 a.m.**      **Coffee Break**
- 10:35 - 12:15 p.m.      Task 5 - Continued  
--Preliminary Savings Analysis - Kelly Kissock  
--Uncertainty in Savings Analysis - Agami Reddy  
--NAC for Linear and Change-Point Models - David Ruch  
--DOE-2 Calibration Procedures - Jeff Haberl  
--Simplified Systems Modeling for Savings Analysis - Srinivas  
    Katipamula  
--Summary of Analysis Developments and Results - David  
    Claridge
- 12:15 - 1:15 p.m.**      **Lunch**
- 1:15 - 1:35 p.m.      HC PRISM - Cathy Reynolds, Princeton University
- 1:35 - 2:35 p.m.      Task 4 and Tech Support  
--Systems Support - Dean Willis  
--Data Base - Robert Lopez  
--Programming and Test Bench - Robert Sparks  
--Communications and Data Summary - Jeff Haberl
- 2:35 - 2:55 p.m.      Task 2 - Summary of Installation Progress - John Bryant

- 2:55 - 3:10 p.m. Coffee Break**
- 3:10 - 4:05 p.m. Task 2 - Continued  
--Building Monitoring - Lessons Learned - Dennis O'Neal
- 4:05 - 4:50 p.m. Task 3 - Calibration Laboratory - W. D. Turner  
--Flowmeter Calibration - Jeff Haberl
- 4:50 - 5:35 p.m. Task 1 - Audit Progress and Reviews - Warren Heffington
- 6:30 p.m. Dinner - Iron Works Barbeque**

**Tuesday, August 20, 1991**

- 7:30 - 8:00 a.m. Continental Breakfast**
- 8:00 - 8:05 a.m. Opening Remarks - Dan Turner
- 8:05 - 8:30 a.m. U.S. Department of Energy - DOE/HUD Initiative - Ernie Freeman
- 8:30 - 8:55 a.m. Electric Power Research Institute - EPRI Programs - Larry Carmichael
- 8:55 - 9:35 a.m. Pacific Gas and Electric - ACT<sup>2</sup> Program - Merwin Brown
- 10:00 - 10:15 a.m. Coffee Break**
- 10:15 - 10:40 a.m. Battelle - Dipstick Audits - Todd Taylor
- 10:40 - 11:05 a.m. ORNL - Monitoring Programs - Bill Mixon
- 11:05 - 11:30 a.m. SERI - Update on SERI Monitoring - Jay Burch
- 11:30 - 11:55 a.m. MIT - Air Handler Measurements and Office Equipment - Les Norford
- 11:55 - 12:20 p.m. UT-Austin - DOE-2 Calibration/Capitol Extension Analysis - Bruce Hunn
- 12:20 - 1:15 p.m. Lunch**

## **FUTURE PLANS**

- |                  |   |
|------------------|---|
| 1:15 - 1:35 p.m. | Task 1 - Desk Top Audit Review  |
| 1:35 - 1:55 p.m. | Task 2 - Metering Equipment Installation and Subcontractor                                    |
| 1:55 - 2:20 p.m. | Task 3 - Calibration Laboratory   |
| 2:20 - 2:40 p.m. | Task 4 - Test Bench and Communications Testing  |
| 2:40 - 3:05 p.m. | Task 5 - Monitoring Analysis  |
| 3:05 - 3:30 p.m. | Task 6 - Improved Energy Audit Process  |
| 3:30 p.m.        | <b>Adjourn</b>  |
| 4:00 p.m.        | (Optional) Tour of Perry Casteneda Library LoanSTAR Installation at UT-Austin - J. Von Wolske |

**GOVERNOR'S  
ENERGY OFFICE (GEO)**

**MARC**  
GEO      DOE  
LBL      PNL  
MIT      EPRI  
UT      HL&P  
ORNL     Princeton  
SERI

**ENERGY SYSTEMS LAB**  
Monitoring & Analysis  
W.D.Turner, Program Manager

**TASK 1**  
Desktop Audit,  
Review, & Training  
Warren Heffington PI

**TASK 3**  
Calibration  
Laboratory  
Dan Turner PI

**TECH.SUPPORT**  
Hardware: D.Willis  
Software: R.Sparks  
Database: R.Lopez

**TASK 5**  
Analysis &  
Planning  
David Claridge PI

**TASK 2**  
Metering  
Installation  
John Bryant Co-PI  
Dennis O'Neal Co-PI

**TASK 4**  
Communications  
Testbench  
Jeff Haberl PI

**MARC**  
Subcontracts  
MIT      UT  
Princeton  
LBL



## **TASK 5**

### **ANALYSIS AND REPORTING**

### **PROGRESS PRESENTATION**

**David E. Claridge, P.I.**

**Jeff S. Haberl**

**Srinivas Katipamula**

**Dennis L. O'Neal**

**Agami Reddy\***

**Mohsen Farzad**

**Robert Sparks**

**Robert Lopez**

**Aamer Athar**

**David Ruch\***

**Kelly Kissock\***

**Jianxun Wu\***

**Mustafa Abbas**

**Naveen Balakrishnan\***

**Doug Bronson**

**Amitava Dhar\***

**Jinrong Wang**

**\*Funded/Partially Funded by ERAP**

**August 1991**

# OUTLINE

- \* **Task Responsibilities**
- \* **Overview of Buildings, Retrofits and Data**
- \* **Building Indices**
- \* **Results**
  - **Monthly Reports**
  - **Agency Contact/O&Ms**
  - **Savings Measured**
- \* **Analysis Approach and Development**
  - **Uncertainty in Savings**
  - **Normalized Annual Consumption Measures**
  - **DOE-2 Calibration**
  - **Calibrated Symplified Systems Models**
- \* **Summary and Conclusions**

## **TASK RESPONSIBILITIES:**

- Coordinate preparation of monitoring and analysis plan**
- Select and develop analysis techniques**
- Develop analysis software**
- Analyze collected Data**

## **TO:**


- 1. Determine retrofit savings**
- 2. Identify O&M opportunities**
- 3. Determine individual measure savings when feasible**
- 4. Initiate end-use database**

## LoanSTAR Buildings with Monthly Reporting - 7/91


	<u>Gross Area (ft<sup>2</sup>)</u>	<u>Building Use</u>
<b>Texas A&amp;M University</b>		
Zachry Engineering Center	324,400	Class/Lab/Office
<b>University of Texas</b>		
Education Building	251,161	Class/Office
University Teaching Center	152,690	Class
P. C. Library	483,895	Library
Garrison Building	54,069	Class/Office/Auditorium
Gearing Building	61,041	Class/Office/Lab
Waggener Hall	57,598	Class/Office/Lab
Welch Building	439,540	Class/Office/Lab
Burdine Building	103,441	Class/Office/Auditorium
Nursing Building	99,815	Class/Lecture/Lounge
Winship Building	109,064	Class/Office/Theatre
R. A. Steindam Building	56,849	Class/Office/Lab
Painter Building	128,409	Class/Office/Lab
W. C. Hogg Building	<u>48,905</u>	Class/Office/Auditorium
	2,046,477	
<b>University of Texas at Arlington</b>		
University Hall	123,450	Class/Office/Lecture
Business Building	149,000	Class/Lecture
Fine Arts Building	<u>223,000</u>	Class/Office/Theatre
	495,450	
<b>Texas Capitol Complex</b>		
J. H. Reagan	169,746	Office
J. E. Rudder	80,000	Office/Computer
Insurance Building	102,000	Office
Insurance Annex	62,000	Office
Archives	120,000	Library/Office
W. B. Travis	491,000	Office
L. B. Johnson	308,080	Office
Winters	<u>503,000</u>	Office/Computer
	1,835,826	
<b>UT Health Science Center - Houston</b>		
School of Public Health	233,738	Lab/Class/Office
<b>Texas Department of Health</b>	484,019	Office/Lab
<b>UT Health Science Center - San Antonio</b>		
Dental School	606,097	Class/Office/Lab
Medical School	<u>284,000</u>	Class/Office/Lab
	890,097	
<b>TOTAL - 6,310,007</b>		

## Monitored/Reported Buildings as of 7/91


Class/Office/Theatre(8.5%)




## Summary of ECRMs for Buildings Being Monitored




Whole-Building Electric




Whole-Building Chilled Water



Whole-Building Hot Water




# Whole-Building Electric (Jan-Jun, 1991)






# Whole-Bldg Chilled Water (Jan-Jun, 1991)



# Whole-Bldg Hot Water (Jan-Jun, 1991)




Codes	3-Letter Code	Building's Name	Gross Area (sq. ft)	Agency	Location
a	HOG	W.C.HOGG	48,905	U.T.Austin	Austin
b	GAR	GARRISON	54,069	U.T.Austin	Austin
c	RAS	R.A.STEINDAM	56,849	U.T.Austin	Austin
d	WAG	WAGGENER	57,598	U.T.Austin	Austin
e	GEA	GEARING	61,041	U.T.Austin	Austin
f	JER	J.E.RUDDER	80,000	SP&GSC	Austin
g	NUR	NURSING	99,815	U.T.Austin	Austin
h	INS	INSURANCE	102,000	SP&GSC	Austin
i	BUR	BURDINE	103,441	U.T.Austin	Austin
j	WIN	WINSHIP	109,064	U.T.Austin	Austin
k	ARC	ARCHIVES	120,000	SP&GSC	Austin
l	UHA	UNIVERSITY HALL	123,450	U.T.Arlington	Arlington
m	PAI	PAINTER HALL	128,409	U.T.Austin	Austin
n	BUS	BUSINESS	149,900	U.T.Arlington	Arlington
o	UTC	UNIV TEACHING CENTER	152,690	U.T.Austin	Austin
p	JHR	J.H.REAGAN	169,746	SP&GSC	Austin
q	FA	FINE ARTS	223,000	U.T.Arlington	Arlington
r	EDU	EDUCATION	251,161	U.T.Austin	Austin
s	LBJ	L.B.JOHNSON	308,080	SP&GSC	Austin
t	ZAC	ZACHRY ENGG CENTER	324,400	Texas A&M	College Station
u	WEL	WELCH HALL	439,540	U.T.Austin	Austin
v	PCL	P.CASTANEDA LIBRARY	483,895	U.T.Austin	Austin
w	WBT	W.B.TRAVIS	491,000	SP&GSC	Austin
— ▲	INS X	INSURANCE ANNEX	62,000	SP&GSC	Austin

# OUTLINE


- \* **Task Responsibilities**
- \* **Overview of Buildings, Retrofits and Data**
- \* **Building Indices**
- \* **Results**
  - **Monthly Reports**
  - **Agency Contact/O&Ms**
  - **Savings Measured**
- \* **Analysis Approach and Development**
  - **Uncertainty in Savings**
  - **Normalized Annual Consumption Measures**
  - **DOE-2 Calibration**
  - **Calibrated Simplified Systems Models**
- \* **Summary and Conclusions**

# Excerpts from Typical Monthly Energy Consumption Report

Zachry Engineering Center  
Texas A&M University  
February 1991  
Page 4



Whole-Building Electric




Monthly Energy Consumption Report ©  
Volume 13


Sam Brown's Energy 880  
LoadSTAR Modeling & Analysis Program

Energy Systems Lab  
Texas A&M University


Whole-Building Electric



Whole-Building Chilled Water




Whole-Building Hot Water




# Method for Determining Energy Savings for Non-Weather Dependent Loads


## Pre-retrofit Lights and Equipment for Education Building for Typical Week



## Post-retrofit Lights and Equipment for Education Building for Typical Week




## Savings Post-retrofit Lights and Equipment for Education Building - Typical Week




# Method for Determining Energy Savings for Weather Dependent Loads

When Pre-Retrofit Measured Data are Available




When Post-Retrofit Measured Data are Available






Motor Control Center electricity use which is almost exclusively air handler use is shown for November 14, 1990 - April 30, 1991. The horizontal dotted lines shows average pre-retrofit MCC use.



**Chilled water consumption plotted as a function of average daily ambient temperature. The model for pre-retrofit consumption is shown with triangles while measured consumption during construction and during post-retrofit consumption for March-April, 1991 are shown as squares and circles respectively.**



## **OUTLINE**

- \* **Task Responsibilities**
- \* **Overview of Buildings, Retrofits and Data**
- \* **Building Indices**
- \* **Results**
  - **Monthly Reports**
  - **Agency Contact/O&Ms**
  - **Savings Measured**
- \* **Analysis Approach and Development**
  - **Uncertainty in Savings**
  - **Normalized Annual Consumption Measures**
  - **DOE-2 Calibration**
  - **Calibrated Simplified Systems Models**
- \* **Summary and Conclusions**

**MONITORED COMMERCIAL BUILDING  
ENERGY DATA: REPORTING THE RESULTS**

**David Claridge, Jeff Haberl, Robert Sparks, Rob Lopez,  
Kelly Kissock, Aamer Athar**


**August 1991**

## **Three Major Reporting Forms Used**













- **Weekly Inspection Plots**
- **Computer Files with Browsing Software**
- **Monthly Energy Consumption Reports**

**WEEKLY INSPECTION PLOTS**




Inspection plot summary sheet showing data for the UT-Austin  
Education Building for the week May 7-13, 1991.



Inspection plots showing individual channels for the UT-Austin Education Building for the week May 7-13, 1991.




Texas A&M University  
Energy Systems Laboratory  
INTERNAL DISTRIBUTION ONLY






**COMPUTER FILES WITH BROWSING  
SOFTWARE**

January - April, 1991 chilled water consumption for the Education Building plotted as a function of ambient dry-bulb temperature using data exploration software.



January - April chilled water consumption for the Education Building plotted as a function of air handler electricity use by the data exploration software.



**MONTHLY ENERGY CONSUMPTION  
REPORTS**

**Zachry Engineering Center**  
Texas A&M University  
324,400 square feet

Site Contact

Charles Darnell, Jr.  
Physical Plant Administration  
Texas A&M University  
(409)-845-5318  
Gene Stewart  
(409)-845-5511

LoanSTAR Contact

Mohsen Farsad or Aamer Athar  
053 WERC  
Texas A&M University  
College Station, TX 77842-3123  
(409)-845-9213

**Summary of Energy Consumption**

	Measured Use	% hours reported	Unit Cost	Estimated Cost
Electricity	702476 kWh	99.9	-	-
Peak 60 Minute Demand	1312 kW	99.9	-	-
Chilled Water	1590.7 MMBtu	99.9	-	-
Hot Water	439.4 MMBtu	99.9	-	-

Peak 60 minute demand was recorded at 1500 Wednesday 4/3/91.  
There were 720 hours in this month.

**Measured Monthly Savings**



Actual	Predicted
\$26,966	\$24,915

**Comments**

★ Total savings to date including those measured during construction are \$83,694. Savings are calculated with the 1988 costs used for loan payback estimates. Savings estimates are preliminary and subject to adjustment.



★ There appears to be a change in system operation near the middle of the month.

Zachry Engineering Center - Texas A&M University - April 1991





Data points for the current month are shown as letters.  
 Monday through Sunday are represented as M,T,W,H,F,S,U.

Monthly Energy Consumption Report<sup>©</sup>





Zachry Engineering Center - Texas A&M University - June 1991




Monthly Energy Consumption Report<sup>©</sup>






Zachry Engineering Center - Texas A&M University - June 1991

### Whole-Building Electric



### Whole-Building Electric



Sundays are marked with an "S"

Zachry Engineering Center - Texas A&M University - June 1991

**TEXAS A&M UNIVERSITY**

**Zachry Engineering Center**

**Building Envelope:**

- 324,400 sq.ft
- 3-1/2 floors and a ground floor level, erected 1973, classes, offices, labs, computer facility, and clean rooms for Solid State Electronics
- walls: cement block
- windows: 22% of total wall area  
single pane with built-in-place vertical blinds
- roof: flat

**Building Schedule:**

- classrooms and labs: 7:30 am to 6:30 pm weekdays
- offices: 7:30 am to 5:30 pm weekdays
- computer facility: 24 hrs/day

**Building HVAC:**

- 12 variable volume dual duct AHUs (12-40hp)
- 3 constant volume multizone AHU (1-1 hp, 1-7hp, 1-10hp)
- 4 constant volume single zone AHU (4-3hp)
- 10 fan coils (10-0.5 hp)
- 2 constant volume chilled water pump (2-30hp)
- 2 constant hot water pump (2-20hp)
- 7 misc. pumps (total of 5.8hp)
- 50 exhaust fans (50-0.5hp)

**HVAC Schedule:**

- 24 hrs/day

**Lighting:**

- fluorescent

**Proposed Retrofits:**

- use of parabolic light fixtures
- control modifications to the dual duct system
- variable volume dual duct system

**Other Information:**

- EMCS system to control HVAC is installed

**Date of Retrofits:**

- estimate date of completion for VAV and control modifications to the dual duct system: 3/30/91

Zachry Engineering Center - Texas A&M University - June 1991

## **CONCLUSIONS**

- 1. Inspection Plots used for data quality control and diagnosis of operating changes and problems.**
- 2. Data Exploration Software used to examine system performance and analyze consumption data.**
- 3. Monthly Energy Consumption Reports provide hard copy tabular and graphical feedback on monthly, daily and hourly performance of building systems.**

**All three forms have been found useful by:**

- Building operators**
- Building administrators**
- Facility engineers**
- Design engineers**
- Monitoring and analysis engineers**
- Project managers**

**THE TEXAS LOANSTAR MONITORING  
AND ANALYSIS PROGRAM**

**CONTACTING & DESCRIBING SITES**

**A PRESENTATION**

**BY**

**AAMER ATHAR**

**MUSTAFA ABBAS**

**NAVEEN BALAKRISHNAN**

**ENERGY SYSTEMS LAB  
TEXAS A&M UNIVERSITY**

# **AGENCY CONTACT & SITE DESCRIPTION GROUP**

## **OBJECTIVES:**

### **AGENCY CONTACT**

**Provides 2-Way Communication Channel  
for:**

- **Follow-up on Monthly Reports**
- **O&M Identification & Verification**
- **Determining Status of Retrofits**
- **Setting up Meetings & Scheduling  
Visits**
- **Verification of Monitored Data**

### **SITE INFORMATION**

- **Collected in the form of *Site  
Description Note Books***

## **RESPONSIBILITIES:**

- **Prepare Site Description Note Books**
- Identify O&M Opportunities
- Generate Comments for Monthly Energy Consumption Reports (MECRs)
- Follow-Up on MECRs. Gather Answers to all the Comments
- Update Information on Status of Retrofits
- Special Data Problems
- Develop Building Indices (W/sq.ft, Btu/hr.sq.ft, etc...)
- Develop Database for Recommended ECRMs

## **SITE DESCRIPTION NOTE-BOOKS:**


- 1) Photographs of the Site**
- 2) Site Summary Form**
- 3) Site Description Form**
- 4) Data Channel List**
- 5) Monitoring Diagram**
- 6) ECRM List from Pre-MAP**
- 7) O&M Opportunities**
- 8) Estimated Savings from the Audit Report**
- 9) Modelling Characteristics**
- 10) Monthly Energy Consumption Reports (MECRs)**
- 11) Comments & Answers**
- 12) Weekly Inspection Plots**
- 13) Appendix**



## **RESPONSIBILITIES:**

- Prepare Site Description Note Books
- **Identify O&M Opportunities**
- Generate Comments for Monthly Energy Consumption Reports (MECRs)
- Follow-Up on MECRs. Gather Answers to all the Comments
- Update Information on Status of Retrofits
- Special Data Problems
- Develop Building Indices (W/sq.ft, Btu/hr.sq.ft, etc...)
- Develop Database for Recommended ECRMs

**Whole - Building Steam & CHW**  
Perry Casteneda Library




## **CLOSURE OF REHEAT VALVES AT PCL:**

- **Questions were Raised about High Steam Consumption at PCL (May 1991)**
- **1<sup>st</sup> Site Visit to Verify Our Instrumentation (June 1991)**
- **Discussion of Problem with Facility Engineer & Building Operator (June 1991)**
- **Building Operator & Facility Engineer Suggested Closure of Reheat Valves (June 1991)**
- **Distribution of More Detailed Data to Facility Engineer (June 1991)**
- **Analysis of Monitored Data**
- **Partial Closure of Valves to Reheat Coils (July 3, 1991)**
- **2<sup>nd</sup> Site Visit Accompanied by Dr. Steve Jaeger & Design Engineer (July 5, 1991)**
- **Total Reheat Shut-Off (July 10, 1991)**

# Whole - Building Steam & CHW

Perry Casteneda Library



## **SAVINGS DUE TO REHEAT SHUT-OFF:**

**Date:** **July 3, 1991**  
**(Reheat Shut-off)**

**Steam Savings**  $\approx$  **1 Million Btu/hr**

**Chilled Water Savings**  $\approx$  **1 Million Btu/hr**


**Cost Savings:**  $\approx$  **\$ 10.00/hr**  
**(\$7,000/month)**

## **RESPONSIBILITIES:**

- Prepare Site Description Note Books
- Identify O&M Opportunities
- **Generate Comments for Monthly Energy Consumption Reports**
- **Follow-Up on MECRs. Gather Answers to all the Comments**
- **Update Information on Status of Retrofits**
- **Special Data Problems**
- **Develop Building Indices (W/sq.ft, Btu/hr.sq.ft, etc...)**
- **Develop Database for ECRMs**


**Estimated Implementation Cost  
Buildings Monitored as of July 1991**

Estimated Implementation Cost: \$13,682,190



**Predicted Cost Savings  
Buildings Monitored as of July 1991**


Predicted Cost Savings: \$4,554,027



**PREDICTED ENERGY SAVINGS**

Buildings Monitored as of July 1991

Source Energy Savings: 1,316,814 MMBtu/yr



Btu savings calculated on the basis of source Btus (i.e. 11,600 Btu/kWh, 1,030,000 Btu/MCF, & 12,000 Btu/ton-hr)



## **ACCOMPLISHMENTS:**

- **13 Site Description Note Books Completed**
- **9 Interviews (4 Facility Administrators and 5 Building Operators)**
- **O&M Identification & Follow-Up**
  - 1) **Hot Water Pump Shut Down at Zachry Engineering Center**
  - 2) **Closure of Reheat Valves at PCL (U.T. Austin)**
- **Building Indices Prepared**
- **Regular Follow-Up/Status Update**

**Measured Retrofit Savings  
For  
Eight Texas LoanSTAR  
Buildings**

-

**Preliminary Methodology and Results**


-

**Kelly Kissock**

-


**August 19, 1991**

# ZEC Air Handler Use




# Education Building

## Pre-Retrofit Chilled Water Use




# ZEC

## Pre-Retrofit Hot Water Use




# ZEC

## Model and Pre-Retrofit Data



# ZEC

## Model and Post-Retrofit Data








Figure 2.1 Pre-retrofit chilled water use and models for eight LoanSTAR buildings.



**Energy Savings By Energy Type  
For Eight LoanSTAR Buildings**



### Cumulative Savings For Eight LoanSTAR Buildings



# **UNCERTAINTY IN SAVINGS ANALYSIS**

## **Task 5: Analysis and Planning**

**T. Agami Reddy  
Kelly Kissock**

**Energy Systems Laboratory  
Dept. of Mechanical Engineering  
Texas A&M University  
August 19, 1991**

## Total Savings Calculations

### Total Savings

$$= \sum_{j=1}^m \hat{E}_{pre,j} - \sum_{j=1}^m E_{meas,j}$$

where

$m$  = number of post-retrofit days

$E$  = daily energy consumption

- chilled water
- hot water
- electricity

$\hat{E}_{pre}$  = model determined daily energy use

$E_{meas}$  = measured post-retrofit daily energy use.

## Source of Uncertainty (Errors)

### ■ Measurement Errors $E_{pre}, E_{meas}, T$

- Approximate effect of small errors can be studied by differentiation in which the behavior of the errors is indicated by the behavior of the differentials. Thus

$$d(x + y) = dx + dy.$$

### ■ Prediction Errors

- Use of a model to predict  $\hat{E}_{pre,j}$

## Prediction Errors


Uncertainty in the sum of  $\hat{E}_{pre,j}$  values

= Uncertainties due to the following:

- Finite number of pre-retrofit days (n)
- Finite number of post-retrofit days (m)
- Auto-correlated measured  $E_{pre}$  values
- Away from mid-range of  $T_{pre}$  values

### ZACHRY-PRE-RETROFIT PERIOD

Oct. 89 - Nov.90



## Prediction Uncertainty on the Sum of $\hat{E}_{pre}$ values

$$= t(m-2, 1 - \frac{\alpha}{2}) \times RMSE \times m \times \left[ \frac{1}{n} + \frac{1}{m} + \frac{2(n-2)}{n^2}p + \frac{\sum_{j=1}^m (T_{post,j} - \bar{T}_{pre})^2}{m \times SS_T} \right]^{\frac{1}{2}}$$

where

$t(m-2, 1 - \frac{\alpha}{2})$  = 100(1 -  $\frac{\alpha}{2}$ ) percentage point of a t-distribution with (m-2) degrees of freedom

[For  $m = 60, t = 2.0$  at 95% C.L.]

$RMSE$  = Root Mean Square Error

$$= \left[ \frac{1}{n-2} \sum_{i=1}^n (E_{pre,i} - \hat{E}_{pre,i})^2 \right]^{\frac{1}{2}}$$

$p$  = auto-correlation coefficient of  $E_{pre,i}$  values

$SS_T$  = sum of squares =  $\sum_{i=1}^n (T_{pre,i} - \bar{T}_{pre})^2$

$\bar{T}_{pre}$  = mean ambient temperature during the pre-retrofit period.

### For Zachry Data:

- No. of pre-retrofit days  $n = 399$
- No. of post-retrofit days  $m = 107$
- Autocorrelation coefficient  $\rho = 0.91$
- Mean Temperature  $\bar{T}_{pre} = 68.9$  F
- RMSE (chilled water) = 10.5 MMBtu/day
- RMSE (hot water) = 11.7 MMBtu/day
  
- Prediction uncertainty on total pre-retrofit energy USE =  $t \times \text{RMSE} \times m \times 0.132$ 
  - chilled water: 2% at 95% C.L.
  - hot water: 8% at 95% C.L.
  
- [Note: On a monthly basis, uncertainty =  $t \times \text{RMSE} \times m \times 0.204$ ]
  
- Prediction uncertainty on total energy savings
  - Chilled water: 3% at 95% C.L.
  - Hot water: 16% at 95% C.L.



**NORMALIZED ANNUAL CONSUMPTION (NAC)**  
**FOR LINEAR AND CHANGE-POINT ENERGY MODELS**

**DEFINITION:** The NAC index for an energy model is the expected energy consumption in a year with average conditions.

**BACKGROUND:** The PRISM method calculates NAC with rigorous error analysis for a three parameter change-point model.

Linear and four parameter change-point energy models appear appropriate for the majority of LoanSTAR buildings.

**GOALS :**

- Develop NAC with rigorous error analysis for the linear and four parameter change-point energy models.
- Compute NAC using several models on the same buildings and assess the performance of each model.
- Study the importance of goodness-of-fit toward producing an accurate NAC estimate for daily data.

**NAC for the two-parameter linear model:**

$$\mathbf{E} = \mathbf{a} + \mathbf{b} * \mathbf{T}$$

For an average year of temperature data {  $T_j$  },

$$\text{NAC} = \sum \hat{E}_j = \sum (a + b * T_j) = 365 + b * \sum T_j$$


so

$$\text{NAC} = 365(a + b * T_{\text{LAV}})$$

where  $T_{\text{LAV}}$  is the (long-term) average temperature for the region.

Using the properties of variance and covariance,

$$\text{s.e. (NAC)} = 365 * \sqrt{[\text{var}(a) + 2 * T_{\text{LAV}} * \text{cov}(a, b) + T_{\text{LAV}}^2 * \text{var}(b)]}$$



**Linear Heating Model Results:**


$$H = 129.3 - 3.4T \quad (\text{GJ/day}) \quad \text{NAC} = 21939$$

(GJ)

Parameter	Standard error	c.v. [parameter]
a	2.4	1.85%
b	0.12	3.62%
NAC	356	1.62%

**Four Parameter Change-Point Model:**

$$E = a + b_2 * (T - \tau)^+ - b_1 * (\tau - T)^+$$



$$\text{NAC} = 365 * a + b_2 * \text{DD}_+(\tau) - b_1 * \text{DD}_-(\tau)$$

where  $\text{DD}_-(\tau)$  is the average number of degree-days below the reference temperature  $t$  in the average year, and  $\text{DD}_+(\tau)$  is the average number above  $\tau$ .


A likelihood-based standard error and confidence intervals for NAC are calculated for this model.

Monte Carlo results for the reliability of NAC error diagnostics.

<b>sample size</b>	<b>Theoretical confidence level</b>		
	<b>68%</b>	<b>95%</b>	<b>99%</b>
365	68	95	99.5
120	68	94.5	99
12	66	94	98

The table entries denote the percentage of the estimated confidence intervals containing true value of NAC.


Conclusion: The error diagnostics of NAC are very accurate for data sets with "nice" (i.i.d.) errors.



Pre-retrofit Winship Data with four parameter (FP) and PRISM CO models. About half the days in normal year fall above 21 C.

	Linear	PRISM CO	FP
R-Square	0.80	0.57	0.85
NAC	19133	18690	20639
se (NAC)	174	261	344
CV (NAC)	0.9%	1.4%	1.7%

The PRISM CO NAC estimate is 9.2% less than the FP NAC estimate.



Welch Data with FP and PRISM HO models.

	Linear	PRISM HO	FP
R-Square	0.73	0.62	0.92
NAC	24565	27733	26402
se(NAC)	511	590	305
CV(NAC)	2.1%	2.1%	1.2%

The PRISM HO NAC estimate is 5% more than the FP model's NAC estimate.

**Texas LoanSTAR  
Monitoring and Analysis Program**

**DOE-2 Calibration Procedures**

**Progress Report**

Jeff S. Haberl  
Doug Bronson  
Sharon Hinchey  
Dennis O'Neal  
David Claridge

August 1991



# **Why Calibrate a DOE-2 Simulation?**

- > Energy Audit Firms occasionally use DOE-2 or ASEAM to calculate energy savings of retrofits.
- > New buildings are often simulated with DOE-2 or ASEAM.
- > A calibrated DOE-2 run might be used to calculate energy savings and/or for commissioning.

# Pros and Cons of Calibrated Models:

## Pros:

- > DOE-2, BLAST, ASEAM, are well known to engineering community.
- > Calibrated models could offer very accurate savings calculations.
- > Calibrated models could be used to synthesize missing data, perform what-ifs, etc.

## Cons:

- > Too many "knobs". Which "knob" to turn?
- > Simulation programs are tree killers. How does one "view" the goodness of fit?
- > TMY, TRY, WYEC weather tapes not representative of "real" weather data. What is the impact of using real weather?

## **Progress with Calibrated Models:**


### **-> Development of calibration toolkits:**

Non-weather dependent calibration toolkit


Weather effect (Tdb, RH) visualization toolkit

### **-> Development of calibrated simplified models (SK):**




# Non-weather dependent toolkit: (General Flow Chart)







# Non-weather dependent toolkit: (Software Routines)







# Non-weather dependent toolkit: (Example: Daytype Profiles)



# Non-weather dependent toolkit: (Example: 3-D DOE-2 Daytypes)







# Non-weather dependent toolkit: (Example: ELF/OLF Daytypes)











# Non-weather dependent toolkit: (Example: 3-D K-H Daytypes)









## Non-weather dependent toolkit: (Summary Chart)

	Sep.1989	Oct.1989	Nov.1989	Dec.1989	Jan.1990	Feb.1990	Total
All units are in MWh							
<b>Monitored</b>	847.6	879.5	848.4	796.5	792.1	749.8	4,914.0
<b>DOE-2</b>	611.9	636.5	612.6	614.0	624.6	555.7	3655.3
<b>(% diff.)</b>	-27.8%	-27.6%	-27.8%	-22.5%	-21.2%	-25.9%	-25.6%
<b>ELF/OL F</b>	847.0	878.8	848.0	795.9	791.7	749.1	4,910.7
<b>(% diff.)</b>	-0.1%	-0.1%	-0.03%	-0.1%	-0.05%	-0.1%	-0.1%
<b>Auditor's</b>	795.7	823.8	792.3	801.0	789.5	744.4	4,746.6
<b>(% diff.)</b>	-6.1%	-6.3%	-6.6%	0.6%	-0.3%	-0.7%	-3.4%
<b>Full Data</b>	874.0	876.4	832.0	815.4	823.4	725.0	4,946.3
<b>(% diff.)</b>	3.1%	-0.4%	-1.9%	2.4%	4.0%	-3.3%	0.7%







# Weather Impact Visualization Toolkit: (Measured data)





# Weather Impact Visualization Toolkit: (DOE-2 TMY Simulated)



# Weather Impact Visualization Toolkit: (DOE-2 Packed TRY)



# Weather Impact Visualization Toolkit: (Summary Chart)



# **Calibrated DOE-2 Simulations:**

## **Summary:**

**-> Specific Toolkits developed & tested.**

Non-weather dependent

Weather effect visualization

**-> Future Work.**

Weather dependent toolkit.

**Presentation  
of  
Use of Simplified Systems Model  
to Measure Retrofit Energy Savings**

**to  
Monitoring and Analysis Review Committee**

**Srinivas Katipamula  
David E. Claridge**

**Energy Systems Laboratory  
Dept. of Mechanical Engineering  
Texas A&M University  
August 19, 1991**



## OUTLINE OF THE PRESENTATION

- INTRODUCTION
- OBJECTIVES OF THIS STUDY
- VAV MODEL DEVELOPMENT
- DESCRIPTION OF MONITORED BUILDING AND SYSTEMS
- CALIBRATION OF VAV MODEL
- DDCV SYSTEM SIMULATION
- COMPARISON OF ENERGY SAVINGS
- QUESTIONS !

## INTRODUCTION

- Typically energy savings are estimated
  - Engineering judgement
  - Utility bill comparison
  - Uncalibrated hourly simulation
  - Regression models with monitored data
  
- Several buildings with DDCV systems are being retrofitted with energy efficient VAV systems as part of the LoanSTAR program
  
- Some buildings in the LoanSTAR program do not have pre-retrofit data

## OBJECTIVE


- Develop calibrated simplified systems models to determine energy savings from HVAC retrofits

### How Did We Achieve It ?


- Adapt VAV and DDCV models based on TC4.7 SEAP methodology
- Calibrate VAV model with post-retrofit data
- Use calibrated loads from VAV model with a DDCV model and measured energy use to determine savings

MAR/C '91: August 19, 1991

### When Pre-Retrofit Measured Data are Available




### When Pre-Retrofit Measured Data Not are Available




Task 5 SK/DEC

5

### When Post-Retrofit Measured Data are Available




### When Post-Retrofit Measured Data are Available



## VAV MODEL

- EC is divided into two zones
- Isolated core zone
- Envelope loads linear with temperature
- Internal loads for both zones are estimated based on hour of day and day of week
- O/A reset on hot deck and fixed temperature on cold deck (55 F)
- Measured outdoor dry-bulb temperature, and relative humidity and decimal date used in model



**Schematic of Zones and the Dual-Duct System**

## **DESCRIPTION OF MONITORED BUILDING**

- **Engineering Center (EC) is 324,000 sf gross**
- **EC is heavy 6-inch concrete floors and insulated concrete walls**
- **Office, class rooms, laboratories, and computer rooms**
- **Open 24 hours per day, 365 days per year**
- **Consumptions shows marked WD/WE differences**
- **EC has 12 identical dual-duct systems**


## VAV MODEL CALIBRATION

- **Variables used in calibration**
  - CLFs
  - Zone temperature
  - Outdoor air intake
  - Measured hot and cold deck temperatures
  
- **Matched typical hourly simulated profile with measured hourly profile by changing CLFs**
  
- **Minimized RMSE by changing zone temperature and outdoor air intake**

MARC '91: August 19, 1991

Task 5 SK/DEC

9




Comparison of Simulated, and Measured Cooling Load and Residuals for a Typical 24 Hour Period(July 2, 1991)



MARC '91: August 19, 1991

Task 5 SK/DEC

10




Simulated Cooling Load and Residuals vs Outdoor Dry-Bulb Temperature (June 21 - July 11, 1991)

MARC '91: August 19, 1991

Task 5 SK/DEC

11



Comparison of Simulated Daily and Measured Daily Cooling Load and Residuals Without Air-Handler Shut Down Days (June 21 - July 11, 1991)

## COMPARISON OF ENERGY SAVING FOR THREE WEEK PERIOD

### ■ Savings from calibrated model

$$* CW_{DDCV,sim} - CW_{VAV,sim} = 598 \text{ MMBtu}$$

$$* HW_{DDCV,sim} - HW_{VAV,sim} = 56 \text{ MMBtu}$$

### ■ Measured savings

$$* CW_{DDCV,reg} - CW_{VAV,mes} = 905 \text{ MMBtu}$$

$$* HW_{DDCV,reg} - HW_{VAV,mes} = 270 \text{ MMBtu}$$

### ■ Savings discrepancy due to pre-retrofit control problem



**Methodology is promising for use with  
buildings lacking pre-retrofit data**

# **TASK 5 SUMMARY**

**Presentation to MARC Meeting**

**by**

**David E. Claridge**

**August 19, 1991**

# **ANALYSIS AND REPORTING ACCOMPLISHMENTS**

## **Results**

- **Reports**
- **Agency Contact/O&Ms**
- **Measured Savings**

## **Analysis Improvement/Development**

- **Uncertainty in Savings**
- **Normalized Annual Consumption Measures**
- **DOE-2 Calibration**
- **Calibrated Simplified Systems Models**

## **Future Directions**

- **Reports**
- **Agency Contact/O&Ms**
- **Measured Savings**
- **Data Base**
- **Analysis Development**

## **REPORTING**

- **Monthly Energy Consumption Reports to 29 Sites at 7 Locations**
- **Voyager Software at 5 Locations**
- **Inspection Plots Distributed on a Request Basis**

## **AGENCY CONTACT SUMMARY**

- **O&Ms Identified Jointly with Facilities Personnel & Implemented**
  - **Closure of Reheat Valves at PCL (U.T. Austin)**
  - **Hot Water Pump Shut Down at Zachry Engineering Center**
  - **Annual Savings Approach \$100,000**
- **13 Site Description Note Books Completed**
- **9 Interviews/27 Buildings**
- **Building Indices Prepared**
- **Follow-Up Implemented**





# **ANALYSIS IMPROVEMENT/DEVELOPMENT**

## **Uncertainty in Savings**

- **Zachry Uncertainty Determined**
- **General Approach Being Defined**

## **Normalized Annual Consumption Measures**

- **NAC Developed for Linear, Multivariate and 4-Parameter Models**
- **Error Diagnostics Developed for Linear, Multivariate and 4-Parameter NACs**
- **Normalized Systematic Residuals Index Defined**

## **DOE-2 Calibration**

- **Procedure Developed for Calibration to Non-Weather Dependent Loads**
- **Procedure Developed for Using Measured Weather Data in Simulations**

## **Calibrated Simplified Systems Models**

- **Procedure Developed and Applied to Zachry Data**

# **FUTURE DIRECTIONS**

## **Reporting**

- **Improve Inspection Plots and Add Sites**
- **Send Voyager Files**
- **Improve Monthly Energy Reports and Add Sites**

## **Future Directions - Agency Contacts/O&Ms**

- **Add engineer**
- **Review all site data for O&Ms**
- **Provide Timely Feedback/Follow-up**
- **Develop Efficient Methodology/Procedures**

## **Future Directions - Measured Savings**

- **Complete Savings Measurement for Current Buildings**
- **Determine Savings for Additional Buildings**
- **Update Utility Cost Basis**
- **Energy End-Use Data Base**
- **Individual-Measure Savings Data Base**

# **Future Directions - Analysis Development**

## **Uncertainty Analysis**

- Amount of Post-Retrofit Data
- Amount of Pre-Retrofit Data
- Range of Predictors in Pre-Retrofit and Post-Retrofit Data

## **Model Error Diagnostics**

## **Model Development**

- PCA
- Hourly Methods
- Improved Predictors


## **DOE-2 Calibration**

## **Calibrated Systems Models**

- Test and Refine Methodology

## **Diagnostic Capabilities**

# LoanSTAR Project



Computer Systems  
And  
Support

## Staff

---

Dean Willis  
Emily Lybarger  
John Lybarger

# Systems Support Functions

- Selection, Acquisition, and Maintenance of Computing Facilities.
- Security of Systems and Data, including:
  - Physical Security (Locks)
  - Logical Security (Passwords)
  - Archival Security (Backups)
- Consulting for Feasibility, Planning, and Development Issues.

# Review from Last Meeting

## LoanSTAR Computing Resources

**UNIX Systems:** AV-4000 Server  
2 Diskless Workstations  
2 X-Window Terminals  
1.5 Gigabytes Disk Storage  
Streaming Cartridge Tape

---

**PC-DOS Systems:** 22 Project Computers  
13 In-Kind TAMU Computers

**Output Devices:** 5 TAMU In-Kind Laser Printers  
7 Asst. Project Printers  
10 Asst. TAMU In-Kind Printers  
Multi-Pen Plotter

# LoanSTAR Computing Resources

**UNIX Systems:** AV-4000 Server, 32 Mb R.A.M., 32 Ordered  
2 Diskless AV-300 Monochrome Stations, 24Mb RAM  
1.5 Gb Disk, 1 Gb Ordered

---


1 AV-310C Color Station, 24 Mb RAM, 334 Mb Disk (Ordered)  
2 Monochrome X Terminals  
1 Color X Terminal (Ordered)  
1 PC UNIX System (Ordered)

**PC-DOS Systems:** 25 Project Computers  
16 In-Kind TAMU Computers

**Output:** 5 TAMU In-Kind Laser Printers  
3 Project Laser Printers  
1 Project Color Printer  
1 Project Color Plotter  
6 Other Project Printers  
10 TAMU In-Kind Printers

**Input:** Logitech Hand Scanner  
AT&T 200 DPI Scanner  
Epson 300 DPI Color Scanner

# UNIX Server



Data General AV-4000

Dual Motorola 88000 RISC CPU

16 Mhz Clock Speed

32 MB RAM (Upgrade on Order)

1.5 Gb Disk (Upgrade on Order)



32 MIPS Performance

Symmetric Multiprocessing

DG/UX UNIX Operating System



# UNIX Workstations



Data General AV-300

Motorola 88100 RISC CPU

16Mhz Clock Speed

24Mb RAM

0 to 334Mb Disk

16 MIPS Performance


1280 by 1024 Graphics

DG/UX UNIX Operating System

MIT X Window System v11

OSF/Motif User Interface

# X Terminals



Run Jobs On Server

Remove User I/O from Server

1024 by 1024 Graphics

Connect to Variety of Hosts


Require Minimal Support

MIT X Window System v11

OSF/Motif User Interface

\$1,800 to \$2,500

# Personal Computers



Intel 8088, 286, 386SX, 386, 486 CPUs

4.77 to 33 MHz Clock Speeds

640kb to 8Mb RAM


20 to 200 Mb Disk

640 x 200 x 2 to 1024 x 768 x 256 Graphics


MS-DOS 4.01 and 5.0

Windows 3.0a

\$1,500 to \$4,000 each



# Logical Network Structure



# Commercial Software Systems

<b>User Interface:</b>	Microsoft Windows on PC OSF/Motif on UNIX
<b>Word Processing:</b>	Windows Word on PC Framemaker and TeX on UNIX
<b>Analysis:</b>	Microsoft Excel on PC Quatro Pro on PC Lotus 1-2-3 on PC
	Voyager on PC SC Spreadsheet on UNIX SAS on PC and UNIX
<b>Graphics:</b>	Grapher/Surfer on PCs Corel Draw on PCs Intek 3D on PC XGraph on UNIX
<b>Database:</b>	Reflex and Paradox on PC Informix SE on UNIX (Ordered)

# Future Plans

- High-Capacity Backup -- 4mm or 8mm
- 
- Read/Write Optical Disk Drives
  - Wingz Graphical Spreadsheet on UNIX
  - More Extensive use of NetWare for PCs

# **Texas LoanSTAR Monitoring and Analysis Program**

## **Technical Support Data Acquisition and Storage**

Submitted by:

Robert E. López  
Vandana Jagannathan  
Jinrong Wang

Energy Systems Laboratory  
Mechanical Engineering  
Texas A&M University  
College Station, Texas

August 1991




# **Texas LoanSTAR Project Data Acquisition and Storage**

## **Primary Responsibilities:**

- **Data Collection/Polling LoanSTAR sites**
- **Processing and Archiving of Data**
- **Data Quality Control**
- **Report Generation**
- **Data Release**

# Data Collection Overview



## Weekly Collection:

### LoanSTAR sites

January 1991	28
August 1991	47

### LoanSTAR channels

January 1991	532
August 1991	717

### Kilobytes collected each week

January 1991	844
August 1991	1,209

### National Weather Service data

1,217 kilobytes each week

*Total weekly collection: 2,426 kbytes*

# Texas LoanSTAR Project

## Data Acquisition and Storage

### Time Requirements:


#### Weekly

- Data Collection/Polling 47 LoanSTAR sites  
*6 hours per week*
  - Processing and Archiving of Data  
*8 hours per week*
  - Data Quality Control  
*15 hours per week*
- 

#### Monthly


- Report Generation  
*120 - 160 hours per month*
- Data Release  
*10 - 20 hours per month*

# LoanSTAR Data Management



# Weekly Quality Control Inspection Plot Notebook

- Weekly time series plot of every channel at every LoanSTAR site.
- Derived summary page for each site.
  - + Time series of whole building electricity consumption.
  - + Time series of submetered electricity consumption.
  - + Time series of chilled water usage and hot water usage.
  - + Scatterplots of thermal energy consumption vs. O/A temp.
  - + Time series of local weather (dry bulb, RH, solar).
- New plots placed in a notebook (by site) and circulated between the Principal Investigators and staff. The plots are reviewed and any problems identified.



# Monthly Report Generation

## Monthly Energy Consumption Report

Every accepted LoanSTAR site receives a 6 page report each month.

<b>Zachry Engineering Center</b> Texas A&M University 324,400 square feet	
<u>Site Contact</u> Mr. Charles Darnell, Jr. Physical Plant Administration Texas A&M University (409)-845-5318 Gene Stewart (409)-845-5511	<u>LoanSTAR Contact</u> Mohsen Farzad or Aamer Athar 053 WERC Texas A&M University College Station, TX 77842-3123 (409)-845-8213

Summary of Energy Consumption				
	Measured Use	% hours reported	Unit Cost	Estimated Cost
Electricity	661201 kWh	97.8	-	-
Peak 60 Minute Demand	1223 kW	97.8	-	-
Chilled Water	1953.0 MMBtu	97.8	-	-
Hot Water	135.5 MMBtu	41.7	-	-
Peak 60 minute demand was recorded at 1500 Friday 5/3/91. There were 744 hours in this month.				

Measured Monthly Savings	
Actual	Predicted
\$25,500	\$-

**Comments**

★ Hot water data is missing for 5/11-5/28 and chilled water data appears abnormal for 5/10-5/23 apparently due to construction activity.

★ Measured "savings" are partly attributable to the construction activity.

# Monthly Report Generation

## Monthly Energy Consumption Report

Production of this report requires *120 man-hours* to complete the first draft. Currently, this consists of two people working full time for a week and a half.

This time includes:

- Concatenation of the weekly files into one summary dataset for the month.
- Creation of daily total files from the monthly data.
- Production of the graphs which appear on pages 2-4 occurs on a PC. Production of the graphs on page 5 is accomplished by SAS on the UNIX file server.
- Postscript output from the PC is transferred over the campus network to the UNIX file server.
- Creation of reports by knitting together the Postscript output into a T<sub>E</sub>X framework.

The first draft is circulated to the Principal Investigators and staff of Tasks 4 - 5. Comments for page 1 are discussed and any presentation or data problems are identified.

A second draft with an initial set of comments on page 1 is circulated.

The final draft is mailed to participating agencies.

The whole process generally takes two weeks.

# **Texas LoanSTAR Project Data Acquisition and Storage**

## **Future Directions:**

- **Maintenance of data within an Integrated Relational Database Management System.**
- **Automation of the polling and processing phases using routines developed by the programming staff.**
- **Maintenance of ARCHIVE's .LOG files with an automated organizer and reporting tool.**
- **Extension of automated quality control to use dynamic ranges rather than static upper and lower bounds.**
- **Continued development of the Inspection Plot Notebook based on comments by the Principal Investigators and staff.**
- **Continued development of the Monthly Energy Consumption Report based on comments by staff and the participating agencies.**



# **Texas LoanSTAR Monitoring and Analysis Program**

## **Technical Support Software Development / Testbench**

Submitted by :

Robert Sparks  
Raghuveer Belur\*  
Souvik Bhattacharyya  
Sugato Chakrabarty  
Murthy Rayaprolu  
Sriram Vadlamani  
Jinrong Wang  
Kristel Weber

\*Funded by DOE-EMCS project

Energy Systems Laboratory  
Mechanical Engineering  
Texas A&M University  
College Station, Texas

August 1991

## **Responsibilities**

### **Programming**


- Software Design, Development and Maintenance
- Source Code Control
- Software Distribution

### **Testbench**


- Evaluating the usability of each vendor's product
- Translating each vendor's communication format to LoanSTAR's standard format
- Rigorous testing of the accuracy of each logger

# Programming Data Acquisition Tools


Weather Data



EMCS




loanstar



Data Format  
Translation Tools



Automatic  
Polling



## **Available for Distribution**

**KWC  
ColRow3D  
ActPre3D  
3DMac  
Air  
023to124  
124to023**

## **Available for Distribution in 1991**


**PredVal  
CR - FourP  
DateTool  
Archive/A&M**

# **Programming Monthly Energy Consumption Report**


Programs have been written to automatically

- Fill in missing records
- Convert multichannel hourly data to daily data
- Merge weather data files with building data files
- Customize Grapher files for each site
- Choose good axis values
- Convert from Gregorian to Decimal Dates
- Create custom SAS programs for each site
- Modify PostScript output from SAS
- Compile all graphs into a single document under the control of TeX






# Testbench Setup



# Digital Test Setup



# Digital Test Results





## Typical Logger Characteristics and Testbench Measurements

Manufacturer	A	B	C	D	E	F	G	H	I
Maximum Pulse Channels	16	8	4	4	4	4	8	4	14
Maximum Analog Channels	15	none	16	4	none	none	32	none	14
Analog Type <sup>1</sup>	V,R,C	none	V	V	none	none	V,R,C	none	V
Maximum Memory	32K	128K	40K	256K	48K	64K	512K	64K	512K
Communications Protocol <sup>2</sup>	P	P	D	P	P	P	D	P	D

<sup>1</sup>V = voltage, R = resistance, C = current

<sup>2</sup>P = Proprietary, D = public Domain

Manufacturer	Min <sup>3</sup> On Time	Min <sup>3</sup> Off Time	Max Square Frequency	Triggering Event	Pullup	Trigger Current
A	30/40	15/40	16.7Hz	closure	4.5V 3mA	2.3mA
B	32/100	35/100	14.3Hz	transition	13.9V 7.3mA	-
C <sup>4</sup>	-/3	-/4	125Hz	opening	1.8V 47uA	20.5uA
E	26/30	27/30	18.5Hz	transition	10.4V 3.8mA	.5mA,3mA <sup>5</sup>
F	81/80	83/80	6Hz	opening	20.7V 11.8mA	1.58mA
H	27/30	27/30	18.5Hz	closure	17.5V 23.75mA	8.5mA

<sup>3</sup>Observed/Manufacturer's published specifications

<sup>4</sup>Logger performs correctly to the limit of our abilities to test it

<sup>5</sup>Input exhibits hysteresis

## **Future Directions**

### **Programming**

Conversion to Relational Database

PolIC180

SCCM

Generic Missing

Generic Interval Conversion

Pattern Recognition for Data Quality Control

### **Testbench**

Complete Analog Tests

Finalize Reports

**Texas LoanSTAR  
Monitoring and Analysis Program**

**Task 4  
Communications Testbench,  
& Technical Support**

**Summary - Progress Report**

Jeff S. Haberl PI  
Robert Sparks  
Rob Lopez  
Dean Willis  
Kristel Weber  
Souvik Bhattacharyya  
Sugato Chakrabarty  
Murthy Rayaprolu  
Sriram Vadlamani  
Jinrong Wang  
John & Emily Hogg

**August 1991**

## **TASK 4 - RESPONSIBILITIES**

- > Ensure that the LoanSTAR MAP Net can communicate with the instrumentation installed in each building.
- > Develop procedures for verifying the accuracy of the data acquisition systems to be used in the program.
- > Develop public domain software for communicating with selected data acquisition systems.
- > Develop procedures to test the accuracy of the data being collected by the data acquisition systems.
- > Develop and implement a data base structure for efficiently analyzing LoanSTAR data.
- > Archive and distribute LoanSTAR data, data products, and data processing procedures.

# **Data Gathering Progress (since July 1990)**

## **July 1990**

3 sites

1 weather station

## **January 1991**

28 agencies

75 weather stations

## **August 1991**

47 sites

50+ weather stations

# Communications Testbench Progress

- > **Digital Tests Nearing Completion for:**
  - Automated Measurements (Datrex)
  - Campbell Scientific
  - GfE Energy Management
  - Gulton Industries (Rustrak)
  - Lambert Engineering
  - Landis & Gyr
  - Process Systems
  - Slumberger Industries
  - Synergistics Control Systems
  
- > **Analog testbench Established and Underway.**
  
- > **DRUMS - PollC180 Prototype working**
  
- > **Final Reports to be Completed in Fall 1991.**
  
- > **Communications Testbench to Sunset in Fall 1991.**

# Technical Support Progress

## January 1991

1 Unix Server  
4 Unix  
1.5 GBytes  
22 LoanSTAR PCs  
13 In-kind PCs

## August 1991

1 Unix Server  
4 Unix (1 ordered)  
1.5 GBytes (1 ordered)  
25 LoanSTAR PCs  
16 In-kind PCs

# **LoanSTAR Data Gathering from Energy Management & Control Systems (Cofunded by USDOE) (Joint effort with LBL)**

## **Basic Motivation:**

Why install dedicated data loggers if EMCSs can be used to gather data?

## **Pros:**

- > Use of an existing EMCSs might save monitoring money.
- > EMCSs as Energy Retrofits might save monitoring money.

## **Cons:**


- > EMCSs are often proprietary.
- > EMCS data might not be in the right format.
- > LoanSTAR personnel had no experience w/ EMCSs.



## **LoanSTAR Progress with EMCS Effort: (Joint Effort w/ LBL)**


- > 4 sites selected  
(TT, PVAM, TAMU, USDOE)
- > Working closely with 3 EMCS  
Companies (Honeywell, JCI, L&G,P).
- > Established prototypes with all three  
Companies.
- > Draft Report underway.

# Example: Texas Tech (Honeywell)












# Texas Tech Data Processing Stream (Flowchart)


Data from the HONEYWELL DELTA 1000 EMCS is converted into a DIF format by the Energy Auditor Software.



# LoanSTAR Inspection Plot for Texas Tech



Texas A&M University  
Energy Systems Laboratory  
INTERNAL DISTRIBUTION  
ONLY



## **LoanSTAR Progress with EMCS Effort: (Joint Effort w/ LBL)**

### **Value to LoanSTAR:**

- > EMCSs can be used to monitor building energy usage data.
- > 3 EMCSs have been prototyped to "feed" into the LoanSTAR format.
- > In certain cases EMCSs may be a cost effective monitoring solution.
- > Each EMCS must be considered separately for unique problems.

## **TASK 2**

# **BUILDING MONITORING ON THE LoanSTAR PROJECT: AGENCY UPDATE**

**DENNIS O'NEAL  
JOHN BRYANT  
KEITH BOLES**

**ENERGY SYSTEMS LABORATORY  
TEXAS A&M UNIVERSITY**

# **ADMINISTRATIVE CHANGES**

- **MEET WITH TASK 5 PRIOR TO INITIAL SITE VISIT**
- **ISSUE AMENDMENT FOR SITE TO DASS EARLY  
IN LOAN CYCLE**
- **ADOPTED FORMAL PROCEDURE TO TRACK SITE  
METERING PROBLEMS**
- **EMPLOYED ADDITIONAL TASK 2 ENGINEER**

## **METERING PROJECTS MAY BE CATEGORIZED AS:**

- **COMPLETED - ONLINE AND COLLECTING DATA**
- **UNDER CONSTRUCTION - SOME DEGREE OF  
COMPLETION**
- **NEW SITE - INITIAL VISIT COMPLETED**



# COMPLETED SITES

<b>SITE</b>	<b># BLDGS</b>	<b># POINTS</b>
<b>Texas A&amp;M - ZEC</b>	<b>1</b>	<b>44</b>
<b>Capitol Complex</b>	<b>10</b>	<b>99</b>
<b>U.T. Austin</b>	<b>11</b>	<b>110</b>
<b>UTHSC - School of Health</b>	<b>1</b>	<b>11</b>
<b>UTHSC - San Antonio</b>	<b>2</b>	<b>12</b>
<b>Texas Dept. of Health</b>	<b>5</b>	<b>20</b>
<b>SP&amp;GSC - Winters Complex</b>	<b>1</b>	<b>3</b>
<b>U.T. Arlington</b>	<b>3</b>	<b>44</b>
<b>Victoria I.S.D.</b>	<b>2</b>	<b>11</b>

# UNDER CONSTRUCTION

<b>SITE</b>	<b># BLDGS</b>	<b># POINTS</b>	
<b>UTHSC - HOUSTON</b>	<b>1</b>	<b>58</b>	<b>95%</b>
<b>M.D. ANDERSON</b>	<b>1</b>	<b>48</b>	<b>95%</b>
<b>TEXAS TECH HSC</b>	<b>1</b>	<b>14</b>	<b>95%</b>
<b>U.T. MEDICAL BRANCH</b>	<b>5</b>	<b>21</b>	<b>80%</b>
<b>TEXAS A&amp;M GALVESTON</b>	<b>4</b>	<b>6</b>	<b>15%</b>
<b>U.T. PAN AMERICAN</b>	<b>1</b>	<b>5</b>	<b>95%</b>
<b>S.W. TEXAS STATE U.</b>	<b>7</b>	<b>14</b>	<b>15%</b>
<b>TEXAS COLLEGE OF OSTEPATHIC MEDICINE</b>	<b>3</b>	<b>3</b>	<b>60%</b>
<b>U.T. DALLAS</b>	<b>3</b>	<b>3</b>	<b>30%</b>
<b>FT. WORTH I.S.D</b>	<b>2</b>	<b>9</b>	<b>60%</b>
<b>TEXAS STATE TECHNICAL INSTITUTE</b>	<b>6</b>	<b>16</b>	<b>25%</b>
<b>CORPUS CHRISTI Jr. COLLEGE</b>	<b>1</b>	<b>13</b>	<b>25%</b>

# NEW SITES

<b>SITE</b>	<b># BLDGS</b>	<b># POINTS</b>
<b>U.T. ARLINGTON</b>	<b>5</b>	<b>40</b>
<b>DALLAS COUNTY</b>	<b>2</b>	<b>15</b>
<b>MIDLAND COUNTY</b>	<b>1</b>	<b>3</b>

# **FUTURE PLANS**

- **COORDINATE PRESENT/FUTURE METERING WITH DESIGN CONSULTANTS**
- **WORK CLOSELY WITH TASK 3 CALIBRATION FACILITY**

## **TASK 2**

# **BUILDING MONITORING ON THE LoanSTAR PROJECT: LESSONS LEARNED**

**DENNIS O'NEAL  
JOHN BRYANT  
KEITH BOLES**

**ENERGY SYSTEMS LABORATORY  
TEXAS A&M UNIVERSITY**

**THE LESSONS LEARNED OVER THE  
PAST TWO YEARS CAN BE SPLIT  
INTO FOUR GENERAL CATEGORIES**

- **INSTRUMENTATION**
- **INSTALLATION**
- **MAINTENANCE**
- **ADMINISTRATION**

## **LESSONS LEARNED: INSTRUMENTATION**

- **A BTU METER MAY PICK UP 60 HZ NOISE FROM THE NOISY SURROUNDINGS.**
- **TWO DIFFERENT BRANDS OF THERMAL ENERGY METERS MOST LIKELY WILL NOT AGREE WITH EACH OTHER.**
- **A BTU METER THAT IS NOT FIELD SCALEABLE MAY BE SET WRONG AT THE FACTORY.**
- **THE MARKED POLARITY OF A CURRENT TRANSFORMER MAY BE OPPOSITE OF ITS ACTUAL POLARITY.**
- **THE OUTPUT OF A CURRENT TRANSFORMER MAY BE FAR DIFFERENT FROM ITS RATING.**

**LESSONS LEARNED:  
INSTRUMENTATION  
(CONTINUED....)**

- **SOME RELATIVE HUMIDITY SENSORS ARE TEMPERATURE DEPENDENT**
- **RELATIVE HUMIDITY INSTRUMENTATION MAY FAIL TO PERFORM ADEQUATELY AFTER ONLY A FEW MONTHS OF OPERATION**
- **THE DATA LOGGER MANUFACTURER WILL NOT TELL YOU ABOUT AN UNDOCUMENTED CALIBRATION PROCEDURE FOR HIS DATA LOGGER UNTIL YOU ASK.**



## **LESSONS LEARNED: INSTALLATION**

- **THE FLOW RATE IN A PIPE MAY BE OUTSIDE THE USEFUL RANGE OF THE FLOW METER.**
- **ASBESTOS INSULATION MAY BE ON THE PIPING WHERE THE THERMAL METERING INSTRUMENTATION IS TO BE INSTALLED.**
- **THE CONTRACTOR MAY NOT COMPENSATE FOR THE LEAD LENGTH WHEN RTDs ARE INSTALLED.**
- **THE DIAMETER OF THE PIPE IN WHICH THE FLOW METER IS INSTALLED MAY BE DIFFERENT FROM THAT TOLD YOU BY THE FACILITY MANAGER OR INDICATED BY THE SCHEMATICS.**
- **IF A TEMPERATURE PROBE CAN BE REACHED BY A PERSON FROM THE FLOOR, THE PROBE WILL BE USED AS A CHIN-UP BAR, STEP LADDER, OR SOME OTHER AIDE.**

## **LESSONS LEARNED: INSTALLATION (CONTINUED....)**

- **IF A TEMPERATURE PROBE IS NO LONGER FUNCTIONING, IT MAY BE BECAUSE IT NO LONGER EXISTS.**
- **IF MULTIPLE VOLTAGES ARE AVAILABLE IN THE BUILDING, THEN THE POTENTIAL TRANSDUCER MAY BE CONNECTED TO THE WRONG REFERENCE VOLTAGE.**
- **IF CTs ARE CONNECTED TO A SECONDARY LINE, THEN THEY PROBABLY WILL NOT BE SCALED CORRECTLY.**
- **DATA ACQUISITION BOARDS ON A DATA LOGGER CAN SUBSTITUTE AS EXPENSIVE FUSES.**

**LESSONS LEARNED:  
INSTALLATION  
(CONTINUED....)**

- **THE DATA LOGGER PROBABLY WILL NOT BE PROGRAMMED CORRECTLY WHEN DATA COLLECTION FIRST BEGINS.**

## **LESSONS LEARNED: MAINTENANCE**

**GENERAL RULE: EXPECT THE INSTRUMENTATION TO FAIL AT SOME POINT IN THE PROGRAM.**

- **MODEMS**
- **INSERTION FLOW METERS**
- **CURRENT TRANSFORMERS**
- **ASPIRATING FAN**
- **BATTERY**

## **LESSONS LEARNED: ADMINISTRATION**

- **EXPECT DELIVERY TIMES ON INSTRUMENTATION AND EQUIPMENT TO BE 30 TO 45 DAYS LONGER THAN EXPECTED.**
- **COORDINATE WITH LOCAL UTILITIES AS EARLY AS POSSIBLE.**
- **DEVELOP A NOTEBOOK FOR EACH SITE TO DOCUMENT INSTALLED MONITORING SYSTEM.**
- **DEVELOP TIGHT DEADLINES FOR THE INSTALLATION COMPLETION AND A THOROUGH CHECKOUT PROCEDURE.**
- **COORDINATE WITH HOST AGENCY FOR SMOOTH INSTALLATION AND MAINTENANCE.**

**LESSONS LEARNED:  
ADMINISTRATION  
(Continued....)**

- **COMMUNICATE WITH THE RETROFIT CONTRACTOR OR EXPECT SOME DESTRUCTION OF YOUR MONITORING EQUIPMENT.**

CALIBRATION LABORATORY

TASK 3 - CALIBRATION LABORATORY

PERSONNEL: DAN TURNER, PI  
DENNIS O'NEAL  
JEFF HABERL  
MELVIN GLASS, PE  
CLINT FINSTAD  
FRANK SCOTT  
DON COONROD

## TASK 3

### Purpose

**To support the field monitoring program and the and the communications subsystems task**

- **trouble shoot sensors with problems in field**
- **provide facility to test new sensors and/or systems prior to field installation**
- **help develop metering system acceptance procedures**
- **develop portable calibration capability**



**CALIBRATION LABORATORY**  
at the Texas A&M  
Energy Systems Laboratory

**TEMPERATURE**

(-40F to +500F)

**HUMIDITY**

(10 to 90% RH)

**HYDRAULIC PRESSURE**

(0 to 500 PSI)

**AIR PRESSURE**

(0 to 24 in.W.G.)

**LIQUID FLOW**

(1 to 650 GPM)

**AIR FLOW**

(0 to 10 in.W.G.)  
(0 to 8,000 CFM)

**ELECTRICAL**

(120-480VAC, 0-200A)  
(0-40,000 W, 0-100%PF)

**LIGHTING**

(1 to 10,000 fc)

**ROTATIONAL SPEED**

(0 to 3,600 RPM)

**SOLAR**

(1 to 2,000 W/M<sup>2</sup>)




FIGURE CALIBRATION FACILITY LAYOUT

FIGURE 3 - Typical Temperature-Humidity Test for Nominal 80%

Relative Humidity Test





Figure 2 - Tangential Paddlewheel in a 6" Pipe



## FUTURE PLANS

- ° Automatic data collection, using two (2) C-180's for data collection
- ° Expand flow loop to add 8" & 10" pipe sizes and increase the capacity to 1200 gpm
- ° Complete the lighting/illumination station
- ° Install new instrumentation for electrical test stand
- ° Develop portable calibration procedures and kit for field checkout
- ° Develop detailed test procedures for each station

# **Texas LoanSTAR Monitoring and Analysis Program**

## **Flowmeter Calibration**


### **Progress Report**

Jeff S. Haberl  
W.Dan Turner  
Mel Glass  
Clint Finstad  
Frank Scott


Don Coonrod  
Coonrod Manufacturing & Services

August 1991

# Importance of liquid flow measurement: (whole-building thermal meas.)




# Liquid Flow Loop Diagram







# Liquid Flow Loop Electronics



# Example Real Time Display



# Insertion-type Paddlewheel Flowmeter




***Preliminary***  
**Depth of Insertion Test Results**  
**(Table)**

Flow Trial	Load Cells Flow	Load Cells Sdev/Flow	Doppler Flow	Doppler Sdev/Flow	Paddle Flow	Paddle Sdev/Flow	Reynolds Number
5	55	8.2%	*	*	.00089 **	306.4%	30,000
1	1.14	6.4%	1.02	29.4%	1.83	4.0%	62,500
2	2.34	3.0%	2.08	11.7%	2.97	2.3%	128,200
3	3.38	3.8%	3.11	6.9%	3.9	3.1%	184,800
4	4.15	3.1%	4.23	4.1%	4.39	2.7%	227,200
5	5.08	2.8%	5.26	2.8%	5.09	3.5%	277,900
6	6.18	2.6%	6.38	2.4%	6.04	2.2%	338,200
7	7.01	2.2%	6.92	7.7%	6.75	1.9%	383,600
8	8.11	3.1%	7.34	8.0%	7.49	2.8%	444,000
9	9.06	3.3%	8.42	2.9%	8.24	3.1%	495,900
10	9.99	3.9%	8.92	13.0%	9.10	3.6%	546,700


**NOTE:**

- (\*) The Doppler flow meter was unavailable for this trial.
- (\*\*) The paddlewheel appeared to stop rotating at this low velocity.

# *Preliminary* Depth of Insertion Test Results (Graphs)



# *Preliminary* Impact on LoanSTAR Sites



- > Tangential paddlewheels appear to be a cost effective metering technology for  $> 3$  fps flow regime.
- > LoanSTAR sites with  $> 3$  fps should not be significantly effected by the new constants.
- > LoanSTAR sites with  $< 3$  fps should increase the savings from variable speed retrofits.
- > Other monitoring with old meter constants should consider issuing new meter constants.

# Liquid Flow Calibration

## Future Work.

- > Develop LoanSTAR meter constants (6, 8, 10, 12" pipes).
- > Adjust historical data.
- > Reissue new constants for existing meters.
- > Investigate alternative metering technologies for low flow velocities (1/2 to 3 fps).
- > Recalibrate LoanSTAR flowmeters.

**TASK 1. AUDIT REVIEW AND ASSIGNMENTS**

**PROGRESS REPORT**

**Warren M. Heffington, P.E.**

**Staff Engineers**

**Angela Britton  
Doug Tiner, P.E.  
Darin Nutter  
Aamer Athar**

**Graduate Students**

**Norman Muraya  
Niranjana Hiras  
S. Thamilseran  
Ben Nuboer (Mansoor Parvaiz)**



## TASK 1. AUDIT REVIEW AND ASSIGNMENTS

### AUDITS RESULTS

(All values except simple paybacks are millions.)

	Building Area Audited (SF)	Invest. Cost (\$)	ECRMs Annual Savings (\$/yr)	Simple Payback (yr)	Invest. Cost (\$)	M&Os Annual Savings (\$/yr)	Invest. Cost (\$)	Combined Annual Savings (\$/yr)	Simple Payback (yr)
TECCP <sup>1</sup>	35.3	42.8	19.9	2.2	0.1	1.4	42.9	21.3	2.0
LoanSTAR <sup>2</sup>	17.4	24.8	7.2	3.4	neg	0.1	24.8	7.3	3.4
Total	52.7	67.6	27.1	2.5	0.1	1.5	67.7	28.6	2.4

<sup>1</sup> TECCP - Texas Energy Cost Containment Program, 1984 and 1986.

<sup>2</sup> LoanSTAR - January 1989 - July 1991.

## **TASK 1. AUDIT REVIEW AND ASSIGNMENTS**

**TABLE 3**

### **ENERGY CONSERVATION IDENTIFIED IN LOANSTAR AUDITS**

<b>Purchased Utility Category</b>	<b>Site Energy Savings</b>	<b>Source* Energy Savings (million Btu/yr)</b>	<b>Fractional Source Energy Savings (%)</b>
Electricity	136,186,131 (kWh/yr)	1,579,759	64
Natural Gas	605,448 (MCF/yr)	623,611	25
Steam/Hot Water	93,456 (million Btu/yr)	124,608	5
Chilled Water	12,932,192 (Ton-hr/yr)	155,186	6
<b>Total</b>		<b>2,483,165</b>	<b>100</b>

\* Btu savings calculated on the basis of 11,600 Btu/kWh, 1,030,000 Btu/MCF, and 12,000 Btu/ton-hr.

## **TASK 1. AUDIT REVIEW AND ASSIGNMENTS**

**TABLE 4**

### **SUMMARY OF ECRM's FOR BUILDINGS RECEIVING LOANSTAR AUDITS**

<b>ECRM Recommendations</b>	<b>Implementation Cost (million dollars)</b>	<b>Fractional Implementation Cost (%)</b>	<b>Annual Cost Savings* (million dollars)</b>	<b>Fractional Cost Savings (%)</b>	<b>Simple Payback (Years)</b>
Lighting Retrofits	8.6	33	2.7	35	3.1
Chiller & CHW Retrofits	4.3	17	0.9	11	4.9
Motor/VSD/VSP Conversion	3.3	13	1.0	13	3.3
HVAC System Retrofits	3.1	12	0.8	11	3.6
Others	2.3	9	0.7	9	3.3
EMC Systems	2.1	8	0.5	7	3.9
Boiler & Steam Retrofits	1.4	5	1.0	12	1.5
Pumping System Retrofits	0.8	3	0.2	2	4.8
<b>Total</b>	<b>25.9</b>	<b>100</b>	<b>7.8</b>	<b>100</b>	<b>3.3</b>

\* Independent values.

# **TASK 1. AUDIT REVIEW AND ASSIGNMENTS**

**TABLE 5**

**TOTAL ENERGY CONSUMPTION, UTILITY COST AND SAVINGS. ENERGY AND COST VALUES ARE IN MILLIONS OF UNITS.**

	Electrical kwh/yr	Natural Gas MCF/yr	Steam Btu/yr	Chilled Water Ton-hr/yr	Other Btu/yr	Total Source Energy Btu/yr	Total Utility Cost \$/yr
Consumption	562	2.08	486,000	68.3	3,165	9,970,000	46.2
Savings (%)	24	29	19	19	--	25	16

**TABLE 6**

**FRACTIONAL COMPARISON OF SOURCE ENERGY TYPES AND COST**

	Consumption (%)	Cost (%)
Electricity	65.4	66.7
Natural Gas	21.5	14
Chilled Water	8.2	11.5
Steam	4.9	7.8
Other	<0.1	<0.1

# TASK 1. AUDIT REVIEW AND ASSIGNMENTS

## COST OF AUDITS

- **1986 TECCP**

**COST - \$0.050/SF**

<b>TYPICAL BLDG. AREA FRACTION</b>	<b>- 63%</b>
<b>COMPLEX BLDG. AREA FRACTION</b>	<b>- 37%</b>
<b>FRACTION OF IMPL. COST</b>	<b>- 3%</b>
<b>FRACTION OF ANNUAL SAVINGS</b>	<b>- 7%</b>

- **LOANSTAR**

**COST - \$0.081/SF**

<b>SIMPLE BLDG. AREA FRACTION</b>	<b>- 8%</b>
<b>TYPICAL BLDG. AREA FRACTION</b>	<b>- 83%</b>
<b>COMPLEX BLDG. AREA FRACTION</b>	<b>- 9%</b>
<b>FRACTION OF IMPL. COST</b>	<b>- 6%</b>
<b>FRACTION OF ANNUAL SAVINGS</b>	<b>- 21%</b>

- **BLDG. TYPES**


**SIMPLE - WAREHOUSES, GYMS, PKG.  
GARAGES**

**TYPICAL - OFFICES, CLASSROOMS**

**COMPLEX - MEDICAL FACILITIES, PHYSICAL  
PLANTS**

# TASK 1. AUDIT REVIEW AND ASSIGNMENTS

**Figure 1. Audit Cost as a Function of Building Size.**  
The data points are for the 38 LoanSTAR reports with available audit cost data (January 1989 - July 1991).



## **TASK 1. AUDIT REVIEW AND ASSIGNMENTS**

### **CHANGES IN THE AUDIT PROCESS**

- **ELIMINATE M&Os.**
- **ELIMINATE INDEPENDENT CALCULATIONS OF ECRMs.**
- **PROVIDE FOR DIFFERING LEVELS OF ECRMs:**
  - **CAT 1 - "DIPSTICK" - BASED ON EQUIPMENT QUANTITY ESTIMATES AND HISTORICAL PAYBACKS.**
  - **CAT 2 - SIMP CALC - SPREADSHEET CALCULATIONS DEVELOPED UNDER CONTRACT TO GEO.**
  - **CAT 3 - PRESENT ECRMs.**

## **TASK 1. AUDIT REVIEW AND ASSIGNMENTS**

**TABLE 8**


### **PROPOSED CATEGORY I ECRMs AND HISTORICAL PAYBACKS**

<b>ECRM</b>	<b>Payback (Years)</b>
Delamping	1
Repair Steam Traps	2
Photocells on Exterior Lights	3
Time Clock Shut Down of Equipment	3
Incandescent to H.P. Sodium	4
Incandescent to Screw-in Fluorescent	2
Energy-Efficient Fluorescent Lamps	2



## Advanced Customer Technology Test for Maximum Energy Efficiency

### Project Overview



Project Overview for the  
LoanSTAR Monitoring and Advisory Review Committee  
August 20, 1991  
Austin, TX  
Presented by Merwin Brown, PG&E R&D

### Summary

- The Advanced Customer Technology Test (ACT<sup>2</sup>) for Maximum Energy Efficiency project is a major R&D program of field experiments. The purpose of ACT<sup>2</sup> is to scientifically test the hypothesis, proposed by many energy efficiency experts and environmentalists, that substantial energy efficiency improvements can be achieved among utility customers at costs competitive with supply. The strategy of ACT<sup>2</sup> is to demonstrate in selected customers' businesses and homes integrated packages of modern end-use technologies optimized for maximum energy efficiency. A significant benefit of ACT<sup>2</sup> will be a scientific characterization of the cost-effective maximum potential for end-use energy efficiency technology.
- One of many unique features of this project is the high-level steering committee that provides overall guidance and review for the design and conduct of the field tests. It is composed of representatives of Lawrence Berkeley Laboratory, Natural Resources Defense Council, Rocky Mountain Institute, and PG&E. Other national and international environmental and energy efficiency experts provide advice and review on an ad hoc basis. The Internal Review Committee, composed of representatives from the various PG&E departments involved in customer energy efficiency, provides Company perspective, advice and review for overall project management and scope.
- PG&E is the project manager of this multi-year effort, and is providing the initial three years of funding of \$10 million. These funds will be used to install the energy-saving packages in a number of residential, commercial, industrial, and agricultural sites to be made available by qualifying PG&E customers willing to serve as hosts for the tests.

6/19/91

## PG&E's Commitment to Environmental Quality: *"A Cleaner, Healthier Environment"*




- Increase customer **energy efficiency**
- Rely on **energy efficiency** as a resource




- **The Commitment: "Cleaner, healthier environment"**
  - Conduct business in environmentally sensitive manner
  - Sound environmental policy and sound business practice go hand in hand
  - Pursue both for benefit of customers, shareholders, employees, and communities PG&E serves

- **Elements of the Commitment Related to ACT<sup>2</sup>**

- Customer Efficiency
  - Promote and implement energy efficiency by customers
  - Focus R&D on improving energy efficiency technologies
  - Work with environmental, consumer and other groups to monitor and improve programs
- Electric Resource Plan
  - Place primary reliance on energy efficiency
  - 1650 MW by 2000
- Collaborative
  - Utility earns by sharing savings
  - Provides funding for ACT<sup>2</sup>





Growing concerns in the US about the environment, dependence on imported oil, and global competition have spurred a renewed push for energy efficiency. New energy-saving technologies, like high efficiency lighting, adjustable speed drive motors, modern office equipment and selective coatings on glass, are fostering projections that:

**Substantial energy savings (perhaps as high as 75%) can be achieved in buildings, or industrial and agricultural processes, at economic costs through the use of modern customer end-use technology systems.** One implication is that considerable environmental benefit can be had if the investment associated with supply were expended instead on energy efficiency.

# Project Hypothesis The Formula for High Efficiency




Use modern technologies  
...plus...

Fully characterize the technologies  
...plus...

Don't forget the small savings  
...plus...

Take advantage of synergisms



**Modern Technologies:** Most of the best electricity-saving technologies are less than 1 year old. Using 5-year-old technology results in half the savings at 3 times the costs\*.


**Full Characterization:** Accounting for extra cost savings resulting from the use of some new technologies, provides economic opportunity for additional energy saving measures. For example, many new high efficiency lighting technologies have much longer operating lives leading to significant reductions in lamp replacement costs. These savings can be used to purchase other energy saving improvements.

**Small Savings:** Including many small savings, like improved exit signs and lap top computers, as well as a few big ones often doubles the total savings\*.

**Synergisms:** Detailed, whole-system engineering often reveals multiple benefits from single expenditures, thus reducing severalfold the total costs of integrated retrofit packages\*. For example, new, special glazings can let in light while keeping out the heat, thereby reducing the needs for lighting and space cooling. High efficiency lighting can reduce further the demand for space cooling, resulting in smaller, cheaper HVAC units.


\* Taken from Amory Lovins' "Why Do Assessments of Potential Electric Savings Differ?"

## Project Purpose *Test the Hypothesis*




Projections of substantial energy savings possible from advanced end-use technologies have been substantiated only in part by the performance of individual technologies, in some instances, measured only under laboratory conditions. Little has been done to scientifically field test these advanced technologies as integrated systems designed to maximize energy efficiency in customer buildings or processes, where the effects of component interactions on technical performance, life-cycle economics and customer acceptance can be measured. The purpose of the ACT<sup>2</sup> for Maximum Energy Efficiency project is to test the hypothesis implied in the above projections that **substantial energy savings can be achieved in buildings, or industrial and agricultural processes, at economic costs through the use of modern customer end-use technology systems.**

By conducting this test, the project will attempt to determine the technical potential for energy efficiency in our customers' homes and businesses. This information will help planners to project to what degree the company can rely on energy efficiency to meet load and to contribute to earnings.



- Project Mission:
  - **To provide scientific field test information, for use by PG&E and its customers, on the maximum energy savings possible, at or below projected competitive costs, by using modern high-efficiency end-use technologies in integrated packages acceptable to the customer.**
  - *Scientific field test information means* evaluation of data objectively collected in experiments at customer sites having suitable experimental control. The data will consist of measurements of energy use, economic and technical performance, and observations of user behavior.
  - *For use by PG&E and customers means* of value to PG&E marketing, supply and corporate planners in making DSM strategic decisions and projections, and to customers in making decisions to deploy these technologies. Value to the public at large is also a conditional goal.
  - *Maximum energy savings means* the greatest possible electrical KWhrs and gas therms saved, as compared to a conventional control site, within the economic and acceptance constraints.
  - *Projected competitive costs means* utility life cycle costs that may not now be competitive but can be reasonably shown to have prospects of becoming competitive with utility supply costs.
  - *Modern high-efficiency end-use technologies means* state-of-the-art, high-efficiency lighting, appliances, HVAC, controls, and similar end-use technologies, for the business or home.
  - *Integrated packages means* combinations of end-use technology systems and envelope designed to take advantage of synergisms and characterizations that produce maximum energy savings.
  - *Acceptable to the customer means* no deterioration in health, safety, convenience, comfort, productivity or aesthetics when compared to a control. The new technologies should be "transparent" to the user.



- The project is a **demand-side demonstration**, analogous to a supply-side demonstration, where a package of near-commercial advanced technologies is field tested to determine actual economic and technical performance, and user response.
  - *Demonstrate* by designing and installing, for each selected PG&E customer building or process, an integrated package of modern end-use technologies that maximizes energy savings at projected economic costs, and by testing performance under actual operating customer situations.
  - *Monitor and analyze*:
    - Capital, installation, and operating and maintenance costs.
    - Installation times and techniques
    - Energy use and savings
    - Device and system technical performance
    - User acceptance and site environmental quality
    - Site characteristics
  - *Disseminate results* by using a variety of methods and mediums to report on the evaluation of the data and lessons learned:
    - Written reports
    - Presentations
    - Forums
    - Testimonies
    - Tours
  - *Assure the credibility* of the results and their acceptance by scientific and environmental organizations by involving, as part of the project management team:
    - A top-level steering committee of renowned experts in energy efficient end-use technologies to advise on and review the overall project experimental and technology design.
    - Other national and international technical experts to advise on and review, on an ad hoc basis, the technologies and processes to be used.

# Project Participants

**PG&E**

**LBL**

Pacific Gas & Electric  
Lawrence Berkeley Laboratory  
Natural Resources Defense Council  
Rocky Mountain Institute

**NRDC**

**RMI**



**PG&E:**

Fund and Manage Project  
Serve on Steering Committee  
Carl Weinberg

**LBL:**

Serve on Steering Committee  
Art Rosenfeld  
Perform selected contract tasks

**NRDC:**

Serve on Steering Committee  
Ralph Cavanagh

**RMI:**

Serve on Steering Committee  
Amory Lovins



# Initial Project Budget

**Total = \$10 Million R&D (1990 - 1992)**

## **\$5 Million for demonstrations:**



System design

Purchase, install, commission, operate and monitor energy efficiency measures

## **\$5 Million for program implementation:**



Project planning

Data analysis & evaluation

Information dissemination

Administration



## **Funding**

- \$5 million was obtained by a California Public Utilities Commission (CPUC) resolution, December 18, 1989, that retained for this project a portion of the 1987-1989 R&D balancing account refund.
- Another \$5 million was approved by the CPUC on August 29, 1990, as part of the Customer Energy Efficiency filing.

## **Budget**

- Based on previous experiences with energy efficiency projects, a rule-of-thumb for budgeting has emerged:
  - 50% for demonstration design, installation, commissioning, operation and monitoring, and
  - 50% for project planning, administration, analysis and evaluation, and information dissemination

## Project Deliverables and Benefits

- Information for planning and decision making
- Customer education and encouragement
- New design and measurement techniques
- Lessons learned from practical experience
- Guidance for future R&D



### **Information for planning and decision making**

Provide information to PG&E customers and planners on the technical potential for maximum energy efficiency, and the associated costs, by using modern, advanced end-use technologies.

### **Customer education and encouragement**

Provide examples of modern energy-saving technologies operating successfully at customer sites, to inspire and encourage others to adopt these environmentally beneficial technologies.

### **New design and measurement techniques**

Identify and develop integrated technology packages, and design and measurement techniques, that can maximize end-use energy savings at costs competitive with generation.

### **Lessons learned from practical experience**

Provide hands-on learning about what to do, and what not to do, in designing, installing, commissioning and operating new energy saving technologies. Learn how to measure their performance and impacts. Reveal unforeseen benefits, e.g., improved productivity, and problems, e.g., deterioration of power quality.

### **Guidance for future R&D**

Provide guidance and direction for future energy efficiency R&D by PG&E and others

# Project Committees & Forums

Advise

Review



Inform




## • Advice and Review:

- **Steering Committee:** To guide PG&E, through advice and review, in the design and conduct of the project to help ensure valid results acceptable to scientific and environmental communities. Members, renowned for leadership in energy efficiency, represent the views of those communities.
  - Lawrence Berkeley Laboratory - Art Rosenfeld
  - Natural Resources Defense Council - Ralph Cavanagh
  - Rocky Mountain Institute - Amory Lovins
  - PG&E - Carl Weinberg
- **Internal Review Committee:** To provide Company perspective, advice and review for overall project management and scope. Members are representatives involved in energy customer efficiency from the PG&E business units of Distribution, Electric Supply, ENCON and Gas Supply, and the departments of Corporate Planning and R&D.
- **Technical Advisory Network:** A collection of national and international technical and human behavior experts to provide advice and review technologies on an *ad hoc* basis.


## • Forums to obtain comment and educate:

- **Regulators:** California regulators, NARUC, *etc.*
- **Utilities:** EPRI, GRI, CURC, *etc.*
- **Trade Associations:** ASHRAE, AEE, NEMA, APEM, *etc.*
- *Etc.*


# Project Planning *Learn by Doing*




- INTENT:
  - To provide a "learn-by-doing" experience to guide the development of the project design, technology design methods, and measurement and monitoring techniques.
- APPROACH:
  - Project planning done in parallel to a pilot demonstration
  - Planning responsive to lessons learned in pilot demonstration
- RATIONALE:
  - Need to minimize risk is great:
    - The amount of money - \$ 10 million - in the project is large.
    - Hosts might be adversely affected by big mistakes.
    - Project will be very visible and too many mistakes could hurt future energy efficiency efforts.
  - Pilot Demo gets some hardware into the field early under tightly controlled circumstances.
  - Maximizes chances that the project plan will result in follow-on demos that are properly designed, operated and monitored.



- The Sunset Building is owned by a PG&E customer, but occupied primarily by PG&E employees. It is a typical low-rise, two-story modern commercial office building located in San Ramon, CA. The ACT<sup>2</sup> Project Team is located on the site, and therefore will observe daily the impacts of the pilot demo on the occupants.
- Location: First floor, from east end to fire wall
- Includes most of the PG&E R&D Department
- 21,688 sq. ft.(pilot)/134,400 sq. ft.(total) & 58,000 sq. ft.(conditioned)/42,000 sq. ft. (occupied)
- 374,191 KWh per year(pilot)/1,162,707 KWh per year(total)
- 8,633 therms per year(pilot)/21,512 therms per year(total)
- \$43,721 per year energy costs(pilot)/\$119,681 per year energy costs(total)



# Pilot Demo Evaluation Plan for Measurement and Data Collection



To achieve the mission, three main categories of information need to be obtained;

1. Maximum Energy Savings Possible
  - System KW, KWh, therms
  - Component energy use and efficiency
  - Power factor
  - Site characteristics (weather, etc.)
2. Projected Competitive Costs
  - Actual purchase, installation and O&M costs.
  - Projected costs
3. Customer Acceptance (Occupant Behavior)
  - Surveys on occupant acceptance
  - Indoor air quality
  - Lighting quality
  - Thermal comfort
  - Noise
  - Harmonic generation
  - Operation ease
  - Installation disruptions

# Pilot Demonstration Conceptual Design Challenge







RFP  
Technology Briefing  
Design Presentations  
Design Selection Jury



- ➔ RFQ conceptual design issued
  - ➔ Most qualified firms selected
    - ➔ Firms prepare energy-efficient conceptual designs
    - ➔ Firms present conceptual designs
    - ➔ Jury selects best design, recommends changes
      - ➔ "Winning" firm completes design
      - ➔ RFP for installation issued

## Suggested Follow-On Demonstration Types



	 Residential	 Commercial	 Industrial	 Agricultural
<b>New</b>	Medium Income	Large Office Small Office		
<b>Retrofit</b>	Medium Income Load Survey* Apartment Building	Small Offices with Shops Supermarket	Drive Intensive Gas Intensive	Dairy Irrigation Pumping
*Load survey data has been collected for these homes				

**ACT<sup>2</sup> for Maximum Energy Efficiency**



- Demonstration types shown above were chosen, after consideration of a broad spectrum of PG&E customer segments and types, in order to focus the search for candidate hosts.
- In general these demonstration types were drawn either from customer segments having the most impact on energy demand overall, or having special needs for energy efficiency.
- Both new construction and retrofit demonstrations will be considered:
  - New construction demonstrations can incorporate innovative building designs and capture energy savings opportunities that would otherwise be lost.
  - Retrofit demonstrations represent a larger near term market for energy efficiency technologies than does new construction.
- Candidates will be identified through the corporate divisions, and selected based on the appropriate criteria and after discussions and agreement among all affected parties.





**Texas LoanSTAR  
Monitoring and Analysis Program**

**Task 6  
Improved Energy Audit Process**

**Beginning: Fall 1991**

Jeff S. Haberl

August 1991

# **Improved Energy Audit Process**

## **Objectives:**

1. Investigate use of dipstick audits (DOE/Battelle).
2. Incorporate demand data and other short term monitoring into auditor's work.
3. Investigate use of selected prescreening indices into audit.
4. Begin to use real savings to improve audit process (Task 2-5 Interaction).

# Improved Energy Audit Process

## Benefits:

- > Improves the accuracy and information content of LoanSTAR audits.
- > Improves and lengthens PRE data stream for LoanSTAR sites.
- > Accelerates technology transfer to/from LoanSTAR project to Texas A/Es.